

# Resene Bio-Cleaner

powerful high  
efficiency  
biodegradable  
cleaner

Resene Bio-Cleaner is a quick and easy way to clean surfaces ready for painting or use annually to give homes and buildings a fresh look by washing away dirt and contaminants that may be present. Formulated with eugenol, the active ingredient in clove oil, which helps to inhibit mould and fungal regrowth.

## exterior/interior

### Typical uses

- Painted surfaces

<b>Vehicle type</b>	Blend of anionic and nonionic surfactants
<b>Form</b>	Concentrated solution
<b>Solvent</b>	Water
<b>Viscosity of solution</b>	Water thin
<b>Colour</b>	Pale yellow
<b>Mixing ratio</b>	1 part Resene Bio-Cleaner to 3 parts water
<b>Number of applications</b>	1
<b>Usage (diluted mix)</b>	10-20 sq. metres per litre
<b>VOC</b>	c. 40 grams per litre (see <a href="#">Resene VOC Summary</a> )

### Physical properties

### Performance

1. Provides an immediately cleaner surface.
2. Helps maintain the longevity of the paint finish.
3. Biodegradable; meets the biodegradability criteria of NZ Eco-Labeling document EC-37-16.
4. Contains eugenol (the active ingredient in clove oil), which helps to inhibit mould and fungal regrowth.
5. An Environmental Choice approved product.

### Limitations

1. Do not add Resene Bio-Cleaner to paint.
2. Mild steel and aluminium are attacked by Resene Bio-Cleaner and are unsuitable materials for either storage or application equipment.
3. Ensure product is well rinsed off glass and metal surfaces. Concentrated product left on glass or metal surfaces may etch the surface.

Please ensure the current Data Sheet and Safety Data Sheet are consulted prior to specification or application of Resene products. View Data Sheets online at [www.resene.com/datasheets](http://www.resene.com/datasheets). If in doubt contact Resene.



# Bio-Cleaner powerful biodegradable cleaner

## Application

Wear adequate protection. Use overalls, gloves, eye protection and suitable footwear.

Mix with water and apply by brush, knapsack, garden or conventional spray. Scrub vigorously using a nylon bristle broom or short, hard bristle scrubbing brush to remove all dirt, grease, mould and any loose flaking paint. Rinse with clean water.

Use more concentrated mixes to clean more heavily soiled surfaces.

## Precautions

Do not allow the product to come into contact with plants, stormwater outlets, streams or animals. May kill aquatic life if allowed to enter the stormwater system. Divert all roof runoff to a sewer or alternative catchment system.



Bio-Cleaner SDS

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products. View Data Sheets online at [www.resene.com/datasheets](http://www.resene.com/datasheets). If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

**In Australia**  
PO Box 924, Beenleigh, Qld 4207  
Call 1800 738 383, visit [www.resene.com.au](http://www.resene.com.au)  
or email [advice@resene.com.au](mailto:advice@resene.com.au)

**Resene**  
the paint the professionals use

**In New Zealand**  
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Call 0800 RESENE (737 363), visit [www.resene.co.nz](http://www.resene.co.nz)  
or email [advice@resene.co.nz](mailto:advice@resene.co.nz)

Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001. Please recycle.