

**NB. This chart is from the
Resene historical file.
Please refer to current
Resene colour charts
for the latest colour options**

Resene lumber-sider

ACRYLIC TIMBER FINISH

exterior/interior



The Paint the Professionals use



SOMBRAERO



CHESTNUT



ROWAN



LONGHORN



KAURI



EL RANCHO

Resene lumber-sider ACRYLIC TIMBER FINISH

The stained look in a permanent finish.
Resene Lumber-sider is a new easy way of painting,
producing a smooth natural satin appearance.
Available in 12 earthy today colours.
Use on exterior and interior surfaces.
Pre-primed weatherboards. Timber fences. Sheds. Garden furniture.
Painted timber. Asbestos sidings. Concrete brick and block work.

SPINACH



LARCH



EL PASO



TUMBLE-WEED



MOSS



BRACKEN



Lumber-sider is formulated on a 100% acrylic Resin to ensure maximum durability over all exposure conditions.

Available in 12 earthy today colours.

Lumber-sider can be used on almost all surfaces. New, old, painted or weathered. Weatherboards, natural timber, dressed or rough sawn fences, sheds, garden furniture. Fibrolite sheets

and shadow line. Concrete, brickwork, blockwork, galvanized iron. Lumber-sider should be applied in two coats. Dries in 20 minutes and can be recoated in 2 hours.

APPLICATION:

Normally applied by brush but can also be successfully sprayed or rolled.

Brushes and equipment wash out in water. Should not be applied at temperature below 10°C (50°F).

Under hot conditions it is preferable to work on the shaded side.

For porous surfaces thin with up to one pint of water per gallon.

Resene lumber-sider

ACRYLIC TIMBER FINISH

MANUFACTURED BY
STIPPLECOTE PRODUCTS LIMITED, GOUGH STREET, LOWER HUTT. P.O. BOX 36-006
WELLINGTON · AUCKLAND · CHRISTCHURCH · DUNEDIN

