

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

KEEP OUT OF REACH OF CHILDREN

Resene

Cemseal

concrete sealer and dust coat

waterborne exterior/interior



net contents 4 litres

LL29710048 7/23

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aid officer if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D504.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Cemeal is a non-decorative coating for use on industrial and domestic concrete floors where a low cost, easily applied and maintained method of controlling concrete dusting is required. It is not designed for non-dusting dense glossy concrete floors. May also be used as an exterior concrete sealer under a range of Resene topcoats.

Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- Waterblasting is the best surface preparation prior to coating of weathered cementitious surfaces.
- Oil and grease must be removed using Resene Paint Prep and Housewash. If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry must be treated (see Data Sheet D83).
- All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.
- This product may be used to seal a wide variety of surfaces. If the surface you propose to seal is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

- Apply one full coat of Resene Cemeal.
- Minimise overlap during brush or roller application to avoid lapmarks.
- Allow at least 24 hours before putting the area into full use.
- Take care to avoid excess film build up on top of the surface being coated to ensure best durability and resistance to mechanical damage.
- Must be overcoated if used outside.

Sealer

Resene Cemeal may be used as a sealer over concrete prior to application of selected topcoats.

Recoating

Where Resene Cemeal is being used as a topcoat, reapply the coating annually to ensure the substrate remains protected.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause standard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Quick check

Use on: Concrete. Must be overcoated if used outside.

Coverage: Dependent upon surface porosity and profile. Typical coverage for concrete is 5-10 square metres per litre per coat.

Dry time (minimum): 2 hours. Drying is slowed by low temperatures and high humidity. Do not reapply under damp conditions.

Recoat time (minimum): 2 hours.

Usual number of coats: One. Very porous concrete may require a second coat.

Application method: Brush, short nap synthetic fibre roller, paint pad or spray.

Thinning: Use direct from container. May be thinned with up to 25% water to assist penetration especially on hot dry days. Alternatively the surface may be pre-dampened.

Clean up: Water.

Colour range: Clear.

Before use: Silicone treatments may affect penetration. A test patch is recommended. Stir well with a wide flat stirrer.

Enjoy the Resene Promise of Quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



Cemeal SDS



Cemeal TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz