

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

KEEP OUT OF REACH OF CHILDREN

Resene

MultiSeal

waterborne sealer

interior

net contents 4 litres

A-LLC4000204 7/21

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists get medical advice or attention.

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned get medical advice or attention. When seeking medical advice take this container with you.

Further information can be obtained from NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Zinc Oxide <35 g/L.

For use as a surface preparation coating.

For full technical instructions see Data Sheet C40.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.



WHITE

Resene MultiSeal is a waterborne odourless sealer for sealing a variety of interior substrates prior to topcoating with Resene topcoats. Excellent penetration and consolidation of the substrate.

Preparation and priming

- All surfaces to be coated must be sound and free from dirt, grease, oil, or other surface contaminants.

- **New masonry/concrete:** fill any surface cracks/defects with a compatible filler prior to application of Resene MultiSeal. New concrete must be allowed to cure for at 4 weeks before sealer application. Surface water content and Ph value must be less than 12 and 10% respectively.

- **Previously painted/chalking surfaces:** Remove peeling/flaking paint by wire brushing or scraping back to a sound edge. Remove surface chalking by hard brushing with a stiff brush/broom or high-pressure water blast. Gloss finishes should be sanded to de gloss. Spot prime bare areas with Resene MultiSeal.

- **Irregular surfaces:** Smooth out irregularities using China Paint Patching Paste #901 and sand to achieve a required level of surface smoothness.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact China Paints for advice.

- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

Application

- Stir well before use.

- Apply by brush, roller or airless spray. Thin up to 10% with water for brush/roller application only. Thinning not necessary for airless spray application.

- Apply a full even coat of Resene MultiSeal to appropriately prepared surfaces.



MultiSeal SDS

Resene

the paint the professionals use



MultiSeal TDS

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Manufactured by The China Paint Mfg. Co., (Shenzhen) Ltd
under the license of Resene Paints Limited.
No. 18, Group 9, Sanwel, Hengjiang Village, Fengcheng District,
Xinfeng, Shaoguan, Guangdong, China.

Please recycle.

Quick check

Use on: Brickwork, concrete masonry, gypsum plasterboard, solid concrete/plaster.

Gloss level: Matt.

Coverage: 15-17 square metres per litre per coat.

Dry time (minimum): Touch dry: 1 hour at 25°C and 70% RH.

Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 6 hours (varies with environmental conditions).

Usual number of coats: One.

Application method: Apply by brush, roller or airless spray.

Thinning: Thin up to 10% with water for brush/roller application only. Thinning not necessary for airless spray application.

Clean up: Water.

Colour: White.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 0800 737 363 (NZ) or visit the Resene website.