

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 250ml

LL2756025 10/17

#### SAFETY PRECAUTIONS

Read label before use. Keep out reach of children. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects. Toxic to the soil environment.

#### PRECAUTIONS

**AVOID BREATHING MISTS, VAPOURS OR SPRAYS.**  
Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Collect spillage.

#### FIRST AID

**IF SWALLOWED:** Immediately call a POISON CENTRE, doctor, physician or first aider.

**IF ON SKIN (or hair):** Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice or attention. Wash contaminated clothing before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists, get medical advice or attention.

If medical advice is required have product container or label at hand.

If exposed or concerned, get medical advice or attention.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: Benzotriazol derivatives 320-780 gms/L.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING APPLICATION EQUIPMENT:** Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

# Resene ProSelect Sun Block

timber flooring finish  
UV protection

## WARNING

KEEP OUT OF REACH OF CHILDREN



Developed specifically for professional flooring contractors, Resene ProSelect Sun Block is an additive to reduce photo oxidation caused by UV radiation on light coloured timber. Note: Does not stop lightening of darker timber species.

#### FOR PROFESSIONAL USE ONLY

**Important note:** All processes for hardwood timber floor coating from the initial consultation, with the client, through to final application/finishing and maintenance should follow the guidelines set out in the Australasian Timber Flooring Association (ATFA) Information Guide Manual and Web Site, [www.atfa.com.au](http://www.atfa.com.au).

**Dose rate:** Up to 25ml per litre of mixed product.

**Mixing:** Add when required at any time. Ensure thorough mixing. Mechanical stir. Do not shake.

**Clean up:** Wipe up excess before cleaning with soapy water.

Refer to [www.resene.com/proselect](http://www.resene.com/proselect) or the Resene ProSelect Technical Data Booklet for more detailed information.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



## Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 164 960  
Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-linkable toners for recycling with no solvent emissions.