

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene Stone Strengthener

LL8520004 5/24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Harmful if inhaled. Causes mild skin irritation. Causes serious eye irritation. May cause damage to organs. Harmful to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Use only outdoors or in a well-ventilated area. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

If exposed or you feel unwell. Call a POISON CENTRE, doctor or physician. When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D904.

SPILLS: Eliminate all sources of ignition and use appropriate protective equipment. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

FIRE: Use CO₂, dry powder or foam to extinguish.

Use on: Sandstone, Oamaru stone, weathered bricks, lightweight concrete and weathered plasters.

Typical coverage: 1-10 square metres per litre per coat depending on surface.

Dry time (minimum): Can be used immediately after application.

Recoat time (minimum): Dependent on substrate and application conditions.

Usual number of coats: One.

Thinning and clean up: Do not thin. Clean up with mineral turps.

Before use: Stir well with a wide flat stirrer.

Pot life: One year in full sealed containers.

Performance

- Reinforces weak substrates with inert, acid-resistant silica gel.

- Negligible change in surface appearance.

- Low molecular weight for optimum penetration.

Precautions and limitations

- Releases ethyl alcohol – use only in well-ventilated areas.

- Will etch glass. Protect window glass.

- Remove excess material left on the surface with mineral turps if still wet or ammonia if dried. Remove unabsorbed material.

- Wear protective gloves and goggles.

- Will gel in contact with moisture – rinse spray equipment thoroughly with water.

Surface preparation

- Ensure surfaces to be treated are clean and dry.

Application

- Flood surfaces with low pressure spray application.

- Some very porous surfaces will take large amounts of Resene Stone Strengthener. The degree of strengthening required should be determined and a suitable application rate established.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Data Sheet and Safety Data Sheet before application.

net contents 4 litres



COMBUSTIBLE LIQUID

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Stone Strengthener SDS

Resene

the paint the professionals use



Stone Strengthener TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



CLEAR