

# 459S

## ANTI-CRATERING ADDITIVE

### Description

Anticratering additive specially designed for 2K polyurethane topcoats.  
Composition based on poly-functional hydrocarbon tensio-active.

### Products

459S                      Anti-cratering Additive

### Properties

- The addition of 459S in the ready-to-spray paint will reduce the surface defects caused by external contamination like oil, greases and silicones.
- Can be used in: Centari<sup>®</sup> 500, Centari<sup>®</sup> 501, Centari<sup>®</sup> 5035, Imron<sup>®</sup> 700, 120SX, 670S HB, 670S MS, 690S, 695S, 696S and 3200S.

### Recommended use

- Product preparation in accordance to the recommendations in the TDS of the selected quality.
- Addition of maximum 10 ml/li ready-to-spray paint will provide optimum effect.

### Equipment cleaning

Use 3608S.

Products	Packages (li)	Storability at 20°C (year)	VOC (g/li)
459S	1	2	847

### Remarks

- Never use in primers or basecoats.
- Use only if defect occurs in 1<sup>st</sup> coat; the systematic use of anticratering additive will sursaturate the environment and create other surface defects.
- Material has to be at room temperature (18-20°C) before use.

### Safety

Consult Material Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.