

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: RAPC 81A TWO PACK ETCH PRIMER BASE

Other Names:

Recommended Use: Etch primer

Company Name: Resene Paints Limited

Phone: (04) 577 0500 **Fax:** (04) 577 0600

Address: 32-50 Vogel Street

Naenae Wellington NEW ZEALAND

P O Box 38242 Wellington Mail Centre

Emergency Telephone: 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS according to NZ HSNO Regulations
Regulated under NZS5433 for land transportation

Risk Phrases

Safety Phrases

Substance Classification 3.1B 6.3A 6.8B 6.9B 8.3A 9.1B 9.2C 9.3C

Hazard Statements Highly flammable liquid and vapour
Causes skin irritation
Causes serious eye damage
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure
Toxic to aquatic life with long lasting effects
Harmful to the soil environment
Harmful to terrestrial vertebrates

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	%	CAS No	TWA	
Methyl benzene	10-30	108-88-3	188 mg/m ³	NZ OSH (WES) 2002
Methyl Ethyl Ketone	10-30	78-93-3	445 mg/m ³	NZ OSH (WES) 2002
isopropanol	10-30	67-63-0	983 mg/m ³	NZ OSH (WES) 1994
n-Butanol	<10	71-36-3	150 mg/m ³	NZ OSH (WES) 2002
Acetone	<10	67-64-1	1185 mg/m ³	NZ OSH (WES) 2002
Cyclohexanone	<10	108-94-1	100 mg/m ³	NZ OSH (WES) 2002

SECTION 4. FIRST AID MEASURES

Eye: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Rinse mouth. DO NOT induce vomiting.
Call a POISON CENTRE (NZ 0800 764766) or Australia (1800 121126) or doctor/physician if you feel unwell.

Skin Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and plenty of soap. If skin irritation occurs get medical advice/attention.

Inhaled

Aggravated medical conditions caused by exposure

Chronic Health Effects

Advice to Doctor

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ignition Temperature Lower Explosion Limit Upper Explosion Limit

Hazchem Code Flash Point 355°C 1.7% 10.4%

3[Y]E

-17°C

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Clean up spills immediately.

Ventilate area, avoid breathing of vapours.

Remove all ignition sources.

Wear protective clothing and breathing apparatus.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Sweep up.

Place in separate container for disposal or recovery.

Major Spills Restrict access to area. No smoking or naked lights.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Clear area of personnel and move upwind.

Dike and contain spill with inert materials (eg. Sand).

Stop leak if safe to do so.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities

Storage Temperatures Min 1°C Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure standards for mixture No exposure standards has been established for this product

Component Pigments Breathing Zone ppm Breathing Zone mg/m³

Personal Protection

Eyes Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet recommended.

Other Use in well ventilated area with explosion proof equipment. When added to other components mixed material presents hazards from all components.

Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of heated materials. Wash hands thoroughly before handling food.

Respirator Class AUS-1 half face respirator with type A organic filter

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Yellow liquid

Odour	pH	Vapour Pressure	Vapour Density	Boiling Point	Melt Freeze	Solubility	Volatile by Weight
Hydrocarb	n/a	6.3kPa	2.6	56°C		Insoluble	70

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Material Strong oxidizers, acids, alkalis

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product
Refer to individual raw materials

SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment
No data available for this product

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineratio
Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

UN Number 1263

UN Proper shipping Paint related product

Subsidiary risk

Poison Schedule

HAZCHEM Code 3[Y]E

Packing Group: II

Class

Special precautions for user

SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants (Flammable)

Approved Handler Class 3.1B required for quantities greater than 250Lt (containers greather than 5Lt capacity) or greater than 500Lt (containers less than 5Lt capacity)

SECTION 16. OTHER INFORMATION

Date of Preparation 23/11/2008

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commissio

TLV Time weighted averag

STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry numbe

TWA Threshold limit valu

Marine Pollutant Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.