


Always use correct Personal Protective Equipment


400 Slow REDUCER

Description

A thinner for use with Durepox Primer and Rapid Filler (2K primers).



Products



Product Type:
Colour: Clear liquid
Pot Life:
Induction Time:
Density: 0.876 kg/L
Recommended DFT:
Theoretical Coverage:

Properties



VOC: 875.83 g/L
Boiling Point: 110 deg C
Volume Solids:
Recoat-ability:


Dry Time @ 20°C:

Health & Safety



For detailed information refer to Safety Data Sheet (SDS). Safety precautions must be strictly followed during storage, handling and use. Avoid breathing vapour. Use protective clothing and respiratory equipment. Product is flammable.

Transport & Storage



Sizes: 1L,4L,20L,208L
Dangerous Goods: 3A
UN: 1263
Hazchem: 3WE
Packing Group: II
Shipment name: PAINT Related Material (flammable)
Flash point: Below 23°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.