


Always use correct Personal Protective Equipment


BREAK

Description



Break is a soil release agent. It is commonly used for passenger and commercial vehicle as a heavy duty wash.

Products




Product Type: Butyl Glycol Ether solution in water
Colour: Clear / Blue.
Pot Life: N/A
Induction Time: N/A
Density: Approx. 1.00 kg/L
Solubility in water: Soluble
Recommended DFT:
Theoretical Coverage:

Properties




VOC:
Volume Solids:
Recoat-ability:
Dry Time @ 20°C:

Substrates



Cured stable painted surfaces with heavy dirt and grime.
Aluminium
Wheels and tires

Directions For Use



Dilute Break at a ratio of 100-200ml/litre of water, depending on degree of soil. Spray on, starting at top of vehicle. Allow to run down. Leave for 3 minutes. Do not allow to dry. Rinse off with high-pressure spray. Use rubber gloves to protect sensitive skin if hand washing.

Health & Safety



Irritant-Avoid contact with eyes or skin. Avoid breathing vapour. If poisoning occurs, contact a doctor or Poison Information Centre. If swallowed, DO NOT induce vomiting. Give a glass of water For further safety information consult the current Safety Data Sheet (SDS).

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Always use correct Personal Protective Equipment

**Transport &
Storage**



Sizes: 5L, 20L
Dangerous Goods: 6.3B / 6.4A
UN: 1263
Hazchem: 3Z
Packing Group:
Shipment name:
Flash point: Above 61°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.