


Always use correct Personal Protective Equipment


# C-POWER

### Description




C-Power is a high strength industrial cleaning fluid with the addition of citrus as a natural cleaner that is **fully biodegradable**.

### Products




<b>Product Type:</b>	Cleaner
<b>Colour:</b>	Clear
<b>Pot Life:</b>	N/A
<b>Induction Time:</b>	N/A
<b>Density:</b>	Approx 1.00 kg/L.
<b>Recommended DFT:</b>	N/A
<b>Theoretical Coverage:</b>	N/A

### Properties




<b>VOC:</b>	N/A
<b>Volume Solids:</b>	N/A
<b>Solubility in water:</b>	Soluble
<b>Recoat-ability:</b>	N/A
<b>Dry Time @ 20°C:</b>	
<b>Other properties:</b>	Has a sweet odour

### Substrates



Vinyl, Laminates and Flooring. Also used as a vehicle wash to help remove silicon grooming oils etc. Use at 20:1 for this purpose and try a small test area first.

### Directions For Use



C-Power can be used on all hard surfaces and diluted by 100 parts of water depending on surface condition.

### Spray Equipment:



Can be brushed or pressure sprayed on, also feed into water blasters.

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.


Always use correct Personal Protective Equipment

### Health & Safety



Irritant-Avoid contact with eyes or skin. If swallowed, DO NOT induce vomiting. Contact a doctor or a Poisons Information Centre. For further safety information consult the current Safety Data Sheet (SDS).

### Transport & Storage



**Sizes:** 1L, 5L, 20L  
**Dangerous Goods:** 6.1B  
**UN:** 1263  
**Hazchem:** 2Z  
**Packing Group:** II  
**Shipment name:**  
**Flash point:** Above 61°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.