


Always use correct Personal Protective Equipment


# ELECTROSTATIC REDUCER

### Description



Electrostatic Reducer is a thinner specifically designed **ONLY** for the **Electrostatic Application** of some topcoats. Electrostatic equipment suppliers will provide the resistant's range for their particular application equipment. RALI Electrostatic Reducer can help by adding enough for correct wrap of topcoats and primers.

### Products



**Product Type:** Reducer  
**Colour:** Clear  
**Pot Life:** N/A  
**Induction Time:** N/A  
**Density:** 0.85kg/ L  
**Recommended DFT:** N/A  
**Theoretical Coverage:** N/A

### Properties




**VOC:** 850 g/ L  
**Volume Solids:**  
**Recoat-ability:** N/A  
**Boiling Point:** 65°C  
**Dry Time @ 20°C:** N/A

### Health & Safety



For detailed information refer to Safety Data Sheet (SDS). Safety precautions must be strictly followed during storage, handling and use. Avoid breathing vapour. Use protective clothing and respiratory equipment. The product is flammable.

### Transport & Storage



**Sizes:** 1L, 4L, 20L, 60L, 208L  
**Dangerous Goods:** 3A  
**UN:** 1263  
**Hazchem:** 3(Y)E  
**Packing Group:** II  
**Shipment name:** PAINT Related Material  
**Flash point:** < 23°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.