

Get a grip

Getting paint to stick to smooth surfaces, such as tiles, can be tricky, with the paint slipping and sliding around the surface. Resene Waterborne Smooth Surface Sealer provides the ideal solution acting as a grip coat on smooth surfaces making them ready for topcoating with your favourite Resene topcoat.

Resene Waterborne Smooth Surface Sealer has excellent adhesion and will stick to a wide variety of smooth surfaces inside or out. It is also suitable for use on new paperfaced plasterboard in wet areas where a waterborne option is desired. For stained or yellowed paperfaced plasterboard, use Resene Sureseal pigmented sealer (see Data Sheet D42).

Best of all, because Resene Waterborne Smooth Surface Sealer is waterborne, it has much lower VOCs than solventborne products that would traditionally have been used. And it's Environmental Choice approved.

For those coating exterior cementitious surfaces, we recommend Resene Concrete Primer, which is optimised for use over cementitious surfaces.

For further technical information see Data Sheet D47a available from Resene ColorShops and Resellers or from the Resene website.



Resene

the paint the professionals use

A selection of projects that have used Resene Waterborne Smooth Surface Sealer:



Porirua Trust Aquatic Centre project

Previously painted old galvanised steel railings, panels and wires showing signs of corrosion, flaking and mould were brought back to life with careful surface preparation, Resene Waterborne Smooth Surface Sealer and Resene Enamacryl Metallic with a final protective coat of Resene Uracryl 403.

For more information see:

www.resene.com/archspec/products/waterworld.htm



Manukau Institute of Technology

Smooth stained areas made way for painted surfaces with a sealer coat of Resene Waterborne Smooth Surface Sealer to promote adhesion of the topcoats. Remaining Rimu was stained with Resene Waterborne Colorwood tinted to Resene Meranti.

For more information see:

www.resene.com/archspec/products/manukau_institute.htm



International Antarctic Centre

Previously two pack painted precast concrete was sealed with one coat of Resene Waterborne Smooth Surface Sealer to promote adhesion of the topcoats followed by two coats of Resene AquaShield mineral effect finish tinted to a special blend of Antarctic White.

For more information see:

www.resene.com/archspec/products/antarctic.htm



Resene. Licensed
products since 1996

Resene

the paint the professionals use

In Australia

Call 1800 738 383,
visit www.resene.com.au
or email advice@resene.com.au

In New Zealand

Call 0800 RESENE (737 363)
visit www.resene.co.nz
or email advice@resene.co.nz