NB.This chart is from the Resene historical file. Please refer to current

Resene colour charts

for the latest colour options

Resene

sandtex



Resene Sandtex

The time-worn strength of sandstone with the mellow patina of age has been recreated in Resene Sandtex. Perfect for beautifying and protecting concrete, this very versatile finish can be used to reproduce a variety of finishes from aged render effects through to natural limestone and sandstone finishes. The fine sandstone texture adds an extra dimension to the coating and effectively disguises minor surface blemishes without changing the basic architectural concept. The combination of strong colour and texture illustrated by the colours overleaf can transform an ordinary surface into an architectural feature.

Resene Sandtex can be rolled or sprayed to create a monolithic finish reminiscent of sponge finished or cement rendered plaster. Simply apply 1 thin coat of Resene Sandtex with a P.A.L. Hi-Solids Roller to provide an anchor for the second coat. Apply a second coat by roller at 6 square metres per litres. Alternatively, apply 1 coat using air spray at 4-6 square metres per litre in smooth even passes.

For an aged plaster or limestone finish simply apply 2 coats of Resene Sandtex using a P.A.L. Hi-Solids Roller at 6 square metres per litre and brush off in a random manner to achieve the desired effect.

With all application methods, a Resene Lumbersider or Resene X-200 basecoat (tinted to the same colour as the Sandtex) can enhance the final appearance.

Inherently durable, Resene Sandtex also provides an ideal basecoat for creating Mediterranean-style effects. The texture in Resene Sandtex adds an extra dimension to the paint effect. Its effect is not dissimilar to traditional limewashes or cement based paints.

Specifying Resene Sandtex is easy with the Resene One-Line Specification system:

Substrate	One-Line Spec Number	Surface Prep	First Coat	Second Coat	Third Coat Sandtex D71	
Cementitious Surfaces	20e 1.51	D83 D84, D85	Quick Dry D45 or Sureseal D42	Sandtex D71		
Gib Board	20e 1.52		Sureseal D42 or Broadwall D403	Sandtex D71	Sandtex D71	
Plaster Systems	20e 1.53	D82	Quick Dry D45	Sandtex D71	Sandtex D71	

Systems will vary depending on the condition of the substrate. For example, if the surface is porous, substitute Resene Sureseal for Quick Dry and topcoat in your chosen Resene Sandtex colour.

The finish will vary depending on application technique. Refer to the Resene Architectural Sample box for a standard panel. Try yourself or request your painter prepares a sample panel for you to agree to prior to commencing your project.

This chart shows only a small selection of the colours that are available in Resene Sandtex. Please contact a Resene Sales Staff member to check the availability of your desired colour.

COLUMN	1	COLUMN	2	COLUMN	3
Colour	Code	Colour	Code	Colour	Code
Cocoa Bean	04B27	Burnt Sienna	HC4006	Revolver	2GR65
Mondo	3GR08	Crab Apple	1RO40	Lucky Point	1801
Muddy Waters	4YO23	Paarl	3YO66	Siam	12B23
Apache	4YO30	Tuscany	3OR70	Stack	5GR10
Colonial White	6YO22	Spanish White	6YO25	Vanilla	6BO03

Resene Sandtex complies with Environmental Choice standards. Refer to Product Data Sheet D71 for further information or talk to a Resene sales staff member at your local Resene ColorShop.

Resene Paints Limited

32 – 50 Vogel Street, Lower Hutt, New Zealand, P.O. Box 38-242, Wellington Mail Centre Telephone: (04) 577 0500 Fax: (04) 577 0600

Email: advice@resene.co.nz website: http://www.resene.co.nz Branches throughout New Zealand.