paving the May

some stencils and a splash of paint.

You will need:

- Pavers, 2 different sizes and colours
- Coloured gravel or pebbles
- Resene Lumbersider tinted to Resene Burnt
- Resene SRG Grit
- Stencils
- Masking tape
- Paint brush
- Blu-Tack
- Scrubbing brush
- Plants and soil

Note:

When laying pavers, add a level of base course (50-75mm for patios and pathways), compact to a tight surface, then add a layer of sand and level before putting down the pavers.






CLEAR the area to be used of any debris. Add base course and sand if necessary (see note). The area we used had previously been levelled.



MAKE sure the pavers to be stencilled are free from dirt and dust. Wash with soap and water and leave to dry.



PLACE stencils in position and secure with masking tape. Use Blu-Tack to ensure there are no gaps between stencil and paver, or bleeding may occur.



APPLY one coat of Resene Lumbersider in Resene Burnt Crimson, or colour of your choice. Leave to dry.



BEFORE proceeding, add Resene SRG Grit to the paint. As painted surfaces can be slippery when wet, SRG Grit will prevent this. Apply two more coats of paint.



Once dry, lay the pavers on levelled ground, leaving gaps for vour plants. Fill the gaps with soil or a sandy mix if using succulents.



PLACE coloured gravel or pebbles around the pavers and level. Pieces of slate, bark or shells are also very effective.



Plant a selection of succulents or other perennials for effect. For more on paints phone o8oo RESENE or visit www.resene.co.nz