

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

tint included

LL2292301 9/13

WARNING

Read label before use. Keep out of reach of children. May cause an allergic skin reaction. Suspected of damaging organs through prolonged or repeated exposure. May cause respiratory irritation.

PRECAUTIONS

DO NOT BREATHE FUMES/VAPOURS/MISTS/SPRAYS. USE WITH ADEQUATE VENTILATION.

Ensure all safety directions have been read and understood before handling. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Use only outdoors or in well ventilated areas. Wear eye/face protection and protective gloves and respiratory protection. Ensure contaminated clothing does not leave the workplace. Wash thoroughly after handling. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply.

FIRST AID

SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with plenty of soap and water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Seek medical advice/attention if you feel unwell.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Mixed fungicides <10 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D57D.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Woodsman Decking Stain

exterior



9

4180221059653

TINT
BASE

Resene Woodsman Decking Stain is a waterborne acrylic modified oil based stain developed for decking. Available in a range of durable colours.

Preparation

- Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration. Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres. Complete removal of existing stain is required when the existing stain is film forming.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- Always colour test first to check your choice of Resene Woodsman Decking Stain colour gives the result you want on the actual timber you are staining.
- Consult your Resene ColorShop or Reseller for advice on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.
- This product may be used to stain a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Precautions

- Contains powerful fungicides.
- Avoid skin contact.
- Will not prevent checking of plywood.
- Where alkaline cleaners (including Resene Moss & Mould Killer) are used in the preparation of the substrate, ensure that any residue is removed by hosing down with clean water. These residues can affect film formation and, subsequently, durability.
- Trafficable areas coated with this product will not comply with the Building Act Clause D1.3.3(d).

Application

- Before use and regularly during use, stir well with a wide flat stirrer.
- Do not apply directly to film forming stains.

- Apply one full coat and allow to dry before applying second coat if required.
- All faces of the timber should be treated with special attention to end grains.
- For new, dressed or dense timber allow to weather for 1-2 months.
- For optimal performance allow first coat to weather for three months before recoating to achieve darker colours.
- Will not penetrate through existing coatings or very hard latewood bands.
- For best results wipe excess Resene Woodsman Decking Stain off with a dry, absorbent, lint-free cloth rubbing along the grain.
- Will typically require maintenance after two to three summers. Performance is related to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications and darker colours will require less maintenance.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



Resene
the paint the professionals use



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Timber surfaces.

Gloss level: None. Fully penetrating over bare timber.

Typical coverage: Dressed timber: 1st coat, 12-14 square metres per litre, 2nd coat after 3 months 14-16 square metres per litre. Badly weathered timber: 1st coat, 3-4 square metres per litre, 2nd coat after 3 months 5-7 square metres per litre.

Dry time (minimum): 24 hours. Suitable for light foot traffic after 24 hours in normal drying conditions. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 24 hours.

Primer required: No.

Usual number of coats: Two. Will require maintenance after two to three summers.

Application method: Brush, roller or spray.

Thinning and clean up: Do not thin. Clean up with water when wet or mineral turps when dry.

Colour range: Standard colours, refer Resene Woodsman colour chart.

Before use: Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.