


# Safety Data Sheet

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Product Name</b>	<b>Qristal Polysatin</b>
<b>Other Names</b>	PAINT. Product Code: 257
<b>Recommended Use</b>	Solvent based varnish.
<b>Company Name</b>	Resene Paints (Australia) Limited.
<b>Address</b>	7 Production Avenue Molendinar, Queensland 4214.
<b>Emergency Tel</b>	Available Monday – Friday, 8:00 a.m. – 5:00 p.m.
<b>Free Call</b>	1800 738 383
<b>Phone</b>	07 3287 0222
<b>Fax</b>	07 3287 0226

## SECTION 2. HAZARDS IDENTIFICATION

<b>Hazard Statement</b>	HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the criteria of the Safe Work Australia and the ADG code.	
<b>GHS Classification</b>	Flammable Liquid Skin Corrosion/Irritation	Category 3 Category 2
<b>Label Elements</b>	 <p style="text-align: center;"><b>WARNING</b></p>	
<b>Hazard Statements</b>	Flammable liquid and vapour. Causes skin irritation.	
<b>Precautionary statements</b>	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection and other personal protection as required. Wash thoroughly after handling.	

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion (v/v) %
	Alkyd resin	Proprietary	30 – 60
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	30 – 60
	Solvent naphtha (petroleum), light aromatic	64742-95-6	< 10
	Mineral turpentine	Mixture	< 10
	Ingredients determined not to be hazardous	-	balance

---

**SECTION 4. FIRST AID MEASURES**


---

<b>Swallowed</b>	Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting.
<b>Eyes</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. If eye irritation persists, get medical advice or attention.
<b>Skin (or hair)</b>	Remove all contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/ shower. If skin irritation occurs get medical advice or attention.
<b>Inhaled</b>	Remove victim to fresh air and keep at rest in a comfortable position for breathing. See medical advice if you feel unwell.
<b>First Aid Facilities</b>	Safety shower and eye wash facilities.
<b>Aggravated medical conditions caused by exposure.</b>	The normal routes of exposure are usually by skin contact with the material and/or inhalation of the vapour. Contact with skin or eyes may cause irritation. Prolonged or repeated skin contact with the liquid may cause Irritant Contact Dermatitis. Inhalation of vapour or mists may cause irritation to the respiratory tract. May be harmful in contact with skin or inhaled. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in the workplace atmosphere, should be avoided. Ingestion in any form can be avoided by observing correct occupational hygiene.
<b>Advice to Doctor</b>	Treat symptomatically.

---

**SECTION 5. FIRE FIGHTING MEASURES**


---

<b>Extinguisher</b>	For small fires - Alcohol stable foam or carbon dioxide. For large fires - Water spray or fog, or dry chemical powder. Do not use water in a jet.
<b>Hazards from combustion products</b>	On combustion, this product may emit toxic fumes of carbon monoxide and carbon dioxide. May emit clouds of acrid smoke. Vapours are heavier than air and can spread along the ground to distant ignition sources causing flashback.
<b>Special protective precautions and equipment for fire fighters</b>	Wear full protective clothing and self contained breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.  DO NOT approach containers suspected of being hot. They may be violently or explosively reactive. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
<b>Hazchem code</b>	3[Y]

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**


---

<b>Emergency procedures</b>	Avoid contact with spilled or released material. Avoid breathing vapour and avoid contact with skin and eyes. Control personal contact by using protective equipment. Clean up spills immediately.
<b>Environmental precautions</b>	Prevent, by any means available, spillage from entering drains or water course or soil. May pose a long term hazard to the aquatic environment.
<b>Methods and materials for</b>	<b>Minor spills</b>

Contain and absorb small quantities with vermiculate or other non-flammable absorbent material.

**Major spills**

Clear area of personnel and move upwind.  
Alert fire brigade and tell them location and nature of hazard.  
Prevent, by any means available, spillage from entering drains or water course.  
Stop leak if safe to do so.  
Contain spill with sand, earth or vermiculite.

---

**SECTION 7. HANDLING AND STORAGE**

---

**Precautions for safe handling**

Use and store in a well ventilated area.  
Avoid smoking, naked lights, heat or ignition sources.  
When handling, DO NOT eat drink or smoke.  
Vapour may ignite on pumping or pouring due to static electricity.  
DO NOT use plastic buckets.  
Use spark free tools when handling  
Always wash hands with soap and water.  
Observe proper occupational work practices.

**Conditions for safe storage, including any incompatibilities**

Store in a metal can or drum in an approved flammable liquids storage area.  
Check all containers are clearly labelled and free from leaks.  
Keep containers securely sealed.  
Store in a cool dry, well-ventilated area, away from sources of ignition.  
Avoid storage with strong oxidizing agents.

---

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**National exposure standards for mixture**

No exposure standard has been established for this product.  
The petroleum solvent products listed in the ingredients have not been assigned National Exposure Standards. However, as a guide for controlling exposure, the exposure standards for the petroleum solvent mixtures listed below should be adopted.  
Exposed individuals are not reasonably expected to be warned, by smell, that the exposure standard is being exceeded.

Component	Breathing Zone (TWA) ppm	Breathing zone (TWA) mg/m <sup>3</sup>	Mixture conc: (%)
White Spirits	-	790	30 - 60
Mineral Turpentine	-	480	<10

**Biological Limit Values** No biological limit allocated

**Engineering Controls** Use in a well ventilated area.  
General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear an approved respirator in compliance with AS1716.

**Personal Protective Equipment**

**Eyes.** Safety glasses with side shields; or as required, Chemical goggles.  
Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

**Hands/Feet** Wear chemical resistant gloves.  
Wear safety footwear.

**Protective Clothing** Skin protection not ordinarily required beyond standard issue work clothes.

**Respiratory Protection** If work practices do not maintain airborne levels below exposure standards, use appropriate respiratory protection equipment as specified in AS1716. Selection of the Class and Type

of respirator will depend on the level of confinement of the contamination.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Clear amber liquid
<b>Odour</b>	Solvent odour
<b>pH</b>	Not applicable
<b>Vapour pressure</b>	5.2kPa
<b>Vapour density</b>	3.7
<b>Boiling point</b>	137°C
<b>Freezing/melting point</b>	Data not available
<b>Solubility</b>	Insoluble in water Soluble in Mineral Turps
<b>Density</b>	Not known
<b>Flash Point</b>	31°C
<b>UEL</b>	Not established
<b>LEL</b>	
<b>VOC</b>	56% by weight

## SECTION 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Product is considered stable.
<b>Conditions to avoid</b>	Ignition sources Presence of incompatible materials.
<b>Incompatible materials</b>	Flammable liquids should not be stored with:- Class 1 – Explosives Class 2 – Flammable gases Class 2.3 – Poisonous gases Class 4.2 – Spontaneously combustible substances Class 5.1 – Oxidizing agents Class 5.2 – Organic peroxides Class 7 – Radioactive substances.
<b>Hazardous decomposition products</b>	Oxides of Carbon and Nitrogen.
<b>Hazardous reactions</b>	Hazardous polymerization will not occur.

## SECTION 11. TOXICOLOGICAL INFORMATION

Toxicological information for this product is not available. Reference is made, where possible, to the individual constituents.

### Acute Health Effects:

#### **Inhaled.**

Inhalation of vapours or mists may cause irritation to the respiratory system.

#### **Skin Contact.**

Mild irritant. Dermal LD<sub>50</sub> (rat) : >2,000 mg/Kg (solvent naphtha).

#### **Swallowed:**

Expected to be of low toxicity: LD50>2000mg/kg, Rat (Solvent Naphtha). Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. May cause irritation to the mouth, throat, oesophagus, and stomach with nausea, abdominal discomfort, vomiting and diarrhoea.

#### **Eye:**

May cause eye irritation, tearing, stinging, blurred vision and redness.

Prolonged skin contact with the liquid may cause defatting of the skin. This can result in drying, cracking and irritation of the skin. Long term use may result in Dermatitis.

Inhalation of solvent over an extended period may result in nervous system impairment and liver and blood changes.

## SECTION 12. ECOLOGICAL INFORMATION

No data available for this product. Refer to data for ingredients below:  
Expected to be hazardous to aquatic organisms. Avoid release to the environment.

### Solvent naphtha

Fish : Toxic 1 <LC/EC/IC<sub>50</sub> <= 10 mg/L  
Aquatic Invertebrates : Toxic 1 <LC/EC/IC<sub>50</sub> <= 10 mg/L  
Algae : Toxic 1 <LC/EC/IC<sub>50</sub> > 10 mg/L

Mobility - Floats on water. Absorbs to soil and has low mobility.

Persistence/degradability – Expected to be readily biodegradable. Oxidizes by photo-chemical reactions in air.

Bioaccumulation – Has the potential to bioaccumulate.

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods and containers** Consult State Land Waste Management Authority for disposal.

**Special precautions for landfill or incineration** Incinerate residue at an approved site.  
Recycle containers if possible, or dispose of in an approved landfill.

## SECTION 14. TRANSPORT INFORMATION

**UN Number** 1263  
**UN Proper shipping name** PAINT.  
**DG Class** 3 Flammable Liquid  
**Subsidiary risk** None  
**Packing Group** III  
**Marine Pollutant** No  
**Hazchem Code** 3[Y]

## SECTION 15. REGULATORY INFORMATION

**Poison Schedule** 5

### FIRST AID:

A For advice, contact a Poisons Information Centre, Australia 13 1126; New Zealand 0800 764 766, or a doctor at once.

G3 If swallowed, do NOT induce vomiting.

### SAFETY DIRECTIONS:

1, 4 & 8 Avoid contact with eyes, skin and avoid breathing dust, vapour or spray mist.

The principle components of this material are listed on the Australian Inventory of Chemical Substances (AICS).

NZ HSNO CCID: 3.1C 6.3A 6.4A 6.8A 6.9B 9.1C  
NZ EPA Approval: HSR002662 Surface Coatings & Colorants (Flammable)

**SECTION 16. OTHER INFORMATION**

**Date of Preparation:** 7<sup>th</sup> November 2012

**Supersedes:** 4<sup>th</sup> May 2010

**Literature references.**

AICS Search page – NOHSC <http://www.nicnas.gov.au/industry/aics/search.asp>

Preparation of Safety Data Sheets for Hazardous Chemicals. *Code of Practice 2011.*

Australian Dangerous Goods Code – 7<sup>th</sup> Edition.

SDS's for individual raw materials.

National Exposure Standards for Atmospheric Contaminants in the Occupational Environment. [NOHSC: 1 03(1995)]

Standard for the Uniform Scheduling of Medicines and Poisons. No. 2

Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Third Revised Edition. United Nations. New York and Geneva, 2009.

**Abbreviations:**

NOHSC	National Occupational Health and Safety Commission
ADG	Australian Code for the Transport of Dangerous Goods by Road & Rail
LD <sub>50</sub>	Median lethal dose
LC <sub>50</sub>	Median lethal concentration.
TWA	Time weighted average. The average airborne concentration of a particular substance when calculated over a normal 8 hour working day, for a five-day working week.
STEL	Short term exposure limit. A 15 minute TWA exposure which should not be exceeded at any time during a working day even if the average is within the TWA exposure standard. Exposures at the STEL should not be longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL.
CAS Number	Chemical Abstract Service registry number

*Safety data sheets are updated frequently. Please ensure that you have a current copy.*

*The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use hereof. Resene Paints (Australia) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material, Such users or vendors assume all risks associated with the use of the material. It is the users' responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The user must determine whether the use of the information and data is in accordance with local laws and regulations.*

**END OF SDS**