

Resene ProSelect Stain Base

Developed specifically for professional flooring contractors, Resene ProSelect Stain Base is a waterborne tint base designed to be coloured using the ProSelect Colour Concentrates. It is supplied in concentrated form and then thinned before use.

Physical properties

| | |
|---------------------|-------------------------------|
| Material type: | Oil modified urethane |
| Solvent: | Water |
| Finish: | Natural finish after thinning |
| Usual no. of coats: | 1 |
| VOC: | 70 g/L |
| Volume Solids: | 26 % |
| Cleanup: | Water or soapy water |

Typical uses

- To stain/colour bare properly prepared timber
 - Hardwoods
 - Veneers
 - Cork

Mixing

For use by experienced professional applicators only.

Add Resene ProSelect Colour Concentrate to achieve desired colour strength. Up to 10% Colour Concentrate is typical (do not add more than 20%). Shake or stir well until colour is even.

Dilute with an equal volume of water immediately before application and mix thoroughly.

Application

Suitable for application by various methods such as brush, wipe, rag and mop. Apply a thin even coat and for best results work into the timber following the grain. Remove any excess before it dries. Drying time is dependent upon application conditions and porosity of the timber. Do not flood the timber surface.

Mix regularly while applying to ensure a uniform colour is maintained. Thinned product must be used the same day it is mixed.

Precautions

Consult the Safety Data Sheet and can labels for this product prior to use. Users should ensure that they are familiar with all aspects concerning safe use of the product. IF IN DOUBT DO NOT USE THIS PRODUCT.

Storage/Transport

Do not allow to freeze. Temperature during transport and or storage is required to be >5°C and <25°C

Refer to www.resene.com/proselect or the Resene ProSelect Technical Data Booklet for more detailed information.

Disclaimer

The information supplied is not a specification and all of the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury.