

Resene Grassmarking Paint

waterborne
exterior

Resene Grassmarking Paint is a waterborne paint suitable for marking out lines and field areas on grass without harming the grass itself. Depending on the concentration required, Resene Grassmarking Paint may be thinned by 2-3 parts water making it a cost-effective option for all field marking projects.

exterior

Typical uses

- Grass

Physical properties

Vehicle type	100% acrylic
Pigmentation	Titanium dioxide/fillers
Solvent	Water
Finish	Low sheen
Colour	Standard colour white. Other colours available on request – minimum orders may apply.
Dry time (minimum)	30 minutes at 18°C
Theoretical coverage	Typically 12-14 square metres per litre but can vary with grass surface and intensity of required marking.
Usual no. of coats	1
Thinning and clean up	Water
VOC	5 grams per litre (see Resene VOC Summary)

Performance

Performance and limitations

1. Quick and easy to apply.
2. Designed especially for application to grass without the normal fungicides and biocides in standard decorative paint.
3. An Environmental Choice approved product.

Limitations

1. Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.
2. Not designed for use on any other surfaces other than grass. For line marking on concrete or black seal tennis courts use Resene Lumbersider (see [Data Sheet D34](#)).

Please ensure the current Data Sheet and Safety Data Sheet are consulted prior to specification or application of product. If in doubt contact Resene.



Grassmarking Paint

Surface preparation

Trim grass to an even length. Ensure grass is dry prior to application.

Application

Apply by brush (No.1 roller sleeve), roller or spray.

To remove the Resene Grassmarking Paint wait for the grass to grow and cut the lawn. This will cut off the painted area.

Precautions

1. Ensure Resene Grassmarking Paint is applied evenly and avoid thick applications. It is important that the grass still receives sunlight through the coating to ensure it will continue to grow.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

In Australia
PO Box 924, Beenleigh, Qld 4207
Call 1800 738 383, visit www.resene.com.au
or email advice@resene.com.au

Resene
the paint the professionals use

In New Zealand
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Call 0800 RESENE (737 363), visit www.resene.co.nz
or email advice@resene.co.nz