

Resene TagCover

waterborne
graffiti covering
paint

Resene TagCover is a range of waterborne satin paints formulated to provide a budget friendly paint system to cover graffiti.

exterior

Typical uses

- Concrete
- Plaster
- Timber

Vehicle type	100% acrylic
Pigmentation	Titanium dioxide/fillers
Solvent	Water
Finish	Satin
Colour	Available in a standard range of Resene TagCover colours, custom colours available on request. Minimum quantities may apply for standard colours.

Dry time (minimum)	30 minutes at 18°C
Theoretical coverage	12-14 square metres per litre per coat. Coverage will vary dependent on surface porosity and profile.
Usual no. of coats	1-2 depending on surface and finish required.
Abrasion resistance	Very good
Chemical resistance	Good
Heat resistance	Thermoplastic
Durability	Excellent
Thinning and clean up	Water.
VOC	c. 10 grams per litre white, other colours vary 4-39 grams per litre (see Resene VOC Summary)

Physical properties

Performance

Performance and limitations

1. Formulated to cover most graffiti in one coat.
2. Quick and easy to apply with easy water washup.
3. An Environmental Choice approved product.

Limitations

1. Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.
2. Not designed as a painted surface from which graffiti can be removed using dedicated graffiti cleaners.

Please ensure the current Data Sheet and Safety Data Sheet are consulted prior to specification or application of product. If in doubt contact Resene.



TagCover graffiti covering paint

Surface preparation

Ensure surfaces are clean and dry, free from dirt, dust and loose material, oil, grease and mould.

Sanding dust from old lead or chromate based paints or old building materials containing asbestos may be injurious to the health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

Application

Apply by roller – Resene No.1 roller sleeve, brush or spray.

Apply 1–2 coats depending on surface and finish required. Best applied to a full wall area rather than part of a wall to ensure a consistent finish across the full area.

Precautions

1. Resene TagCover is designed for application to previously painted surfaces. Ensure existing surface is painted or if unpainted, prime or seal prior to applying Resene TagCover.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

In Australia
PO Box 924, Beenleigh, Qld 4207
Call 1800 738 383, visit www.resene.com.au
or email advice@resene.com.au

Resene
the paint the professionals use

In New Zealand
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Call 0800 RESENE (737 363), visit www.resene.co.nz
or email advice@resene.co.nz