

RESENE ARMOURCOTE 512 HARDENER

Resene Paints Ltd

Chemwatch Hazard Alert Code: 3

Version No: 1.2
Safety Data Sheet according to HSNO Regulations

Issue Date: 21/12/2015
Print Date: 21/12/2015
Initial Date: 21/12/2015
L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE ARMOURCOTE 512 HARDENER
Synonyms	Not Available
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	5533
--------------------------	------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Naenae 5011 Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 577 3327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)
Emergency telephone numbers	0800 764 766
Other emergency telephone numbers	Not Available

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
+800 2436 2255	+612 9186 1132	Not Available

Once connected and if the message is not in your preferred language then please dial 01


SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Goods for transport purposes.

GHS Classification [1]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Skin Sensitizer Category 1, Reproductive Toxicity Category 2, STOT - SE Category 2, STOT - RE Category 2, Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2, Flammable Liquid Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1B, 9.1B, 6.5B (contact), 6.4A, 6.9B, 6.3A, 9.1D, 6.8B

Label elements

GHS label elements	
SIGNAL WORD	DANGER

Hazard statement(s)

Continued...

RESENE ARMOURCOTE 512 HARDENER

H315	Causes skin irritation
H319	Causes serious eye irritation
H317	May cause an allergic skin reaction
H361	Suspected of damaging fertility or the unborn child
H371	May cause damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H225	Highly flammable liquid and vapour

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
------	---

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
-----------	--

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
-----------	--

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
26761-45-5	10-20	<u>glycidyl neodecanoate</u>
28064-14-4	10-20	<u>bisphenol F glycidyl ether/ formaldehyde copolymer</u>
25068-38-6	30-60	<u>bisphenol A/ diglycidyl ether resin, liquid</u>
108-88-3	1-10	<u>toluene</u>
78-93-3	1-10	<u>methyl ethyl ketone</u>

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

RESENE ARMOURCOTE 512 HARDENER

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	▶ Liquid and vapour are highly flammable. Combustion products include; carbon dioxide (CO ₂) aldehydes other pyrolysis products typical of burning organic material

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	▶ Remove all ignition sources.
Major Spills	▶ Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Avoid all personal contact, including inhalation. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	▶ Store in original containers in approved flame-proof area.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packing as supplied by manufacturer. ▶ For low viscosity materials (l) : Drums and jerry cans must be of the non-removable head type.
Storage incompatibility	▶ Avoid cross contamination between the two liquid parts of product (kit). ▶ Avoid reaction with amines, mercaptans, strong acids and oxidising agents Glycidyl ethers: ▶ may form unstable peroxides on storage in air, light, sunlight, UV light or other ionising radiation, trace metals - inhibitor should be maintained at adequate levels ▶ may polymerise in contact with heat, organic and inorganic free radical producing initiators ▶ may polymerise with evolution of heat in contact with oxidisers, strong acids, bases and amines ▶ react violently with strong oxidisers, permanganates, peroxides, acyl halides, alkalis, ammonium persulfate, bromine dioxide ▶ attack some forms of plastics, coatings, and rubber

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	toluene	Toluene	188 mg/m ³ / 50 ppm	Not Available	Not Available	Skin absorption
New Zealand Workplace Exposure Standards (WES)	methyl ethyl ketone	Methyl ethyl ketone	445 mg/m ³ / 150 ppm	890 mg/m ³ / 300 ppm	Not Available	Exposure can also be estimated by biological monitoring.

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
bisphenol F glycidyl ether/ formaldehyde copolymer	Phenol, polymer with formaldehyde, oxiranylmethyl ether	12 mg/m ³	130 mg/m ³	790 mg/m ³
bisphenol A/ diglycidyl ether resin, liquid	Epoxy resin (EPON 1001)	90 mg/m ³	990 mg/m ³	5900 mg/m ³
bisphenol A/ diglycidyl ether resin, liquid	Epoxy resin (EPON 1007)	90 mg/m ³	990 mg/m ³	5900 mg/m ³
bisphenol A/ diglycidyl ether resin, liquid	Epoxy resin (EPON 820)	41 mg/m ³	450 mg/m ³	2700 mg/m ³
bisphenol A/ diglycidyl ether resin, liquid	Epoxy resin ERL-2795	32 mg/m ³	350 mg/m ³	2100 mg/m ³
toluene	Toluene	Not Available	Not Available	Not Available
methyl ethyl ketone	Butanone, 2-; (Methyl ethyl ketone; MEK)	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
glycidyl neodecanoate	Not Available	Not Available
bisphenol F glycidyl ether/ formaldehyde copolymer	Not Available	Not Available
bisphenol A/ diglycidyl ether resin, liquid	Not Available	Not Available
toluene	2,000 ppm	500 ppm
methyl ethyl ketone	3,000 ppm	3,000 [Unch] ppm

RESENE ARMOURCOTE 512 HARDENER

MATERIAL DATA

For toluene:

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)

NOTE: Detector tubes measuring in excess of 5 ppm, are available.


For methyl ethyl ketone:

Odour Threshold Value: Variously reported as 2 ppm and 4.8 ppm

Odour threshold: 2 ppm (detection); 5 ppm (recognition) 25 ppm (easy recognition); 300 ppm IRRITATING

Exposures at or below the recommended TLV-TWA are thought to prevent injurious systemic effects and to minimise objections to odour and irritation.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. ▶ When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butadiene rubber), boots and aprons.
Body protection	See Other protection below
Other protection	▶ Overalls. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

RESENE ARMOURCOTE 512 HARDENER

Material	CPI
PE/EVAL/PE	A
PVA	B
TEFLON	B
BUTYL	C
BUTYL/NEOPRENE	C
CPE	C
HYPALON	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PVC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
VITON	C
VITON/CHLOROBUTYL	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity.

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS / Class 1 P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	Air-line*	-	-
up to 100 x ES	-	A-3 P2	-
100+ x ES	-	Air-line**	-

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

RESENE ARMOURCOTE 512 HARDENER

Information on basic physical and chemical properties

Appearance	Liquid with strong solvent odour		
Physical state	Liquid	Relative density (Water = 1)	1.104
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	502
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	94	Molecular weight (g/mol)	Not Available
Flash point (°C)	-1	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.5	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.5	Volatile Component (%vol)	10
Vapour pressure (kPa)	6.2	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	2.8	VOC g/L	82

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation".
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.
Chronic	On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population. Exposure to the material may cause concerns for human fertility, on the basis that similar materials provide some evidence of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects. All glycidyl ethers show genotoxic potential due their alkylating properties. Bisphenol F, bisphenol A, fluorine-containing bisphenol A (bisphenol AF), and other diphenylalkanes were found to be oestrogenic in a bioassay with MCF7 human breast cancer cells in culture. Bisphenol F (4,4'-dihydroxydiphenylmethane) has been reported to exhibit oestrogen agonistic properties in the uterotrophic assay. Bisphenol A exhibits hormone-like properties that raise concern about its suitability in consumer products and food containers. Respiratory sensitisation may result in allergic/asthma like responses; from coughing and minor breathing difficulties to bronchitis with wheezing, gasping. Sensitisation may give severe responses to very low levels of exposure, in situations where exposure may occur.

RESENE ARMOURCOTE 512 HARDENER

RESENE ARMOURCOTE 512 HARDENER	TOXICITY	IRRITATION
		Not Available
glycidyl neodecanoate	TOXICITY	IRRITATION
	dermal (rat) LD50: 3800 mg/kg ^[2]	[SHELL]
	Inhalation (rat) LC50: >0.24 mg/L4 h ^[1]	
	Oral (rat) LD50: 9600 mg/kg ^[2]	
bisphenol F glycidyl ether/ formaldehyde copolymer	TOXICITY	IRRITATION
	dermal (rat) LD50: 4000 mg/kg ^{e[2]}	* [Ciba-Geigy]
	Oral (rat) LD50: 4000 mg/kg ^{t[2]}	Effects transient
		Eyes * (-) (-) Slight irritant
		May cause allergic response
	Skin * (-) (-) Slight irritant	
bisphenol A/ diglycidyl ether resin, liquid	TOXICITY	IRRITATION
	dermal (rat) LD50: >800 mg/kg ^[1]	Eye (rabbit): 100mg - Mild
	Oral (rat) LD50: 13447 mg/kg ^[1]	
toluene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 12124 mg/kg ^[2]	Not Available
	Inhalation (rat) LC50: >26700 ppm/1hd ^[2]	
	Inhalation (rat) LC50: 49 mg/L/4H ^[2]	
	Oral (rat) LD50: 636 mg/kg ^{e[2]}	
methyl ethyl ketone	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >8100 mg/kg ^[1]	- mild
	Inhalation (rat) LC50: 23.5 mg/L/8H ^[2]	Eye (human): 350 ppm -irritant
	Inhalation (rat) LC50: 50.1 mg/L/8 hr ^[2]	Eye (rabbit): 80 mg - irritant
	Oral (rat) LD50: 3474.9 mg/kg ^[1]	Skin (rabbit): 402 mg/24 hr - mild
		Skin (rabbit):13.78mg/24 hr open

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

RESENE ARMOURCOTE 512 HARDENER	The following information refers to contact allergens as a group and may not be specific to this product. The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit many common characteristics with respect to animal toxicology. for 1,2-butylene oxide (ethyloxirane): Ethyloxirane increased the incidence of tumours of the respiratory system in male and female rats exposed via inhalation.
GLYCIDYL NEODECANOATE	The following information refers to contact allergens as a group and may not be specific to this product. The material has a low order of acute toxicity by the oral, dermal, and inhalation routes of exposure. Acute Toxicity The material has a low order of acute toxicity by the oral, dermal, and inhalation routes of exposure . Repeated Dose Toxicity A low order of toxicity was observed in rats following five-week dietary testing . * HPV Chemical Challenge Program 2003
BISPHENOL F GLYCIDYL ETHER/ FORMALDEHYDE COPOLYMER	The following information refers to contact allergens as a group and may not be specific to this product. The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon.
BISPHENOL A/ DIGLYCIDYL ETHER RESIN, LIQUID	The following information refers to contact allergens as a group and may not be specific to this product. The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. In mice, dermal application of bisphenol A diglycidyl ether (BADGE) (1, 10, or 100 mg/kg) for 13 weeks produced mild to moderate chronic active dermatitis. Foetotoxicity has been observed in animal studies Oral (rabbit, female) NOEL 180 mg/kg (teratogenicity); NOEL (maternal 60 mg/kg
TOLUENE	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). For toluene: Acute Toxicity Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death.
METHYL ETHYL KETONE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

RESENE ARMOURCOTE 512 HARDENER

Methyl ethyl ketone is considered to have a low order of toxicity; however methyl ethyl ketone is often used in combination with other solvents and the toxic effects of the mix may be greater than either solvent alone.

Acute Toxicity	☹	Carcinogenicity	☹
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	☹	Aspiration Hazard	☹

Legend: ✗ – Data available but does not fill the criteria for classification
 ✓ – Data required to make classification available
 ☹ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
glycidyl neodecanoate	EC50	96	Algae or other aquatic plants	0.348mg/L	3
glycidyl neodecanoate	LC50	96	Fish	4.102mg/L	3
glycidyl neodecanoate	NOEC	96	Algae or other aquatic plants	≈1mg/L	1
glycidyl neodecanoate	EC50	48	Crustacea	ca.4.8mg/L	2
glycidyl neodecanoate	EC50	72	Algae or other aquatic plants	ca.1.2mg/L	2
bisphenol A/ diglycidyl ether resin, liquid	LC50	96	Fish	1.2mg/L	2
bisphenol A/ diglycidyl ether resin, liquid	EC50	48	Crustacea	1.1mg/L	2
bisphenol A/ diglycidyl ether resin, liquid	EC50	48	Crustacea	1.7mg/L	2
bisphenol A/ diglycidyl ether resin, liquid	NOEC	504	Crustacea	0.3mg/L	2
bisphenol A/ diglycidyl ether resin, liquid	EC50	72	Algae or other aquatic plants	9.4mg/L	2
toluene	BCF	24	Algae or other aquatic plants	10mg/L	4
toluene	EC50	3	Algae or other aquatic plants	0.1336030mg/L	4
toluene	EC50	48	Crustacea	0.01151750mg/L	4
toluene	EC50	72	Algae or other aquatic plants	12.5mg/L	4
toluene	LC50	96	Fish	0.0031704mg/L	4
toluene	NOEC	168	Crustacea	0.74mg/L	2
methyl ethyl ketone	EC50	384	Crustacea	52.575mg/L	3
methyl ethyl ketone	LC50	96	Fish	228.130mg/L	3
methyl ethyl ketone	EC50	96	Algae or other aquatic plants	>500mg/L	4
methyl ethyl ketone	EC50	48	Crustacea	308mg/L	2
methyl ethyl ketone	NOEC	48	Crustacea	68mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

For bisphenol A and related bisphenols:

In general, studies have shown that bisphenol A can affect growth, reproduction and development in aquatic organisms.

Significant environmental findings are limited.

for 1,2-butylene oxide (ethyloxirane):

Environmental fate: Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
glycidyl neodecanoate	HIGH	HIGH
bisphenol A/ diglycidyl ether resin, liquid	HIGH	HIGH
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)
methyl ethyl ketone	LOW (Half-life = 14 days)	LOW (Half-life = 26.75 days)

Bioaccumulative potential

Continued...

RESENE ARMOURCOTE 512 HARDENER

Ingredient	Bioaccumulation
glycidyl neodecanoate	LOW (LogKOW = 3.7305)
bisphenol A/ diglycidyl ether resin, liquid	LOW (LogKOW = 2.6835)
toluene	LOW (BCF = 90)
methyl ethyl ketone	LOW (LogKOW = 0.29)

Mobility in soil

Ingredient	Mobility
glycidyl neodecanoate	LOW (KOC = 105.5)
bisphenol A/ diglycidyl ether resin, liquid	LOW (KOC = 51.43)
toluene	LOW (KOC = 268)
methyl ethyl ketone	MEDIUM (KOC = 3.827)

SECTION 13 DISPOSAL CONSIDERATIONS



Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	
HAZCHEM	•3YE

Land transport (UN)

UN number	1263				
Packing group	II				
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)				
Environmental hazard	No relevant data				
Transport hazard class(es)	<table border="1"> <tr> <td>Class</td> <td>3</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table>	Class	3	Subrisk	Not Applicable
Class	3				
Subrisk	Not Applicable				
Special precautions for user	<table border="1"> <tr> <td>Special provisions</td> <td>163; 367</td> </tr> <tr> <td>Limited quantity</td> <td>5 L</td> </tr> </table>	Special provisions	163; 367	Limited quantity	5 L
Special provisions	163; 367				
Limited quantity	5 L				

Air transport (ICAO-IATA / DGR)

UN number	1263						
Packing group	II						
UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)						
Environmental hazard	No relevant data						
Transport hazard class(es)	<table border="1"> <tr> <td>ICAO/IATA Class</td> <td>3</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> <tr> <td>ERG Code</td> <td>3L</td> </tr> </table>	ICAO/IATA Class	3	ICAO / IATA Subrisk	Not Applicable	ERG Code	3L
ICAO/IATA Class	3						
ICAO / IATA Subrisk	Not Applicable						
ERG Code	3L						

RESENE ARMOURCOTE 512 HARDENER

Sea transport (IMDG-Code / GGVSee)

UN number	1263		
Packing group	II		
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)		
Environmental hazard	Marine Pollutant		
Transport hazard class(es)	IMDG Class	3	
	IMDG Subrisk	Not Applicable	
Special precautions for user	EMS Number	F-E, S-E	
	Special provisions	163 367	
	Limited Quantities	5 L	

Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	glycidyl neodecanoate	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	toluene	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methyl ethyl ketone	Z

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002662	Surface Coatings and Colourants (Flammable) Group Standard 2006

GLYCIDYL NEODECANOATE(26761-45-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

BISPHENOL F GLYCIDYL ETHER/ FORMALDEHYDE COPOLYMER(28064-14-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

BISPHENOL A/ DIGLYCIDYL ETHER RESIN, LIQUID(25068-38-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

TOLUENE(108-88-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Workplace Exposure Standards (WES)

METHYL ETHYL KETONE(78-93-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Workplace Exposure Standards (WES)

New Zealand Inventory of Chemicals (NZIoC)

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
3.1B	100 L in containers greater than 5 L 250 L in containers up to and including 5 L	50 L 50 L

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
3.1B	250 L (when in containers greater than 5 L) 500 L (when in containers up to and including 5 L)

Continued...

RESENE ARMOURCOTE 512 HARDENER

Refer Group Standards for further information

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (toluene; glycidyl neodecanoate; bisphenol A/ diglycidyl ether resin, liquid; bisphenol F glycidyl ether/ formaldehyde copolymer; methyl ethyl ketone)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	N (bisphenol F glycidyl ether/ formaldehyde copolymer)
Japan - ENCS	N (bisphenol F glycidyl ether/ formaldehyde copolymer)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
glycidyl neodecanoate	26761-45-5, 71206-09-2
bisphenol F glycidyl ether/ formaldehyde copolymer	28064-14-4, 42616-71-7, 59029-73-1, 94422-39-6
bisphenol A/ diglycidyl ether resin, liquid	25068-38-6, 25085-99-8

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL: No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.