

RESENE DEEP CLEAN SPRAY VERSION

Resene Paints Ltd

Version No: 1.1
Safety Data Sheet according to HSNO Regulations

Issue Date: **22/10/2019**
Print Date: **22/10/2019**
L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE DEEP CLEAN SPRAY VERSION
Synonyms	Not Available
Proper shipping name	DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (contains benzyl C12-14 alkyldimethylammonium chloride)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	10504
--------------------------	-------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Skin Corrosion/Irritation Category 1B, Acute Aquatic Hazard Category 1, Serious Eye Damage Category 1, Acute Toxicity (Oral) Category 4, Acute Vertebrate Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.1D (oral), 8.2B, 8.3A, 9.1A, 9.3B

Label elements

Hazard pictogram(s)	
SIGNAL WORD	DANGER

Hazard statement(s)

H314	Causes severe skin burns and eye damage.
H400	Very toxic to aquatic life.
H302	Harmful if swallowed.
H432	Toxic to terrestrial vertebrates.

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/ spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P270	Do not eat, drink or smoke when using this product.

Continued...

RESENE DEEP CLEAN SPRAY VERSION

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P321	Specific treatment (see advice on this label).
P391	Collect spillage.
P363	Wash contaminated clothing before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
-------------	------------------

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
85409-22-9	20-40	<u>benzyl C12-14 alkyldimethylammonium chloride</u>
9003-11-6	1-10	<u>polypropylene/ polyethylene glycol copolymer</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing for at least 15 minutes. ▶ Transport to hospital or doctor in event of irritation without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▶ Quickly remove all contaminated clothing, including footwear. ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor in event of irritation.
Inhalation	<p>If aerosols, fumes or combustion products are inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop seek medical attention.</p>
Ingestion	<ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

RESENE DEEP CLEAN SPRAY VERSION

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> Non combustible. carbon dioxide (CO₂) hydrogen chloride phosgene nitrogen oxides (NO_x) other pyrolysis products typical of burning organic material.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Clean up all spills immediately.
Major Spills	<p>Chemical Class:acidic compounds. Clean contaminated objects and areas thoroughly observing environmental regulations. If the product contaminates waterways, inform competent authorities in accordance with local regulations.</p> <ul style="list-style-type: none"> Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> Avoid unnecessary personal contact, including inhalation. DO NOT allow clothing wet with material to stay in contact with skin
Other information	<ul style="list-style-type: none"> Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	As supplied by manufacturer.
Storage incompatibility	<ul style="list-style-type: none"> Reacts with mild steel, galvanised steel / zinc producing hydrogen gas. Avoid strong bases. Segregate from alkalies and oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
polypropylene/ polyethylene glycol copolymer	Polypropylene-polyethylene glycol; (Pluronic L-81)	6.9 mg/m ³	76 mg/m ³	460 mg/m ³

Ingredient	Original IDLH	Revised IDLH
benzyl C12-14 alkyldimethylammonium chloride	Not Available	Not Available
polypropylene/ polyethylene glycol copolymer	Not Available	Not Available

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
benzyl C12-14 alkyldimethylammonium chloride	E	≤ 0.01 mg/m ³

Continued...

RESENE DEEP CLEAN SPRAY VERSION


Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
Skin protection	See Hand protection below
Hands/feet protection	▶ Elbow length PVC gloves ▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	See Other protection below
Other protection	▶ Overalls.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

'Forsberg Clothing Performance Index'.

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

RESENE DEEP CLEAN SPRAY VERSION

Material	CPI
BUTYL	A
NEOPRENE	A
VITON	A
NATURAL RUBBER	C
PVA	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as 'feel' or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AK-P Filter of sufficient capacity.

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AK-AUS / Class1 P2	-
up to 50	1000	-	AK-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AK-2 P2
up to 100	10000	-	AK-3 P2
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid		
Physical state	Liquid	Relative density (Water = 1)	1.04-1.07
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	5-7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available

Continued...

RESENE DEEP CLEAN SPRAY VERSION

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	>90
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	▶ stable
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Ingestion of acidic corrosives may produce circumoral burns with a distinct discolouration of the mucous membranes of the mouth, throat and oesophagus. The very bitter taste is likely to give early warning of accidental ingestion. Concentrated solutions of cationic surfactants (exceeding 10%) may produce corrosive damage of the mucous membranes and oesophagus, and may cause nausea and vomiting.
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). 1% solutions of many cationic surfactants produce dermal irritation and 10% solutions may be corrosive producing chemical burns. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Eye	Direct eye contact with acid corrosives may produce pain, lachrymation, photophobia and burns. When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Solutions of many cationic surfactants (as low as 0.1% strength) produce significant irritation of the eyes. Irritation of the eyes may produce a heavy secretion of tears (lachrymation).
Chronic	Repeated or prolonged exposure to acids may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Prolonged or repeated skin contact may cause degreasing with drying, cracking and dermatitis following.

RESENE DEEP CLEAN SPRAY VERSION	TOXICITY	IRRITATION
	Not Available	Not Available
benzyl C12-14 alkyldimethylammonium chloride	TOXICITY	IRRITATION
	Oral (rat) LD50: 447 mg/kg ^[2]	Eye: adverse effect observed (irreversible damage) ^[1]
		Skin: adverse effect observed (corrosive) ^[1]
polypropylene/ polyethylene glycol copolymer	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 0.32 mg/l/4h ^[2]	Eye (rabbit): 500 mg/24h - mild
	Oral (rat) LD50: 2300 mg/kg ^[2]	Skin (rabbit): 500 mg/24h - mild
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

RESENE DEEP CLEAN SPRAY VERSION

RESENE DEEP CLEAN SPRAY VERSION	Most undiluted cationic surfactants satisfy the criteria for classification as Harmful (Xn) with R22 and as Irritant (Xi) for skin and eyes with R38 and R41. For quaternary ammonium compounds (QACs): Quaternary ammonium compounds (QACs) are cationic surfactants.
BENZYL C12-14 ALKYLDIMETHYLAMMONIUM CHLORIDE	The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). For alkyldimethylbenzylammonium chlorides (ADMBAC): Alkyldimethylbenzylammonium chlorides (ADMBAC) are included in Annex 1 of list of dangerous substances of Council Directive 67/548/EEC with the following classification: C8-18 ADMBAC are classified as Harmful (Xn) with the risk phrases R21/22 (Harmful in contact with skin and if swallowed) and Corrosive (C) with R34 (Causes burns) and (N) with R50 (Very toxic to aquatic organisms). For similar compound benzyl C12-18 alkyldimethyl ammonium chloride CAS RN 68391-01-5:
POLYPROPYLENE/ POLYETHYLENE GLYCOL COPOLYMER	* Varies - dependent on degree of ethoxylation. Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved. The material may be irritating to the eye, with prolonged contact causing inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).
RESENE DEEP CLEAN SPRAY VERSION & BENZYL C12-14 ALKYLDIMETHYLAMMONIUM CHLORIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5.

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

RESENE DEEP CLEAN SPRAY VERSION	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
benzyl C12-14 alkyldimethylammonium chloride	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.515mg/L	2
	EC50	48	Crustacea	0.016mg/L	2
	EC50	96	Algae or other aquatic plants	0.01mg/L	2
	EC10	96	Algae or other aquatic plants	0.002mg/L	2
	NOEC	72	Algae or other aquatic plants	<=0.0012mg/L	2
polypropylene/ polyethylene glycol copolymer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

Surfactants are in general toxic to aquatic organisms due to their surface-active properties.

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse.

For quaternary ammonium compounds (QACs):

QACs are generally white crystalline powders.

Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels (chloride >3000 mg/l).

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Continued...

RESENE DEEP CLEAN SPRAY VERSION

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible. <p>Consult manufacturer for recycling option. Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</p>
------------------------------	--



Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	
HAZCHEM	2X

Land transport (UN)

UN number	1903				
UN proper shipping name	DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (contains benzyl C12-14 alkyldimethylammonium chloride)				
Transport hazard class(es)	<table border="0"> <tr> <td>Class</td> <td>8</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table>	Class	8	Subrisk	Not Applicable
Class	8				
Subrisk	Not Applicable				
Packing group	II				
Environmental hazard	Environmentally hazardous				
Special precautions for user	<table border="0"> <tr> <td>Special provisions</td> <td>274</td> </tr> <tr> <td>Limited quantity</td> <td>1 L</td> </tr> </table>	Special provisions	274	Limited quantity	1 L
Special provisions	274				
Limited quantity	1 L				

Air transport (ICAO-IATA / DGR)

UN number	1903														
UN proper shipping name	Disinfectant, liquid, corrosive, n.o.s. * (contains benzyl C12-14 alkyldimethylammonium chloride)														
Transport hazard class(es)	<table border="0"> <tr> <td>ICAO/IATA Class</td> <td>8</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> <tr> <td>ERG Code</td> <td>8L</td> </tr> </table>	ICAO/IATA Class	8	ICAO / IATA Subrisk	Not Applicable	ERG Code	8L								
ICAO/IATA Class	8														
ICAO / IATA Subrisk	Not Applicable														
ERG Code	8L														
Packing group	II														
Environmental hazard	Environmentally hazardous														
Special precautions for user	<table border="0"> <tr> <td>Special provisions</td> <td>A3 A803</td> </tr> <tr> <td>Cargo Only Packing Instructions</td> <td>855</td> </tr> <tr> <td>Cargo Only Maximum Qty / Pack</td> <td>30 L</td> </tr> <tr> <td>Passenger and Cargo Packing Instructions</td> <td>851</td> </tr> <tr> <td>Passenger and Cargo Maximum Qty / Pack</td> <td>1 L</td> </tr> <tr> <td>Passenger and Cargo Limited Quantity Packing Instructions</td> <td>Y840</td> </tr> <tr> <td>Passenger and Cargo Limited Maximum Qty / Pack</td> <td>0.5 L</td> </tr> </table>	Special provisions	A3 A803	Cargo Only Packing Instructions	855	Cargo Only Maximum Qty / Pack	30 L	Passenger and Cargo Packing Instructions	851	Passenger and Cargo Maximum Qty / Pack	1 L	Passenger and Cargo Limited Quantity Packing Instructions	Y840	Passenger and Cargo Limited Maximum Qty / Pack	0.5 L
Special provisions	A3 A803														
Cargo Only Packing Instructions	855														
Cargo Only Maximum Qty / Pack	30 L														
Passenger and Cargo Packing Instructions	851														
Passenger and Cargo Maximum Qty / Pack	1 L														
Passenger and Cargo Limited Quantity Packing Instructions	Y840														
Passenger and Cargo Limited Maximum Qty / Pack	0.5 L														

RESENE DEEP CLEAN SPRAY VERSION

Sea transport (IMDG-Code / GGVSee)

UN number	1903	
UN proper shipping name	DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (contains benzyl C12-14 alkyldimethylammonium chloride)	
Transport hazard class(es)	IMDG Class	8
	IMDG Subrisk	Not Applicable
Packing group	II	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-A , S-B
	Special provisions	274
	Limited Quantities	1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002526	Cleaning Products (Corrosive) Group Standard 2017

BENZYL C12-14 ALKYLDIMETHYLAMMONIUM CHLORIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations
International Maritime Dangerous Goods Requirements (IMDG Code)

New Zealand Inventory of Chemicals (NZIoC)
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

POLYPROPYLENE/ POLYETHYLENE GLYCOL COPOLYMER IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
9.1A, 9.2A, 9.3A, and 9.4A	Any quantity

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	22/10/2019
Initial Date	22/10/2019

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Continued...

RESENE DEEP CLEAN SPRAY VERSION

Powered by AuthorITe, from Chemwatch.