

# Resene Uracryl Graffitishield Flat

## Resene Paints Ltd

Version No: 1.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 06/01/2025

Print Date: 06/01/2025

L.GHS.NZL.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

Product name	Resene Uracryl Graffitishield Flat
Synonyms	Not Available
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	11783
--------------------------	-------

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 5770500
Fax	+64 4 5773327
Website	<a href="http://www.resene.co.nz">www.resene.co.nz</a>
Email	<a href="mailto:advice@resene.co.nz">advice@resene.co.nz</a>

#### Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7days)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	0800 764766	+64 800 700 112
Other emergency telephone number(s)	Not Available	+61 3 9573 3188


Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

Classification [1]	Sensitisation (Skin) Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.5B (contact), 9.1C

#### Label elements

Hazard pictogram(s)	
Signal word	Warning

#### Hazard statement(s)

H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statement(s) Prevention

P280	Wear protective gloves and protective clothing.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

#### Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

## Resene Uracryl GraffitiShield Flat

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 September 2022 to be identified:

**Mixtures**

CAS No	%[weight]	Name
41556-26-7	<0.5	<u>bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate</u>
84133-50-6	0.1-0.3	<u>alcohols C12-14 secondary ethoxylated</u>
34590-94-8	1-5	<u>dipropylene glycol monomethyl ether</u>
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

**SECTION 4 First aid measures****Description of first aid measures**

<b>Eye Contact</b>	If this product comes in contact with eyes: <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	If skin contact occurs: <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 Firefighting measures****Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**Advice for firefighters**

<b>Fire Fighting</b>	▶ Alert Fire Brigade and tell them location and nature of hazard.
<b>Fire/Explosion Hazard</b>	Non- combustible Burning release: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit corrosive fumes.

**SECTION 6 Accidental release measures****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	Contain spill with sawdust or sand then place in suitable container for disposal. Clean area with large quantity of water to complete clean-up.
<b>Major Spills</b>	Moderate hazard. Clear area of personnel and move upwind. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Contain spill with sawdust or sand then place in suitable container for disposal. Clean area with large quantity of water to complete clean-up.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 Handling and storage**

Continued...

## Resene Uracryl GraffitiShield Flat

## Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> <li>Avoid unnecessary personal contact, including inhalation.</li> <li><b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>
Other information	

## Conditions for safe storage, including any incompatibilities

Suitable container	As supplied by manufacturer
Storage incompatibility	Avoid reaction with oxidising agents

## SECTION 8 Exposure controls / personal protection

## Control parameters

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	dipropylene glycol monomethyl ether	Dipropylene glycol methyl ether	100 ppm / 606 mg/m3	909 mg/m3 / 150 ppm	Not Available	(skin) - Skin absorption

Ingredient	Original IDLH	Revised IDLH
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	Not Available	Not Available
alcohols C12-14 secondary ethoxylated	Not Available	Not Available
dipropylene glycol monomethyl ether	600 ppm	Not Available

## Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	D	> 0.1 to ≤ 1 ppm
alcohols C12-14 secondary ethoxylated	E	≤ 0.1 ppm
<b>Notes:</b>	<i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i>	

## MATERIAL DATA

for dipropylene glycol monomethyl ether:

The TLV-TWA and STEL recommendations were thought to be sufficiently low to prevent objectionable irritation and provide a considerable safety factor against CNS impairment.

## Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Individual protection measures, such as personal protective equipment	
Eye and face protection	<ul style="list-style-type: none"> <li>Safety glasses with side shields.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> <li>Wear chemical protective gloves, e.g. PVC.</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>The material may produce skin sensitisation in predisposed individuals.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.</p>
Body protection	Overall
Respiratory protection	Respiratory protection required in insufficiently ventilated working areas and during spraying. An approved respirator with a replaceable vapour/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to AS/NZS 1715 Standard, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 Standard, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. Recommended filter type: Type A filter (organic vapour).

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

Appearance	This product is a mixture		
Physical state	Liquid	Relative density (Water = 1)	1.0-1.1
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Continued...

## Resene Uracryl Graffitishield Flat

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7-9	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	71
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	65
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

## SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## SECTION 11 Toxicological information

## Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as 'harmful by ingestion'.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models).
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.

Resene Uracryl Graffitishield Flat	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral (Rat) LD50: 3100 mg/kg <sup>[2]</sup>	Not Available
alcohols C12-14 secondary ethoxylated	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
dipropylene glycol monomethyl ether	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 9500 mg/kg <sup>[2]</sup>	Eye (Human): 8mg - Mild
	Oral (Rat) LD50: 5135 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 500mg/24H - Mild
		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (Rodent - rabbit): 500mg - Mild
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

## Resene Uracryl Graffitishield Flat

<p><b>ALCOHOLS C12-14 SECONDARY ETHOXYLATED</b></p>	<p>No significant acute toxicological data identified in literature search. Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved. Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products . Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units: EO &lt; 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes) EO &gt; 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41 EO &gt; 15-20 gives Harmful (Xn) with R22-41 &gt;20 EO is not classified (CESIO 2000) Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) . AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC</p> <p>In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats.</p> <p>For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers): <b>Skin absorption:</b> Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ethylene ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm2/hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.</p>
<p><b>DIPROPYLENE GLYCOL MONOMETHYL ETHER</b></p>	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. for propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The material may be irritating to the eye, with prolonged contact causing inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).</p>
<p><b>Resene Uracryl Graffitishield Flat &amp; BIS(1,2,2,6,6- PENTAMETHYL-4- PIPERIDYL)SEBACATE</b></p>	<p>The following information refers to contact allergens as a group and may not be specific to this product.</p>
<p><b>Acute Toxicity</b></p>	<p>✗ <b>Carcinogenicity</b> ✗</p>
<p><b>Skin Irritation/Corrosion</b></p>	<p>✗ <b>Reproductivity</b> ✗</p>
<p><b>Serious Eye Damage/Irritation</b></p>	<p>✗ <b>STOT - Single Exposure</b> ✗</p>
<p><b>Respiratory or Skin sensitisation</b></p>	<p>✓ <b>STOT - Repeated Exposure</b> ✗</p>
<p><b>Mutagenicity</b></p>	<p>✗ <b>Aspiration Hazard</b> ✗</p>

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

<p><b>Resene Uracryl Graffitishield Flat</b></p>	<table border="1"> <thead> <tr> <th>Endpoint</th> <th>Test Duration (hr)</th> <th>Species</th> <th>Value</th> <th>Source</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> <td>Not Available</td> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	Endpoint	Test Duration (hr)	Species	Value	Source	Not Available	Not Available	Not Available	Not Available	Not Available																				
Endpoint	Test Duration (hr)	Species	Value	Source																											
Not Available	Not Available	Not Available	Not Available	Not Available																											
<p><b>bis(1,2,2,6,6-pentamethyl-4- piperidyl)sebacate</b></p>	<table border="1"> <thead> <tr> <th>Endpoint</th> <th>Test Duration (hr)</th> <th>Species</th> <th>Value</th> <th>Source</th> </tr> </thead> <tbody> <tr> <td>EC0(ECx)</td> <td>24h</td> <td>Crustacea</td> <td>&lt;10mg/l</td> <td>1</td> </tr> <tr> <td>LC50</td> <td>96h</td> <td>Fish</td> <td>0.34mg/l</td> <td>1</td> </tr> </tbody> </table>	Endpoint	Test Duration (hr)	Species	Value	Source	EC0(ECx)	24h	Crustacea	<10mg/l	1	LC50	96h	Fish	0.34mg/l	1															
Endpoint	Test Duration (hr)	Species	Value	Source																											
EC0(ECx)	24h	Crustacea	<10mg/l	1																											
LC50	96h	Fish	0.34mg/l	1																											
<p><b>alcohols C12-14 secondary ethoxylated</b></p>	<table border="1"> <thead> <tr> <th>Endpoint</th> <th>Test Duration (hr)</th> <th>Species</th> <th>Value</th> <th>Source</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> <td>Not Available</td> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	Endpoint	Test Duration (hr)	Species	Value	Source	Not Available	Not Available	Not Available	Not Available	Not Available																				
Endpoint	Test Duration (hr)	Species	Value	Source																											
Not Available	Not Available	Not Available	Not Available	Not Available																											
<p><b>dipropylene glycol monomethyl ether</b></p>	<table border="1"> <thead> <tr> <th>Endpoint</th> <th>Test Duration (hr)</th> <th>Species</th> <th>Value</th> <th>Source</th> </tr> </thead> <tbody> <tr> <td>EC50</td> <td>96h</td> <td>Algae or other aquatic plants</td> <td>&gt;969mg/l</td> <td>2</td> </tr> <tr> <td>EC50</td> <td>72h</td> <td>Algae or other aquatic plants</td> <td>&gt;969mg/l</td> <td>2</td> </tr> <tr> <td>NOEC(ECx)</td> <td>528h</td> <td>Crustacea</td> <td>&gt;=0.5mg/l</td> <td>2</td> </tr> <tr> <td>EC50</td> <td>48h</td> <td>Crustacea</td> <td>1930mg/l</td> <td>2</td> </tr> <tr> <td>LC50</td> <td>96h</td> <td>Fish</td> <td>&gt;1000mg/l</td> <td>2</td> </tr> </tbody> </table>	Endpoint	Test Duration (hr)	Species	Value	Source	EC50	96h	Algae or other aquatic plants	>969mg/l	2	EC50	72h	Algae or other aquatic plants	>969mg/l	2	NOEC(ECx)	528h	Crustacea	>=0.5mg/l	2	EC50	48h	Crustacea	1930mg/l	2	LC50	96h	Fish	>1000mg/l	2
Endpoint	Test Duration (hr)	Species	Value	Source																											
EC50	96h	Algae or other aquatic plants	>969mg/l	2																											
EC50	72h	Algae or other aquatic plants	>969mg/l	2																											
NOEC(ECx)	528h	Crustacea	>=0.5mg/l	2																											
EC50	48h	Crustacea	1930mg/l	2																											
LC50	96h	Fish	>1000mg/l	2																											
<p><b>Legend:</b></p>	<p>Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data</p>																														

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
dipropylene glycol monomethyl ether	HIGH	HIGH

## Bioaccumulative potential

## Resene Uracryl GraffitiShield Flat

Ingredient	Bioaccumulation
alcohols C12-14 secondary ethoxylated	LOW (LogKOW = 3.32)
dipropylene glycol monomethyl ether	LOW (BCF = 100)

**Mobility in soil**

Ingredient	Mobility
dipropylene glycol monomethyl ether	LOW (Log KOC = 10)

## SECTION 13 Disposal considerations

## Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</li> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ Recycle wherever possible.</li> <li>Consult manufacturer for recycling option.</li> <li>Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</li> </ul>

## Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal. The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021) and local regulations.

## SECTION 14 Transport information

## Labels Required

Label	Requirement
Marine Pollutant	NO
HAZCHEM	Not Applicable

**Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

## 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	Not Available
alcohols C12-14 secondary ethoxylated	Not Available
dipropylene glycol monomethyl ether	Not Available

## 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	Not Available
alcohols C12-14 secondary ethoxylated	Not Available
dipropylene glycol monomethyl ether	Not Available

## SECTION 15 Regulatory information

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

**bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate is found on the following regulatory lists**

New Zealand Inventory of Chemicals (NZIoC)

Continued...

## Resene Uracryl GraffitiShield Flat

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

**alcohols C12-14 secondary ethoxylated is found on the following regulatory lists**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data  
 New Zealand Inventory of Chemicals (NZIoC)  
 New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

**dipropylene glycol monomethyl ether is found on the following regulatory lists**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data  
 New Zealand Inventory of Chemicals (NZIoC)  
 New Zealand Workplace Exposure Standards (WES)

**Additional Regulatory Information**

Not Applicable

**Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

**Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

**Maximum quantities of certain hazardous substances permitted on passenger service vehicles**

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	

**Tracking Requirements**

Not Applicable

**National Inventory Status**

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; alcohols C12-14 secondary ethoxylated; dipropylene glycol monomethyl ether)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (alcohols C12-14 secondary ethoxylated)
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	No (alcohols C12-14 secondary ethoxylated)
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

**SECTION 16 Other information**

<b>Revision Date</b>	06/01/2025
<b>Initial Date</b>	06/01/2025

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

**Definitions and abbreviations**

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit

Continued...

**Resene Uracryl GraffitiShield Flat**

- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
  
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.