Resene Paints Ltd

Version No: 2.2 Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017 Issue Date: 25/01/2022 Print Date: 25/01/2022 L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	RESENE ARMOURCOTE 221 BASE
Synonyms	Not Available
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	7829
--------------------------	------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd	
Address	32-50 Vogel Street Wellington New Zealand	
Telephone	+64 4 577 0500	
Fax	+64 4 5773327	
Website	www.resene.co.nz	
Email	advice@resene.co.nz	

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Flammable Liquids Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2, Specific Target Organ Toxicity - Single Exposure Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Reproductive Toxicity Category 2, Sensitisation (Skin) Category 1, Carcinogenicity Category 2	
Legend:	1. Classified by Chernwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	1 3 1(; 6 1) (oral) 6 3A 6 4A 6 5B (contact) 6 7B 6 8B 6 9B 9 1B	

Label elements

Hazard pictogram(s)	
---------------------	--

Signal word Warning

Hazard statement(s)

H226	Flammable liquid and vapour.	
H411	Toxic to aquatic life with long lasting effects.	
H371	May cause damage to organs. (Oral, Dermal)	
H373	May cause damage to organs through prolonged or repeated exposure. (Oral, Dermal)	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	

H319	Causes serious eye irritation.	
H361	Suspected of damaging fertility or the unborn child.	
H317	May cause an allergic skin reaction.	
H351	Suspected of causing cancer.	

autionary statement(s) Provention

Precautionary statement(s) Prevention		
P201	Obtain special instructions before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P233	Keep container tightly closed.	
P260	Do not breathe mist/vapours/spray.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P240	Ground and bond container and receiving equipment.	
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.	
P242	Use non-sparking tools.	
P243	Take action to prevent static discharges.	
P270	Do not eat, drink or smoke when using this product.	
P264	Wash all exposed external body areas thoroughly after handling.	
P273	Avoid release to the environment.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.	
P302+P352	IF ON SKIN: Wash with plenty of water and soap.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider.	
P314	Get medical advice/attention if you feel unwell.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P391	Collect spillage.	
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P330	Rinse mouth.	

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
7779-90-0	1-10	zinc phosphate
1314-13-2	0.1-0.2	zinc oxide
71-36-3	0.1-1	<u>n-butanol</u>
1330-20-7	1-10	xylene
100-41-4	1-10	ethylbenzene
100-51-6	0.1-0.5	benzyl alcohol
95-63-6	5-15	1.2.4-trimethyl benzene
98-82-8	1-10	cumene
Legend:	1. Classified by Chernwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention if pain persists or recurs. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5 Firefighting measures

Extinguishing media

- Foam.Dry chemical powder.
- Carbon dioxide. Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are flammable. Combustion products include: carbon dioxide (CO2) carbon monoxide (CO) metal oxides other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Remove all ignition sources. Contain spill with inert non- combustible absorbent then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean- up.
Major Spills	Remove all ignition sources. Clear area of personnel and move upwind. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible, contain the spill. Place inert absorbent, non- combustible material onto spillage. Use clean non- sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authority.

SECTION 7 Handling and storage

Safe handling	 Containers, even those that have been emptied, may contain explosive vapours. Avoid personal contact, including inhalation. Wear protective clothing when risk of overexposure occurs. Use in a well-ventilated area. Avoid smoking, naked lights or ignition sources. Avoid generation of static electricity. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. DO NOT allow clothing wet with material to stay in contact with skin
Other information	Store in original containers in approved flammable liquid storage area.

Conditions for safe storage, including any incompatibilities

Suitable container	Packing as supplied by manufacturer.
Storage incompatibility	 may ignite or explode in contact with strong oxidisers. attack some plastics, rubber and coatings Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	zinc phosphate	Diesel Particulate Matter (DPM) as elemental carbon	0.1 mg/m3	Not Available	Not Available	diesel engine exhaust is a confirmed carcinogen
New Zealand Workplace Exposure Standards (WES)	zinc phosphate	Particulates not otherwise classified	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc phosphate	Particulates not otherwise classified respirable dust	3 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide fume respirable dust	3 mg/m3	10 mg/m3	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide Dust respirable dust	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	n-butanol	n-Butyl alcohol	Not Available	Not Available	50 ppm / 150 mg/m3	skin-Skin absorption
New Zealand Workplace Exposure Standards (WES)	xylene	Dimethylbenzene	50 ppm / 217 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	ethylbenzene	Ethyl benzene	100 ppm / 434 mg/m3	543 mg/m3 / 125 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	cumene	Cumene	25 ppm / 125 mg/m3	375 mg/m3 / 75 ppm	Not Available	skin-Skin absorption

Emergency Limits

Emergency Emite					
Ingredient	TEEL-1	TEEL-1 TEEL-2		TEEL-3	
zinc phosphate	12 mg/m3	12 mg/m3 36 mg/m3		220 mg/m3	
zinc oxide	10 mg/m3	15 mg/m3		2,500 mg/m3	
n-butanol	60 ppm	800 ppm		8000** ppm	
xylene	Not Available	Not Available		Not Available	
ethylbenzene	Not Available	Not Available Not Available		Not Available	
benzyl alcohol	30 ppm	ppm 52 ppm		740 ppm	
1,2,4-trimethyl benzene	140 mg/m3	360 mg/m3		2,200 mg/m3	
1,2,4-trimethyl benzene	Not Available	Not Available		480 ppm	
cumene	Not Available	Not Available		Not Available	
Ingredient	Original IDLH	Original IDLH		Revised IDLH	
zinc phosphate	Not Available	Not Available		Not Available	
zinc oxide	500 mg/m3	500 mg/m3		Not Available	
n-butanol	1,400 ppm	1,400 ppm		Not Available	
xylene	900 ppm	900 ppm		Not Available	
ethylbenzene	800 ppm	800 ppm		Not Available	
benzyl alcohol	Not Available		Not Available		

Ingredient	Original IDLH	Revised IDLH			
1,2,4-trimethyl benzene	Not Available	Not Available			
cumene	900 ppm	Not Available			
Occupational Exposure Banding					
Occupational Exposure Banding					
Occupational Exposure Banding Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit			
		Occupational Exposure Band Limit ≤ 0.1 ppm			

 hyl benzene
 E
 ≤ 0.1 ppm

 Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Notes:

Fragrance substance with is an established contact allergen in humans.

IFRA Prohibited Fragrance Substance

The International Fragrance Association (IFRA) Standards form the basis for the globally accepted and recognized risk management system for the safe use of fragrance ingredients and are part of the IFRA Code of Practice.

for zinc oxide:

Zinc oxide intoxication (intoxication zincale) is characterised by general depression, shivering, headache, thirst, colic and diarrhoea.

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits.

For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix.

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

For n-butanol:

Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially.

for ethyl benzene:

Odour Threshold Value: 0.46-0.60 ppm

NOTE: Detector tubes for ethylbenzene, measuring in excess of 30 ppm, are commercially available.

For cumene:

Odour Threshold Value: 0.008-0.132 ppm (detection), 0.047 ppm (recognition)

Exposure at or below the TLV-TWA is thought to prevent induction of narcosis.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Other protection	 Overalls. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.

Respiratory protection

Respiratory protection required in insufficiently ventilated working areas and during spraying. An approved respirator with a replaceable vapour/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to AS/NZS 1715 Standard, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 Standard, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. Recommended filter type: Type A filter (organic vapour).

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Grey dispersion with characteristic odour			
Physical state	Liquid	Relative density (Water = 1)	1.54-1.55	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	120	Molecular weight (g/mol)	Not Available
Flash point (°C)	35	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	45
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	403

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

The acute toxicity of inhaled alkylbenzenes is best describe general anaesthetics.	ed by central r	nervous system depression. As a rule, these compounds may also act as		
A significant number of individuals exposed to mixed trimethylbenzenes complained of nervousness, tension, anxiety and asthmatic bronchitis.				
Headache, fatigue, lassitude, irritability and gastrointestinal disturbances (e.g., nausea, anorexia and flatulence) are the most common symptoms of xylene overexposure. Xylene is a central nervous system depressant.				
Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemica pneumonitis; serious consequences may result.				
Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.				
Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions.				
Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Prolonged or repeated contact with xylenes may cause defatting dermatitis with drying and cracking. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes.				
ΤΟΧΙΟΙΤΥ		IRRITATION		
Not Available		Not Available		
TOXICITY	IRRITATION			
	general anaesthetics. A significant number of individuals exposed to mixed trimet Headache, fatigue, lassitude, irritability and gastrointestinal of xylene overexposure. Xylene is a central nervous system depressant. Swallowing of the liquid may cause aspiration of vomit into pneumonitis; serious consequences may result. Evidence exists, or practical experience predicts, that the n following direct contact. The material may accentuate any pre-existing dermatitis cc Open cuts, abraded or irritated skin should not be exposed Entry into the blood-stream through, for example, cuts, abra Evidence exists, or practical experience predicts, that the n produce significant ocular lesions. Repeated or long-term occupational exposure is likely to pr On the basis, primarily, of animal experiments, concern has respect of the available information, however, there presen Prolonged or repeated contact with xylenes may cause def Chronic solvent inhalation exposures may result in nervous TOXICITY Not Available	A significant number of individuals exposed to mixed trimethylbenzenes of Association of the liquid, irritability and gastrointestinal disturbances of xylene overexposure. Xylene is a central nervous system depressant. Swallowing of the liquid may cause aspiration of vomit into the lungs with pneumonitis; serious consequences may result. Evidence exists, or practical experience predicts, that the material either following direct contact. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this materi Entry into the blood-stream through, for example, cuts, abrasions, punctu Evidence exists, or practical experience predicts, that the material may conduce significant ocular lesions. Repeated or long-term occupational exposure is likely to produce cumula On the basis, primarily, of animal experiments, concern has been express respect of the available information, however, there presently exists inad Prolonged or repeated contact with xylenes may cause defatting dermati Chronic solvent inhalation exposures may result in nervous system impa		

	Oral (Rat) LD50; >5000 mg/kg ^[2]	Eye: n	no adverse effect observed (not irrita	ating) ^[1]	
		Skin: r	no adverse effect observed (not irrit	ating) ^[1]	
	dermal (rat) LD50: >2000 mg/kg ^[1]		ye (rabbit) : 500 mg/24 h - mild		
zinc oxide	Inhalation(Rat) LC50; >1.79 mg/l4h ^[1]			ve: no adverse effect observed (not irritating) ^[1]	
	Oral (Rat) LD50; >5000 mg/kg ^[1]		kin (rabbit) : 500 mg/24 h- mild	[4]	
		S	kin: no adverse effect observed (no	t irritating) ^[1]	
	TOXICITY	IRRIT	TATION		
	Dermal (rabbit) LD50: 3400 mg/kg ^[2]	Eye ((human): 50 ppm - irritant		
	Inhalation(Rat) LC50; 8000 ppm4h ^[2]	Eye ((rabbit): 1.6 mg-SEVERE		
n-butanol	Oral (Rat) LD50; 790 mg/kg ^[2]	Eye ((rabbit): 24 mg/24h-SEVERE		
		Eye:	adverse effect observed (irreversib	e damage) ^[1]	
		Skin	(rabbit): 405 mg/24h-moderate		
		Skin:	adverse effect observed (irritating)	1]	
	ΤΟΧΙΟΙΤΥ		IRRITATION		
	Dermal (rabbit) LD50: >1700 mg/kg ^[2]		Eye (human): 200 ppm irritant		
	Inhalation(Rat) LC50; 5000 ppm4h ^[2]		Eye (rabbit): 5 mg/24h SEVER	E	
xylene	Oral (Mouse) LD50; 2119 mg/kg ^[2]		Eye (rabbit): 87 mg mild		
			Eye: adverse effect observed (i	rritating) ^[1]	
			Skin (rabbit):500 mg/24h mode		
			Skin: adverse effect observed (irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ	15	RRITATION		
	Dermal (rabbit) LD50: 17800 mg/kg ^[2]		eye (rabbit): 500 mg - SEVERE		
ethylbenzene			ye: no adverse effect observed (no	irritating) ^[1]	
,			Skin (rabbit): 15 mg/24h mild		
			Skin: no adverse effect observed (no	t irritating) ^[1]	
	TOVICITY		IDDITATION		
	TOXICITY Dermal (rabbit) LD50: 2000 mg/kg ^[2]		IRRITATION Eye (rabbit): 0.75 mg open SEVER	E	
	Inhalation(Rat) LC50; >4.178 mg/L4h ^[1]		Eye: adverse effect observed (irrita		
benzyl alcohol				ung)t	
	Oral (Rat) LD50; 1230 mg/kg ^[2] Skin (man): 16 mg/48h-m		Skin (rabbit):10 mg/24h open-mild	ı-mild	
			Skin: no adverse effect observed (r		
	ΤΟΧΙCITY			IRRITATION	
1,2,4-trimethyl benzene	Dermal (rabbit) LD50: >3160 mg/kg ^[2]			Not Available	
1,2,4-timethyr benzene	Inhalation(Rat) LC50; 18 mg/L4h ^[2]				
	Oral (Rat) LD50; 6000 mg/kg ^[1]				
	ΤΟΧΙCΙΤΥ	IRI	RITATION		
			ve (rabbit): 500 mg/24h mild		
	Inhalation(Rat) LC50; 39 mg/L4h ^[2]		ve (rabbit): 86 mg mild		
cumene	Oral (Rat) LD50; 1400 mg/kg ^[2]		ve: no adverse effect observed (not	irritating) ^[1]	
			sin (rabbit): 10 mg/24h mild	0,	
			kin (rabbit):100 mg/24h moderate		
		Sk	in: no adverse effect observed (not	irritating) ^[1]	

RESENE ARMOURCOTE 221 BASE	Data demonstrate that during inhalation exposure, aromatic hydrocarbons undergo substantial partitioning into adipose tissues.				
N-BUTANOL	for n-butanol Acute toxicity: n-Butanol (BA) was only slightly toxic to experimental animals following acute oral, dermal, or inhalation exposure.				
XYLENE	Reproductive effector in rats The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.				
ETHYLBENZENE	Liver changes, utheral tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded. Ethylbenzene is readily absorbed following inhalation, oral, and dermal exposures, distributed throughout the body, and excreted primarily through urine. NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.				
BENZYL ALCOHOL	The following information refers to contact allergens For benzyl alkyl alcohols: Unlike benzylic alcohols, the beta-hydroxyl group of the For benzoates: Acute toxicity: Benzyl alcohol, benzoic acid and its as they are all rapidly metabolised and excreted via a A member or analogue of a group of benzyl derivativ flavouring substances in food; their rapid absorption. The aryl alkyl alcohol (AAA) fragrance ingredients and The AAA fragrances demonstrate low acute and sub At concentrations likely to be encountered by consur The potential for eye irritation is minimal. With the exception of benzyl alcohol and to a lesser patch tests and human induction studies, indicate the	the members of this cluster is unlikely t sodium and potassium salt can be con a common pathway within 24 hrs. es generally regarded as safe (GRAS) e a diverse group of chemical structure chronic dermal and oral toxicity. ners, AAA fragrance ingredients are no extent phenethyl and 2-phenoxyethyl A	o undergo phase II metabolic activation. sidered as a single category regarding human health based in part on their self-limiting properties as s with similar metabolic and toxicity profiles. n-irritating to the skin. AA alcohols, human sensitization studies, diagnostic		
1,2,4-TRIMETHYL BENZENE	Other Toxicity data is available for CHEMWATCH 12	172 1,2,3-trimethylbenzene CHEMWAT	CH 2325 1,3,5-trimethylbenzene		
CUMENE	Cumene is reasonably anticipated to be a human car animals. similar metabolic pathways. The relevance specific mechanism not relevant to humans contribut genotoxicity, may also contribute to kidney-tumour fo For aromatic terpenes: Acute toxicity : Mammalian LD50 for p-cymene have Tenth Annual Report on Carcinogens: Substance and [<i>National Toxicology Program: U.S. Dep.</i>	of the kidney tumors to cancer in huma es to their induction, but it is possible t rmation in male rats. e shown it to have low toxic potential.	ns is uncertain; there is evidence that a species-		
RESENE ARMOURCOTE 221 BASE & BENZYL ALCOHOL	Adverse reactions to fragrances in perfumes and in fragranced cosmetic products include allergic contact dermatitis, irritant contact dermatitis, photosensitivity, immediate contact reactions (contact urticaria), and pigmented contact dermatitis. Fragrance allergens act as haptens, i.e. low molecular weight chemicals that are immunogenic only when attached to a carrier protein.				
RESENE ARMOURCOTE 221 BASE & 1,2,4-TRIMETHYL BENZENE	For trimethylbenzenes: Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure.				
ZINC OXIDE & N-BUTANOL & XYLENE & ETHYLBENZENE & BENZYL ALCOHOL & CUMENE	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).				
N-BUTANOL & 1,2,4- TRIMETHYL BENZENE & CUMENE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.				
N-BUTANOL & XYLENE & ETHYLBENZENE	The material may produce severe irritation to the eye causing pronounced inflammation.				
ETHYLBENZENE & CUMENE	WARNING: This substance has been classified by the	ne IARC as Group 2B: Possibly Carcino	ogenic to Humans.		
Acute Toxicity	✓	Carcinogenicity	✓		
Skin Irritation/Corrosion	✓	Reproductivity	*		
	×	STOT - Single Exposure	*		
Serious Eye Damage/Irritation	1				
Respiratory or Skin sensitisation	*	STOT - Repeated Exposure	*		

SECTION 12 Ecological information

Toxicity

RESENE ARMOURCOTE 221 BASE	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
zinc phosphate	EC50(ECx)	24h	Crustacea	0.22mg/l	2
	EC50	48h	Crustacea	>1.08mg/l	2

	Endpoint	Test Duration (hr)	Sp	ecies	Valu	le	Source
	NOEC(ECx)	72h	Alg	ae or other aquatic plants	0.00	5mg/l	2
	BCF	1344h	Fis	h	19-1	10	7
zinc oxide	LC50	96h	Fis	h	0.92	7-2.589mg/l	4
	EC50	72h	Alg	ae or other aquatic plants	0.03	6-0.049mg/l	4
	EC50	48h	Cru	istacea	0.30	1-0.667mg/l	4
	EC50	96h	Alg	ae or other aquatic plants	0.3n	ng/l	2
	Endpoint	Test Duration (hr)	5	Species		Value	Source
	NOEC(ECx)	504h		Crustacea		4.1mg/l	2
	LC50	96h		ish		100-500mg/l	4
n-butanol	EC50	72h		Algae or other aquatic plants		>500mg/l	1
	EC50	48h		Crustacea		>500mg/l	1
	EC50	96h		Algae or other aquatic plants		225mg/l	2
	2000						-
	Endpoint	Test Duration (hr)		Species		Value	Source
	NOEC(ECx)	73h		Algae or other aquatic plants		0.44mg/l	2
xylene	LC50	96h		Fish		2.6mg/l	2
	EC50	72h		Algae or other aquatic plants		4.6mg/l	2
	EC50	48h		Crustacea		1.8mg/l	2
	Endpoint	Test Duration (hr)	Spe	ecies	Value	9	Source
	NOEC(ECx)	720h	Fish			Img/L	4
	LC50	96h	Fish			I-4.075mg/L	4
ethylbenzene	EC50	72h		ae or other aquatic plants	4.6m		1
	EC50	48h		stacea		4.4mg/l	4
	EC50	96h		ae or other aquatic plants	3.6m	-	2
	2000		7.09		0.011	9,1	
	Endpoint	Test Duration (hr)		Species		Value	Source
	NOEC(ECx)	336h		Fish 5.1mg/l		5.1mg/l	2
	LC50	96h		Fish 10mg/l		10mg/l	2
benzyl alcohol	EC50	72h		Algae or other aquatic plants 500mg/l		2	
	EC50	48h		Crustacea 230mg/l		2	
	EC50	96h		Algae or other aquatic plants 76.828mg/l		76.828mg/l	2
	Endpoint	Test Duration (hr)		pecies		Value	Source
	BCF	1344h		ïsh		31-207	7
1,2,4-trimethyl benzene	EC50(ECx)	96h		lgae or other aquatic plants		2.356mg/l	2
	LC50	96h	F	ish		3.41mg/l	2
	EC50	48h	C	rustacea		ca.6.14mg/l	1
	EC50	96h	A	Algae or other aquatic plants		2.356mg/l	2
	Endpoint	Test Duration (hr)		Species		Value	Source
		96h		Crustacea		0.4mg/l	1
	NOEC(ECx)			Fish		2.7mg/l	2
cumene	NOEC(ECx)	96h					
cumene	LC50	96h 72h				-	
cumene		96h 72h 48h		Algae or other aquatic plants Crustacea		1.29mg/l 4mg/l	2

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

For 1,2,4-trimethylbenzene: Half-life (hr) air : 0.48-16 Half-life (hr) H2O surface water : 0.24-672 Half-life (hr) H2O ground : 336-1344 Half-life (hr) soil : 168-672

Henry's Pa m3 /mol: 385-627 Bioaccumulation : not significant 1,2,4-Trimethylbenzene is a volatile organic compound (VOC) substance. For aromatic hydrocarbons: Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus. For xylenes : log Koc : 2.05-3.08 Koc: 25.4-204 Half-life (hr) air : 0.24-42 Half-life (hr) H2O surface water : 24-672 Half-life (hr) H2O ground : 336-8640 Half-life (hr) soil : 52-672 Henry's Pa m3 /mol: 637-879 Henry's atm m3 /mol: 7.68E-03 BOD 5 if unstated: 1.4,1% COD: 2.56,13% ThOD : 3.125 BCE · 23 log BCF : 1.17-2.41 Environmental Fate Terrestrial fate:: Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil. DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-butanol	LOW (Half-life = 54 days)	LOW (Half-life = 3.65 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
benzyl alcohol	LOW	LOW
1,2,4-trimethyl benzene	LOW (Half-life = 56 days)	LOW (Half-life = 0.67 days)
cumene	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
zinc oxide	LOW (BCF = 217)
n-butanol	LOW (BCF = 0.64)
xylene	MEDIUM (BCF = 740)
ethylbenzene	LOW (BCF = 79.43)
benzyl alcohol	LOW (LogKOW = 1.1)
1,2,4-trimethyl benzene	LOW (BCF = 275)
cumene	LOW (BCF = 35.5)

Mobility in soil

Ingredient	Mobility
n-butanol	MEDIUM (KOC = 2.443)
ethylbenzene	LOW (KOC = 517.8)
benzyl alcohol	LOW (KOC = 15.66)
1,2,4-trimethyl benzene	LOW (KOC = 717.6)
cumene	LOW (KOC = 817.2)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. DO NOTallow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. Recycle wherever possible. Consult manufacturer for recycling option. Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.
------------------------------	---

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal. The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021) and local regulations.

Flammable substance can be disposed of if the substance is treated by using a method that changes the characteristics or composition of the substance so that the substance is no

longer a hazardous substance, or exporting the substance from New Zealand as waste. For treating and discharging processes contact your local authority.

The treating may include burning the substance if the burning is managed to ensure that no person, or place where a person may legally be present.

The substance may be discharged into the environment as waste or disposed into a landfill if the substance will not come into contact with oxidising substances and where is no ignition source which is capable to ignite the substance.

SECTION 14 Transport information

Labels Required

Marine Pollutant	
HAZCHEM	•3Y

Land transport (UN)

• • •	
UN number	1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Transport hazard class(es)	Class 3 Subrisk Not Applicable
Packing group	III
Environmental hazard	Environmentally hazardous
Special precautions for user	Special provisions 163; 223; 367 Limited quantity 5 L

Air transport (ICAO-IATA / DGR)

UN number	1263			
UN proper shipping name	Paint related material (including paint thinning or reducing compounds); Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	ICAO / IATA Subrisk Not Applicable		
Packing group	Ш			
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions Cargo Only Packing In Cargo Only Maximum Passenger and Cargo Passenger and Cargo	Qty / Pack Packing Instructions Maximum Qty / Pack	A3 A72 A192 366 220 L 355 60 L Y344	
	Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack		10 L	

Sea transport (IMDG-Code / GGVSee)

UN number	1263	
UN proper shipping name		aint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL nning or reducing compound)
Transport hazard class(es)	IMDG Class IMDG Subrisk	3 Not Applicable
Packing group	Ш	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-E, S-E

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
zinc phosphate	Not Available
zinc oxide	Not Available
n-butanol	Not Available
xylene	Not Available
ethylbenzene	Not Available
benzyl alcohol	Not Available
1,2,4-trimethyl benzene	Not Available
cumene	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
zinc phosphate	Not Available
zinc oxide	Not Available
n-butanol	Not Available
xylene	Not Available
ethylbenzene	Not Available
benzyl alcohol	Not Available
1,2,4-trimethyl benzene	Not Available
cumene	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002669	Surface Coatings and Colourants Flammable Carcinogenic Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

zinc phosphate is found on the following regulatory lists	
New Zealand Approved Hazardous Substances with controls	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals	New Zealand Workplace Exposure Standards (WES)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data	
zinc oxide is found on the following regulatory lists	
New Zealand Approved Hazardous Substances with controls	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals	New Zealand Workplace Exposure Standards (WES)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data	
n-butanol is found on the following regulatory lists	
New Zealand Approved Hazardous Substances with controls	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals	New Zealand Workplace Exposure Standards (WES)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data	
xylene is found on the following regulatory lists	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Approved Hazardous Substances with controls	

Chemical Footprint Project - Chemicals of High Concern List	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	of Chemicals	
Monographs	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	of Chemicals - Classification Data	
Monographs - Group 2B: Possibly carcinogenic to humans	New Zealand Inventory of Chemicals (NZIoC)	
New Zealand Approved Hazardous Substances with controls	New Zealand Workplace Exposure Standards (WES)	
benzyl alcohol is found on the following regulatory lists		
New Zealand Approved Hazardous Substances with controls	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	of Chemicals - Classification Data	
of Chemicals	New Zealand Inventory of Chemicals (NZIoC)	
1,2,4-trimethyl benzene is found on the following regulatory lists		
New Zealand Approved Hazardous Substances with controls	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	of Chemicals - Classification Data	
of Chemicals	New Zealand Inventory of Chemicals (NZIoC)	
cumene is found on the following regulatory lists		
Chemical Footprint Project - Chemicals of High Concern List	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	of Chemicals	
Monographs	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	of Chemicals - Classification Data	
Monographs - Group 2B: Possibly carcinogenic to humans	New Zealand Inventory of Chemicals (NZIoC)	

New Zealand Workplace Exposure Standards (WES)

Hazardous Substance Location

New Zealand Approved Hazardous Substances with controls

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
3.1C	500 L in containers more than 5 L	250 L
3.1C	1 500 L in containers up to and including 5 L	250 L

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	
3.1C or 3.1D				10 L

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	25/01/2022
Initial Date	30/03/2017

SDS Version Summary

Version	Date of Update	Sections Updated
1.2	25/01/2022	Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Chronic Health, Classification, Environmental, Exposure Standard, Fire Fighter (fire/explosion hazard), Handling Procedure, Personal Protection (hands/feet)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.