

RESENE TIMBER & FURNITURE GEL

Resene Paints Ltd

Version No: 2.5
Safety Data Sheet according to HSNO Regulations

Issue Date: 27/04/2020
Print Date: 27/04/2020
L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE TIMBER & FURNITURE GEL
Synonyms	Incl KWILA, JARRA, SHEER BLACK, SILVERED GREY
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	9786, 9787, 9788, 9789
--------------------------	------------------------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132


Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Acute Aquatic Hazard Category 3, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Skin Sensitizer Category 1, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 6.4A, 6.5B (contact), 9.1C, 9.1D

Label elements

Hazard pictogram(s)	
---------------------	---

SIGNAL WORD **WARNING**

Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

RESENE TIMBER & FURNITURE GEL

P321	Specific treatment (see advice on this label).
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
55406-53-6	0.1-0.5	<u>3-iodo-2-propynyl butyl carbamate</u>
64742-82-1.	0.1-1	<u>naphtha_petroleum_hydrodesulfurised heavy</u>
82919-37-7	0.1-1	<u>methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</u>
121-44-8	1-2	<u>triethylamine</u>
84133-50-6	0.1-1	<u>alcohols C12-14 secondary ethoxylated</u>

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

for diuron:

- ▶ Symptomatic and supportive action is indicated.
- ▶ Methaemoglobinaemia is possible
- ▶ if compound is hydrolysed in vivo to aniline.
- ▶ Methaemoglobinaemia causes cyanosis. Reversion of methaemoglobin to haemoglobin is spontaneous after removal from exposure, so moderate degrees of cyanosis need be treated only by supportive measures such as bed rest and oxygen inhalation.
- ▶ Thorough cleansing of the entire contaminated area of the body, including the scalp and nails is of the utmost importance.

SECTION 5 FIREFIGHTING MEASURES**Extinguishing media**

- ▶ Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
----------------------	---

RESENE TIMBER & FURNITURE GEL

Fire/Explosion Hazard	<p>Combustible.</p> <p>Combustion products include: carbon monoxide (CO) carbon dioxide (CO₂) hydrogen iodide metal oxides other pyrolysis products typical of burning organic material. May emit corrosive fumes.</p>
------------------------------	---

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Clean up all spills immediately.
Major Spills	▶ Absorb or contain isothiazolinone liquid spills with sand, earth, inert material or vermiculite.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling**

Safe handling	▶ Avoid all personal contact, including inhalation.
Other information	▶ Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Metal can or drum ▶ Packaging as recommended by manufacturer.
Storage incompatibility	For alkyl aromatics: The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms. ▶ Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphtha, petroleum, hydrodesulfurised heavy	White spirits (Stoddard solvent)	100 ppm / 525 mg/m ³	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	naphtha, petroleum, hydrodesulfurised heavy	Rubber solvent (Naphtha)	400 ppm / 1600 mg/m ³	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	triethylamine	Triethylamine	3 ppm / 12 mg/m ³	20 mg/m ³ / 5 ppm	Not Available	skin-Skin absorption

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
3-iodo-2-propynyl butyl carbamate	Butyl-3-iodo-2-propynylcarbamate	3.3 mg/m ³	36 mg/m ³	220 mg/m ³
naphtha, petroleum, hydrodesulfurised heavy	Naphtha, hydrotreated heavy; (Isopar L-rev 2)	350 mg/m ³	1,800 mg/m ³	40,000 mg/m ³
naphtha, petroleum, hydrodesulfurised heavy	Naphtha (coal tar); includes solvent naphtha, petroleum (64742-88-7), naphtha (petroleum) light aliphatic, rubber solvent (64742-89-8), heavy catalytic cracked (64741-54-4), light straight run (64741-46-4), heavy aliphatic solvent (64742-96-7), high flash aromatic and aromatic solvent naphtha (64742-95-6)	1,200 mg/m ³	6,700 mg/m ³	40,000 mg/m ³
naphtha, petroleum, hydrodesulfurised heavy	Naphtha (coal tar); includes solvent naphtha, petroleum (64742-88-7), naphtha (petroleum) light aliphatic, rubber solvent (64742-89-8), heavy catalytic cracked (64741-54-4), light straight run (64741-46-4), heavy aliphatic solvent (64742-96-7), high flash aromatic and aromatic solvent naphtha (64742-95-6)	1,200 mg/m ³	6,700 mg/m ³	40,000 mg/m ³
naphtha, petroleum, hydrodesulfurised heavy	Petroleum distillates; petroleum ether; includes clay-treated light naphthenic [64742-45-6]; low boiling [68477-31-6]; petroleum extracts [64742-06-9]; petroleum base oil [64742-46-7]; petroleum 50 thinner, petroleum spirits [64475-85-0], Soltrol, VM&P naphtha [8032-32-4]; Ligroine, and paint solvent; petroleum paraffins C5-C20 [64771-72-8]; hydrotreated light naphthenic [64742-53-6]; solvent refined light naphthenic [64741-97-5]; and machine coolant 1	1,100 mg/m ³	1,800 mg/m ³	40,000 mg/m ³

Continued...

RESENE TIMBER & FURNITURE GEL

naphtha, petroleum, hydrodesulfurised heavy	Naphtha (coal tar); includes solvent naphtha, petroleum (64742-88-7), naphtha (petroleum) light aliphatic, rubber solvent (64742-89-8), heavy catalytic cracked (64741-54-4), light straight run (64741-46-4), heavy aliphatic solvent (64742-96-7), high flash aromatic and aromatic solvent naphtha (64742-95-6)	1,200 mg/m ³	6,700 mg/m ³	40,000 mg/m ³
naphtha, petroleum, hydrodesulfurised heavy	Petroleum distillates; petroleum ether; includes clay-treated light naphthenic [64742-45-6]; low boiling [68477-31-6]; petroleum extracts [64742-06-9]; petroleum base oil [64742-46-7]; petroleum 50 thinner, petroleum spirits [64475-85-0], Soltrol, VM&P naphtha [8032-32-4]; Ligroine, and paint solvent; petroleum paraffins C5-C20 [64771-72-8]; hydrotreated light naphthenic [64742-53-6]; solvent refined light naphthenic [64741-97-5]; and machine coolant 1	1,100 mg/m ³	1,800 mg/m ³	40,000 mg/m ³
naphtha, petroleum, hydrodesulfurised heavy	Stoddard solvent; (Mineral spirits, 85% nonane and 15% trimethyl benzene)	300 mg/m ³	1,800 mg/m ³	29500** mg/m ³
triethylamine	Triethylamine	1 ppm	170 ppm	1,000 ppm

Ingredient	Original IDLH	Revised IDLH
3-iodo-2-propynyl butyl carbamate	Not Available	Not Available
naphtha, petroleum, hydrodesulfurised heavy	20,000 mg/m ³ / 1,100 ppm / 1,000 ppm	Not Available
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Not Available	Not Available
triethylamine	200 ppm	Not Available
alcohols C12-14 secondary ethoxylated	Not Available	Not Available

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
3-iodo-2-propynyl butyl carbamate	E	≤ 0.01 mg/m ³
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	D	> 0.1 to ≤ 1 ppm

Notes: Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

1,2-Benzisothiazoline-3-one (BIT) produces sensitising effects and causes skin irritation at concentrations of 0.05%.

CEL TWA: 0.1 mg/m³; STEL 0.3 mg/m³ total isothiazolinones (Rohm and Haas)

(CEL = Chemwatch Exposure Limit)

for diuron:

Exposures at or below the recommended TLV-TWA is thought to protect the worker from the significant risk of anaemia and methaemoglobinaemia associated with use of the product for dipropylene glycol monomethyl ether:

The TLV-TWA and STEL recommendations were thought to be sufficiently low to prevent objectionable irritation and provide a considerable safety factor against CNS impairment for propylene glycol:

Saturated vapour concentration @ 20 deg C.= 65.8 ppm, 204.6 mg/m³; i.e higher concentrations can only occur as aerosols or at higher temperatures.

For amorphous crystalline silica (precipitated silicic acid):

Amorphous crystalline silica shows little potential for producing adverse effects on the lung and exposure standards should reflect a particulate of low intrinsic toxicity.

For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix.

Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

For triethylamine:

Odour Threshold Value: <0.1-0.65 ppm (detection), 0.27-29.0 ppm (recognition)

NOTE: Detector tubes for triethylamine, measuring in excess of 5 ppm, are commercially available.


Odour Threshold Value: 3.3 ppm (detection), 7.6 ppm (recognition)

Exposure at or below the recommended isopropanol TLV-TWA and STEL is thought to minimise the potential for inducing narcotic effects or significant irritation of the eyes or upper respiratory tract.

NOTE H: Special requirements exist in relation to classification and labelling of this substance.

NOTE P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.01% w/w benzene (EINECS No 200-753-7).

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. ▶ Butyl rubber gloves -Nitrile rubber gloves (Note: Nitric acid penetrates nitrile gloves in a few minutes.)

RESENE TIMBER & FURNITURE GEL

Body protection	See Other protection below
Other protection	▶ Overalls.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Light sensitive. Coloured gel		
Physical state	Gel	Relative density (Water = 1)	1.04
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.2-9.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	>93	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	76
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	60

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	<p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).</p> <p>A significant number of individuals exposed to mixed trimethylbenzenes complained of nervousness, tension, anxiety and asthmatic bronchitis. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness.</p> <p>The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression.</p> <p>The odour of isopropanol may give some warning of exposure, but odour fatigue may occur.</p>
Ingestion	<p>Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml.</p> <p>The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".</p> <p>Isothiazolinones are moderately to highly toxic by oral administration.</p> <p>Following ingestion, a single exposure to isopropyl alcohol produced lethargy and non-specific effects such as weight loss and irritation.</p>
Skin Contact	<p>Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Solutions of 0.5% strength 1,2-benzisothiazoline-3-one (BIT) are irritating to the skin.</p> <p>Aqueous solutions of isothiazolinones may be irritating or even corrosive depending on concentration.</p> <p>511ipa</p>

RESENE TIMBER & FURNITURE GEL

Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Solutions containing isothiazolinones may produce corrosion of the mucous membranes and cornea. Isopropanol vapour may cause mild eye irritation at 400 ppm.
Chronic	Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. In a teratogenic study in rats concentrations of up to 40 mg/kg 1,2-benzisothiazoline-3-one (BIT) were neither embryotoxic nor teratogenic. The isothiazolinones are known contact sensitisers. Severe exposure to triethylamine vapours may result in bronchitis, chemical inflammation of the lungs, pulmonary oedema and even death. Chronic effects of exposure to diuron may initially include skin irritation, or blurring of vision, liver enlargement; spleen and thyroid effects; red blood cell destruction; or reduction of the blood's oxygen carrying capacity with cyanosis (bluish discolourisation), weakness or shortness of breath by formation of methemoglobin. On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Long term or repeated ingestion exposure of isopropanol may produce incoordination, lethargy and reduced weight gain. Propylene glycol is though, by some, to be a sensitising principal following the regular use of topical creams by eczema patients.

RESENE TIMBER & FURNITURE GEL	TOXICITY	IRRITATION
	Not Available	Not Available
3-iodo-2-propynyl butyl carbamate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[2]	Eye: adverse effect observed (irreversible damage) ^[1]
	Inhalation (rat) LC50: 0.680 mg/l/4h ^[2]	Eye: Irritating
	Oral (rat) LD50: 1056 mg/kg ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
		Skin: Slight irritant
naphtha, petroleum, hydrodesulfurised heavy	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >4500 mg/kg ^[1]	Skin: adverse effect observed (irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	TOXICITY	IRRITATION
	Not Available	Not Available
triethylamine	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 416.1 mg/kg ^[2]	Eye (rabbit): 0.25 mg/24h SEVERE
	Inhalation (rat) LC50: 3.675 mg/l/1 h ^[1]	Eye(rabbit): 50ppm/30d int SEVERE
	Oral (rat) LD50: =460 mg/kg ^[2]	Skin (rabbit): 365 mg open mild
alcohols C12-14 secondary ethoxylated	TOXICITY	IRRITATION
	Not Available	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

RESENE TIMBER & FURNITURE GEL	The acute oral toxicity of propylene glycol is very low, and large quantities are required to cause perceptible health damage in humans. For trimethylbenzenes: Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure. Diuron is absorbed readily through the gut and lungs while uptake through the skin is more limited.
3-IODO-2-PROPYNYL BUTYL CARBAMATE	for 3-iodo-2-propynyl butyl carbamate (IPBC): Acute toxicity: Acceptable acute toxicity studies with IPBC indicate low toxicity except eye irritation.
NAPHTHA, PETROLEUM, HYDRODESULFURISED HEAVY	Studies indicate that normal, branched and cyclic paraffins are absorbed from the mammalian gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30.
TRIETHYLAMINE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. While it is difficult to generalise about the full range of potential health effects posed by exposure to the many different amine compounds, characterised by those used in the manufacture of polyurethane and polyisocyanurate foams, it is agreed that overexposure to the majority of these materials may cause adverse health effects. <ul style="list-style-type: none"> ▶ Many amine-based compounds can induce histamine liberation, which, in turn, can trigger allergic and other physiological effects, including bronchoconstriction or bronchial asthma and rhinitis. ▶ Systemic symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, tachycardia (rapid heartbeat), itching, erythema (reddening of the skin), urticaria (hives), and facial edema (swelling). <p>The material may produce severe irritation to the eye causing pronounced inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). Inhalation (human) TCLo: 12mg/m³/11W contin. Skin (rabbit)mild</p>
ALCOHOLS C12-14 SECONDARY ETHOXYLATED	Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved. Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products .

RESENE TIMBER & FURNITURE GEL

Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units:
 EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes)
 EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41
 EO > 15-20 gives Harmful (Xn) with R22-41
 >20 EO is not classified (CESIO 2000)
 Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) .
 AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC

In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats.

For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers):

Skin absorption: Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ethylene ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm²/hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.

The following information refers to contact allergens as a group and may not be specific to this product.
 Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.

No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

RESENE TIMBER & FURNITURE GEL	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
3-iodo-2-propynyl butyl carbamate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.067mg/L	2
	EC50	48	Crustacea	0.04mg/L	5
	EC50	72	Algae or other aquatic plants	0.022mg/L	2
	EC10	72	Algae or other aquatic plants	0.0058mg/L	2
NOEC	72	Algae or other aquatic plants	0.0046mg/L	2	
naphtha, petroleum, hydrodesulfurised heavy	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	72	Algae or other aquatic plants	=13mg/L	1
	NOEC	72	Algae or other aquatic plants	=0.1mg/L	1
	LC50	96	Fish	4.1mg/L	2
	EC50	48	Crustacea	4.5mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	LC50	96	Fish	4.1mg/L	2
	EC50	48	Crustacea	4.5mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	LC50	96	Fish	18mg/L	2
	EC50	48	Crustacea	1.4mg/L	2
	EC50	72	Algae or other aquatic plants	3.7mg/L	2
	LC50	96	Fish	4.1mg/L	2
	EC50	48	Crustacea	4.5mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	72	Algae or other aquatic plants	<0.1mg/L	1
LC50	96	Fish	0.00746mg/L	4	
EC50	48	Crustacea	0.058mg/L	4	
BCF	96	Fish	0.2mg/L	4	

Continued...

RESENE TIMBER & FURNITURE GEL

	NOEC	168	Crustacea	<=0.05mg/L	4
	LC50	96	Fish	4.1mg/L	2
	EC50	48	Crustacea	3.7mg/L	4
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	72	Algae or other aquatic plants	<0.1mg/L	1
	LC50	96	Fish	4.1mg/L	2
	EC50	48	Crustacea	4.5mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	72	Algae or other aquatic plants	<0.1mg/L	1
	LC50	96	Fish	0.14mg/L	2
	EC50	96	Algae or other aquatic plants	0.277mg/L	2
	NOEC	720	Crustacea	0.024mg/L	2
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
triethylamine	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	24mg/L	2
	EC50	48	Crustacea	17mg/L	2
	EC50	96	Algae or other aquatic plants	1.167mg/L	2
	NOEC	72	Algae or other aquatic plants	1.1mg/L	2
alcohols C12-14 secondary ethoxylated	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

May cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

For 1,2,4-trimethylbenzene:

Half-life (hr) air : 0.48-16

Half-life (hr) H2O surface water : 0.24-672

Half-life (hr) H2O ground : 336-1344

Half-life (hr) soil : 168-672

Henry's Pa m³ /mol: 385-627

Bioaccumulation : not significant

1,2,4-Trimethylbenzene is a volatile organic compound (VOC) substance.

For aromatic hydrocarbons:

Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus.

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters.

For surfactants:

Environmental fate:

Octanol/water partition coefficients cannot easily be determined for surfactants because one part of the molecule is hydrophilic and the other part is hydrophobic.

Diuron is a systemic substituted phenylurea herbicide.

The isothiazolinones are very toxic to marine organisms (fish, Daphnia magna and algae)

The high water solubility and low log Kow values of several chlorinated and non-chlorinated indicate a low potential for bioaccumulation.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
3-iodo-2-propynyl butyl carbamate	HIGH	HIGH
triethylamine	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
3-iodo-2-propynyl butyl carbamate	LOW (LogKOW = 2.4542)
triethylamine	LOW (BCF = 7.45)

Mobility in soil

Ingredient	Mobility
3-iodo-2-propynyl butyl carbamate	LOW (KOC = 365.3)
triethylamine	LOW (KOC = 107.2)

RESENE TIMBER & FURNITURE GEL

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Recycle wherever possible or consult manufacturer for recycling options.
-------------------------------------	--

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017

3-IODO-2-PROPYNYL BUTYL CARBAMATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)

NAPHTHA, PETROLEUM, HYDRODESULFURISED HEAVY IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemical Footprint Project - Chemicals of High Concern List
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
 New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)
 New Zealand Workplace Exposure Standards (WES)

METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

TRIETHYLAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)
 New Zealand Workplace Exposure Standards (WES)

ALCOHOLS C12-14 SECONDARY ETHOXYLATED IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

RESENE TIMBER & FURNITURE GEL

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (3-iodo-2-propynyl butyl carbamate; naphtha, petroleum, hydrodesulfurised heavy; methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; triethylamine; alcohols C12-14 secondary ethoxylated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (alcohols C12-14 secondary ethoxylated)
Japan - ENCS	No (alcohols C12-14 secondary ethoxylated)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)
Vietnam - NCI	Yes
Russia - ARIPS	No (methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; alcohols C12-14 secondary ethoxylated)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	27/04/2020
Initial Date	12/11/2015

SDS Version Summary

Version	Issue Date	Sections Updated
1.5.1.1.1	27/04/2020	Classification, Environmental, Physical Properties, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.