

net contents 500 mL

Must be mixed with the appropriate hardener. Makes 1 litre when mixed with 500 mL of Resene Alumastic Hardener.

LL50501B 10/21

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. May cause an allergic skin reaction. Causes mild skin irritation. May cause damage to organs. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Collect spillage. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing breathing difficulties seek medical attention.

If exposed or concerned get medical advice or attention. When seeking medical advice take this container with you.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Glycidyl Neodecanoate 10-150 g/L, Bisphenol A Diglycidyl Ether 420-850, Naphtha Petroleum light aromatic Solvent 10-150 g/L. For use as a decorative/protective coating.

For full technical instructions see Data Sheet RA402.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING
KEEP OUT OF REACH OF CHILDREN

Resene

Alumastic high-build epoxy base

Engineered Coating Systems



ALUMINIUM

Resene Alumastic is formulated with a unique blend of low-molecular weight resins, penetrants and surface active agents. This allows excellent wetting and penetration of rusted steel surfaces. Reaction occurs on the surface, setting the components into a high molecular weight, tough durable polymer. Self-priming maintenance coat over steel, rusted steel and galvanised steel.

General

• Safety Data Sheet (SDS) is available and must be consulted before use.
• In every case it is recommended that the current Resene Data Sheet is consulted for product data and surface preparation information.

- This product comprises a Base and Hardener, which must be mixed in the required ratio using an air or explosion-proof power mixer before application. Mix each component separately before blending them together. Add the total contents of the Hardener container to the total contents of the Base container. Once uniformly mixed, allow to stand for the recommended induction time prior to re-mixing and use.
- Thinning requirements may vary according to application method, equipment and environmental conditions.
- If thinning is required add recommended thinner after components have been blended and thoroughly re-mix using the power mixer.
- Ensure correct wet film thickness is applied to achieve desired dry film thickness. Allowance must be made for any thinner added.
- Use of incorrect thinner may have an adverse effect on application and performance.
- Drying is affected by low temperatures and high humidity.
- Ensure that the mixed product is used within the stated pot life. The pot life of the mixed product is given for a specific temperature. Higher temperatures will reduce the pot life, conversely lower temperatures will increase it.
- The temperature of the substrate should be 3°C above the "Dew Point".
- The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.
- Following appropriate preparation, all surfaces must be dry and clean prior to painting.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or reseller for your nearest Technical Representative.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



UN 3082, ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (PAINTS)

COMBUSTIBLE LIQUID

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Alumastic Base SDS



Alumastic TD3

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Manufactured under a quality system certified as complying with ISO 9001 by Telarc SAL, an accredited certification body. Printed on paper produced in manufacturing facilities which comply with environmental management systems EMAS and ISO 14001, using vegetable-based inks. Please recycle.

Quick check

Name: Resene Alumastic.

Generic type: Two component epoxy.

Colours: Bright Aluminium.

Finish: Metallic.

Primer required: Not normally.

Application method: Airless spray. Brush/roller: Suitable for small areas only. Use solvent resistant brushes or roller sleeves such as the PAL Strong Solvent sleeve.

Mixing ratio: 1 part Base: 1 part Hardener (by volume).

Induction time: 10-15 minutes.

Pot life: 4 hours at 21°C. Increased temperatures will shorten pot life.

Recommended dry film thickness (D.F.T.):

Typical exposure: 125 microns.

Severe exposure: 175 microns.

Theoretical coverage: 7.2 square metres per litre per coat at 125 microns D.F.T.

Dry time (minimum): 24 hours at 18°C (time to take light foot traffic). Drying is affected by low temperatures and high humidity. Cure time is considerably slowed below 10°C.

Thinning: Resene Thinner No.6.

Clean up: Resene Thinner No.12.

Resene Data Sheet: RA402.

Epoxies and polyaminoamides have been known to cause dermatitis and usual precautions to avoid skin contact should be taken.

A test patch is always recommended when applying over-aged paint systems to confirm compatibility. Do not apply over thermoplastic coatings, rubber or bitumen based coatings.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.