

SHAKE WELL BEFORE USE

# Resene

**Aquapel**  
**waterborne water**  
**repellent**  
**exterior/interior**

KEEP OUT OF REACH OF CHILDREN



9 418022 1027874

LL2791004F 11/12

# net contents 4 litres

LL2791004B 11/12

## WARNING

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Avoid inhaling spray mists.

## PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply.

## FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with plenty of soap and water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. When seeking medical advice take this container with you.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON  
(764 766) or call Resene 0800 737 363.  
For use as a water repellent on most porous building materials.

For full technical instructions see Data Sheet D65.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Aquapel is a water repellent treatment formulated to help control efflorescence and give a long-term water-beading effect to deter water penetration. May be used on its own or as a primer under waterborne coatings, especially Resene AquaShield mineral effect (see Data Sheet D601). Resene Aquapel will not prevent the penetration of driving rain or water under hydrostatic pressure.

## Preparation

- Ensure all surfaces to be treated are dry, free from dust, dirt and loose materials, oil and grease.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Flush clean with water.
- Remove oil and grease from surface using Resene Paint Prep and Housewash (see Data Sheet D812).
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• This product may be used to treat a wide variety of surfaces. If the surface you propose to treat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller.

## Application

- Resene Aquapel can only be used over a porous surface that will allow the treatment to penetrate. It cannot be applied over a fully sealed surface then overcoated.
- Saturate the surface with Resene Aquapel.
- Remove any Resene Aquapel that gets onto glass to avoid the risk of staining.
- If it starts to rain, immediately cease application and cover all treated areas that have yet to dry out.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.
- Maximum hydrophobicity (or water repellency) develops after a few days weathering.

## Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

## Quick check

**Use on:** Most porous building materials. May be used in multiple coats to keep concrete in its natural state looking good for longer by minimising the opportunity for moss, mould and lichen growths.

**Gloss level:** None – fully penetrating.

**Typical coverage:** Dependent on surface porosity – typically 2.5 square metres per litre for concrete block, 11 square metres per litre for concrete (tilt and precast), 5-6 square metres per litre for concrete plaster.

**Dry time (minimum):** Penetrates – up to 48 hours.

**Recoat time (minimum):** 6 hours.

**Primer required:** No.

**Usual number of coats:** One.

**Application method:** Low pressure spray is best, brush or roller.

**Thinning:** Supplied ready to use – do not thin.

**Clean up:** Water when wet; mineral turps when dry.

**Colour range:** Clear.

**Product ingredients** will settle on storage. Shake well to reincorporate before application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Aquapel SDS

# Resene

the paint the professionals use



Aquapel TDS

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207

Phone 1800 738 383 Fax 1800 064 960

Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited

Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045

Phone (04) 577 0500 Fax (04) 577 0600

Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO 9001 by Telarc, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using U.V. inks ensuring no emissions.