

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

LL5440001 5/24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAYS. DO NOT EAT, DRINK OR SMOKE WHILE USING. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Wash all exposed external body areas thoroughly after handling. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment. Collect spillage. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

If exposed or concerned, seek medical advice.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Xylene 10-75 g/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet RA30A.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

IN CASE OF FIRE: Use foam, CO₂, dry chemical for extinction.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene ArmourX Rust-Arrest anti-corrosive primer



Resene ArmourX Rust-Arrest is a lead and chromate free primer developed for use on steel where optimum surface preparation is not practical. Resene ArmourX Rust-Arrest has good surface wetting properties and protects via passivating pigments.

Preparation

• For rusted areas, scrub down using Resene Roof and Metal Wash (see Data Sheet D88). Do not allow the wash solution to dry out on the surface or on window glass or joinery. Rinse clean or hose down with copious amounts of freshwater ensuring all wash solution is removed.

• Remove as much red rust as is practicable. Remove all paint that is flaking or unsound with mechanical methods, such as a 3M Rust and Paint Removal Disc, to leave only sound adherent corrosion products taking care not to damage either the substrate or the surrounding areas. Where under-film corrosion is taking place, remove the existing paint and under-film corrosion products following the process above taking care not to damage sound zinc coated areas. Feather all paint edges to a smooth finish.

Mixing and Application

• Mix the paint thoroughly before use. Efficient mixing at all stages requires power mixing with an air or explosion proof mixer until uniformly blended.

• Thinning requirements may vary according to application method, equipment and environmental conditions. Excessive thinning will reduce the dry film build and may result in the appearance of runs or sags in the coating. Use of the incorrect thinner may have an adverse effect on application and performance. After thinning thoroughly re-mix using the power mixer.

• Ensure the correct wet film thickness is applied to achieve the required dry film thickness. Allow for any thinner added.

• Drying is affected by low temperatures and high humidity.

• The temperature of the substrate should be 3°C above the "Dew Point". The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.

• Following appropriate preparation, all surfaces must be dry and clean prior to painting.

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or reseller for your nearest Resene Technical Representative.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your painting on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



Resene
the paint professionals

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, Qld 4214
Ph 1800 738 383 Visit resene.com.au
In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre,
Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Resene
Automotive & Light Industrial

Resene Automotive & Light Industrial
PO Box 62282, Sylvia Park, Auckland 1644
Call (09) 259 2738
Visit reseneauto.co.nz

Quick check

Use on: Steel.

Generic type: Alkyd anti-corrosive primer (inhibitive).
Finish: Low sheen.

Coverage: 13.75 square metres per litre per coat at 40 microns D.F.T. 11 square metres per litre per coat at 50 microns D.F.T.

Recommended dry film thickness (D.F.T.): 40-50 microns per coat.

Dry time (minimum): Surface dry: 4 hours at 20°C. Hard dry: 24 hours at 20°C. Drying is affected by low temperatures and high humidity.

Recoat time (minimum): Acrylic/alkyd: 24 hours at 20°C (minimum), one month (maximum). Sand Resene ArmourX Rust-Arrest if recoating beyond the maximum recoating time.

Usual number of coats: One (two for severe exposure or when topcoating with an acrylic system).
Application method: Brush, roller or conventional spray.

Thinning and clean up: Resene Thinner No.10 (brush/roller application); Resene Thinner No.12 (spray application).

Colour: Red oxide.

Limitations: Do not apply directly to zinc rich surfaces, such as bare galvanised steel, Zincalume, or zinc primers. Not recommended for immersion service. Not designed for exterior exposure without overcoating. Do not topcoat with strong solvent containing or two component topcoats.

Before use: Stir with a wide, flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. Read the appropriate Product Data Sheet and Safety Data Sheet before use.

FLAMMABLE LIQUID AND VAPOUR
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.