

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Armourchlor HB-F high-build finish

chlorinated rubber

Engineered Coating Systems

A-LL49404B 7/14

WARNING

Read label before use. Keep out of reach of children. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply.

FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Get medical attention without delay.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing and wash before re-use. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

INHALATION: Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Chlorinated paraffin 105-115 gms/L, Epoxy resin 10-15 gms/L. For use as a decorative/protective coating. For full technical instructions see Data Sheet RA61.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

FIRE: Use foam, carbon dioxide or dry chemical powder.



WHITE

Resene Armourchlor HB-F is a single pack high build chlorinated rubber finish coat providing outstanding resistance to corrosion in severe atmospheres, where it may be difficult or uneconomic to employ a two pack coating. These characteristics ensure maintenance free performance during many years' exposure in highly corrosive environments.

General

- Safety Data Sheet (SDS) is available and must be consulted before use.
- In every case it is recommended that the current Resene Data Sheet is consulted for product data and surface preparation information.
- This product must be thoroughly mixed before use. Efficient mixing at all stages requires power mixing with an air or explosion proof mixer until uniformly blended.
- Thinning requirements may vary according to application method, equipment and environmental conditions.
- If thinning is required thoroughly re-mix using the power mixer.
- Ensure correct wet film thickness is applied to achieve desired dry film thickness. Allowance must be made for any thinner added.
- Use of incorrect thinner may have an adverse effect on application and performance.
- Drying is affected by low temperatures and high humidity.
- The temperature of the substrate should be 3°C above the "Dew Point".
- The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.
- Following appropriate preparation, all surfaces must be dry and clean prior to painting.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or Reseller for your nearest Technical Representative.

net contents 4 litres
(includes tinters in base)

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/open flames/hot surfaces.
No smoking.

UN NO. 1263 – PAINT RELATED MATERIAL



Resene

the paint the professionals use



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Name: Resene Armourchlor HB-F.

Generic type: Chlorinated rubber.

Colour: White, selected BS 381C, 2660, 5252, Resene Total Colour System, Whites & Neutrals and MIOX Colours.

Finish: Gloss (initially).

Application method: Airless or conventional spray.

Recommended dry film thickness (D.F.T.): Up to 125 microns per coat.

Theoretical coverage: 2.4 square metres per litre at 125 microns D.F.T.

Dry time (minimum): Touch: 2 hours at 18°C. Drying is affected by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time: Minimum: 12 hours at 18°C. Maximum: Indefinite when overcoating with chlorinated rubber based coating.

Thinning and clean up: Resene Thinner No.6.

Resene Data Sheet: RA61.

Limitations: Poor resistance to aromatic solvents. Not resistant to vegetable oils or animal fats. Will soften at temperatures over 50°C. Chalks in exposed situations.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.