



## WARNING

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

## PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

## FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with plenty of soap and water/shower. If skin irritation or rash occurs: get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: get medical attention/advice. When seeking medical advice take this container with you.

Further information can be obtained from AUST. POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as an interior surface preparation coating. For full technical instructions see Data Sheet D810.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Broadwall 3 in 1 is a very low VOC product designed for use over stopped and jointed wall systems in place of traditional surfacers and sealers. It equalises surface porosities; smooths minor surface irregularities; minimises textural differences; and provides a perfect base for subsequent Resene finishes. A key element to achieving a level 5 finish on paperfaced plasterboard. Suitable for use as a surfacer, sealer and finish coat on ceilings in dry areas.

## Preparation

- Ensure surfaces to be painted are dry, free from dust, grease, loose material and weak, powdery or uncured jointing compound.
- Fill cracks and holes with an appropriate filler before painting.
- Where staining is present the source of staining must be removed.
- Remove excess jointing compounds where possible by sanding down to a smooth surface and wipe with a damp cloth to remove dust.
- When preparing paperfaced plasterboard, avoid sanding the paper as this will cause furring and unacceptable textural differences in the finish.
- Where the paper surface has yellowed due to prolonged exposure to light or is stained, use Resene Sureseal (see Data Sheet D42).
- Plasterboard must be prepared to an appropriate level of finish. Resene Broadwall 3 in 1 is recommended for critical lighting areas.

**All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- This product is typically used on new plaster and plasterboard. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

## Application

- Refer to Resene Broadwall Application Guide for full application information.
- Resene Broadwall 3 in 1 may be applied by airless spray.

If brush or roller application is desired, use Resene Broadwall Surface Prep & Seal (see Data Sheet D807).

- Apply by airless spray following the recommendations in the quick check panel. Lightly sand with a pole sander to produce a smooth surface and wipe with a clean, damp sponge to remove dust. Wear a well-fitted dust mask when sanding Resene Broadwall 3 in 1.
- Over plasterboard in dry broadwall areas, Resene Broadwall 3 in 1 may be used as a surfacer and sealer ready for topcoating. On ceiling areas in non wet areas, Resene Broadwall 3 in 1 may be used as a surfacer, sealer and finish coat. Over new paperfaced plasterboard In wet areas, use Resene Broadwall 3 in 1 as the surfacer, then apply Resene Sureseal before topcoating.
- When overcoating with waterborne paints, the coverage of that first coat may vary with application method, technique and temperature. If necessary, thin it with up to 10% clean tap water to maintain recommended coverage.
- Resene Broadwall 3 in 1 is a high build product that may be applied at high film thicknesses, releasing large volumes of moisture into the air. Maintain good ventilation throughout the drying and curing period to ensure the coating is properly cured. Poor ventilation may inhibit curing and performance.

## Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

# Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited  
Vogel Street, Lower Hutt, PO Box 38-242, Wgtn Mail Centre  
Phone (04) 577 0500 Fax (04) 577 0600  
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

## Quick check

**Use on:** Interior paperfaced plasterboard and jointing compounds.

**Gloss level:** Flat.

**Coverage:** As a sealer – one coat at 7 square metres per litre per coat.

As a ceiling finish – one coat at 7 square metres per litre, allow to dry 1-2 hours then apply a second coat at 5 square metres per litre.

As a surfacer – one coat at 2.5 square metres per litre per coat.

**Dry time (minimum):** 4 hours. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 4 hours.

**Usual number of coats:** One or two.

**Application method:** Airless spray (refer to Data Sheet D810 for details).

**Colour range:** White and colours off white.

**Before use:** Stir well with a wide flat stirrer.

**Clean up:** Water.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 RESENE (NZ) or visit the Resene website.