

KEEP OUT OF REACH OF CHILDREN

Resene

Clearcoat UVS

waterborne U.V. protective glaze

exterior

WARNING

KEEP OUT OF REACH OF CHILDREN



LL28404F 10/23

net contents

4 litres

LL28404B 10/23

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause an allergic skin reaction. Harmful to aquatic life.

PRECAUTIONS

AVOID BREATHING MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE
131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE
0800 POISON (764 766) or call Resene
0800 737 363.

CONTAINS: Benzotriazol derivatives 10-55 g/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D502.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and store in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water on grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Clearcoat UVS is based on a unique acrylic-urethane for ease of application and maximum life over painted surfaces. Formulated with U.V. absorbers, Resene Clearcoat UVS filters out harmful U.V. light, protecting the underlying coloured coat. Ideally suited for direct application to freshly painted bright organic hues and shades to aid colour retention by protecting these more vulnerable pigments against fading.

Preparation

• Ensure surfaces to be painted are in sound condition, dry, free from dirt, dust and loose material.

• Oil and grease must be removed using Resene Paint Prep and Housewash (see Data Sheet D812). If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry must be treated (see Data Sheet D83).

• All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate-based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or reseller.

Application

• To avoid foaming of material, do not shake and do not brush excessively. Stir well with a wide flat stirrer prior to application.

• Allow at least two hours between coats.

• Do not apply in direct sunlight.

• Do not apply over solventborne paint finishes.

• Not recommended for exterior tile or decorative aggregate flooring where ponding occurs.

Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Quick check

Use on: Exposed colours that may be prone to fading. Not for use on opening sashes and doors. Do not apply over solventborne paint finishes.

Gloss level: Gloss.

Coverage: 12 square metres per litre per coat. Coverage will vary dependent upon surface porosity and profile.

Dry time (minimum): 45 minutes at 18°C. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.

Usual number of coats: 1.

Application method: Brush, roller (Resene No.10 Waterborne Clears sleeve) or airless spray.

Thinning and clean up: Water. In hot conditions may be thinned with up to 5% Resene Hot Weather Additive to slow drying.

Colour range: Clear.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



Clearcoat SDS

Resene

the paint the professionals use



Clearcoat TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz