

Resene

Concrete Clear

waterborne coating

exterior/interior

WARNING

KEEP OUT OF REACH OF CHILDREN



9 418022 060000

SATIN

LL2870301F 8/14



net contents 1 litre

LL2870301B 8/14

WARNING

Read label before use. Keep out reach of children. Harmful if swallowed. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves/protective clothing/eye and face protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with plenty of soap and water/shower. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Polyurethane polymer 300-400 gms/L, mixed fungicides <5gms/L.

For use as a decorative/protective coating. For full technical instructions see Data Sheet D54a.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Concrete Clear is a tough waterborne glaze for use on masonry and brick surfaces to enhance its colour and natural beauty. It also increases the durability of high build waterborne specialist coatings. Resene Concrete Clear can also be used over solid colour or metallic decorative paint finishes.

Preparation

- Ensure surfaces to be coated are in sound condition, dry, free from dirt, oil (including form oil), release agents, dust, loose material and salt. Remove accumulated windblown salt by prolonged washing with clean water.
- Waterblasting is the best surface preparation prior to coating of weathered cementitious surfaces.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Efflorescence on masonry must be treated (see Data Sheet D83).
- Wherever oil and grease are present ensure the surface to be coated is thoroughly cleaned using Resene Paint Prep and Housewash (see Data Sheet D812). Flush clean with water.
- On porous and cementitious substrates, use Resene Solventborne Aquapel (see Data Sheet D655) as a pretreatment.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Do not shake contents, rather stir well with a wide flat stirrer.
- Brick, fibre cement and cementitious surfaces - apply first coat thinned with 10% water. Apply second and third coats undiluted.
- On very porous substrates, the first coat can be thinned up to 10% with water. When using Resene Concrete Clear satin or flat on a porous or unsealed surface, use Resene Concrete Clear gloss as the first coat.
- Allow at least two hours between coats.
- To avoid foaming of material, do not shake and do not brush excessively.
- Do not apply in direct sunlight.
- Not recommended for exterior tile or decorative aggregate flooring where ponding occurs.
- Where weathertight issues exist, a pigmented high build system, such as Resene X-200 (see Data Sheet D62), is recommended.
- Application to exterior substrates will not give weathertightness; if weathertightness is required use the Resene XC-700 system (see Data Sheet D509).

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Quick check

Use on: Existing waterborne and high build coatings, concrete, masonry surfaces, plaster, brick work and fibre cement.

Gloss level: Flat, satin and gloss.

Typical coverage: 12 square metres per litre per coat, coverage will vary with surface porosity.

Coverage will vary dependent upon surface porosity and profile.

Dry time (minimum): 30 minutes at 18°C. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period.

Recoat time (minimum): 2 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Usual number of coats: Three.

Primer required: Yes on porous and cementitious substrates.

Application method: Brush, roller (Resene No.10 Waterborne Clears sleeve) or spray.

Thinning and clean up: Water. On very porous surfaces the first coat may be thinned with up to 10% clean water.

Colour range: Milky - dries clear.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



Concrete Clear SDS



Concrete Clear TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.