

Resene

Concrete Wax
waterborne satin glaze
interior



9 418022 059806

CLEAR

LL288001F 8/16

SAFETY PRECAUTIONS

Read label before use. Keep out reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Continue rinsing. If eye irritation persists: Get medical attention or advice.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If exposed or concerned get medical attention. When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D508.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Concrete Wax is a tough waterborne satin glaze for use on concrete floors and benchtops. Scratches can be easily repaired with a light sand, feathering of the edges and overcoating to keep the surface in good condition. May also be used as an interior clear finish over waterborne paints, such as Resene Walk-on flooring and paving paint.

Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, curing and release membranes, oil and salt.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Efflorescence on masonry **must be treated** (see Data Sheet D83).
- It is recommended that the surface is diamond ground, followed by a thorough wash to ensure all dust and unbound surface material is removed.
- If the floor has been ground, mop with water to remove residual engrained dust.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Coat floors using a Swish mop (lambswool floor applicator) and a synthetic brush for cutting-in. Smaller areas may be brushed and rolled using a speed brush or Resene No.10 Waterborne Clears roller sleeve.
- While the product is supplied at application viscosity thinning with up to 30% with clean water is required for application of the first coat. Apply up to four coats of Resene Concrete Wax allowing at least two hours between coats. The surface is sealed when water splashed onto the dried coated surface does not cause darkening of the concrete.
- Do not brush or roll excessively to avoid excess foaming of the material. Lay-off with care.
- Do not apply in direct hot sunlight.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

Maintenance (after a minimum of four weeks' drying)
Clean as you would vinyl flooring. Avoid cleaning products containing high levels of solvent.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Concrete Wax
SDSConcrete Wax
TDS**Quick check**

Use on: Concrete benchtops and floors.

Gloss level: Satin.

Coverage: 16 square metres per litre per coat.

Dry time (minimum): Touch dry 30 minutes. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.

Primer required: No.

Usual number of coats: 3-4 (varies with surface porosity).

Application method: Swish mop or roller. Brush application suitable for cutting in only.

Thinning: While the product is supplied at application viscosity thinning with up to 30% with clean water is required for application of the first coat. Subsequent coats may be thinned with up to 5% clean tap water if required.

Clean up: Water.

Colour range: Milky – dries clear.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beemleigh, Qld 4207
Phone. 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.