

# Resene Crackle

crackle effect



9 418022 026570

375ml

Creating unique broken, antique looking finishes is quick and easy with Resene Crackle.

- Simply brush apply one coat of your chosen tinted acrylic basecoat (such as Resene Lumbersider) onto the surface you wish to coat at a spreading rate of 10 square metres per litre and allow to dry. Do not use a waterborne enamel as the basecoat or topcoat as the Resene Crackle only works with standard acrylic finishes.
- Apply one coat of Resene Crackle and allow to dry. Dry time is generally 30-40 minutes depending on temperature and humidity. Allow at least two hours before recoating.
- Apply one coat of an acrylic topcoat tinted to a contrasting colour to the basecoat. Resene Crackle will cause the topcoat to shrink and crack revealing the basecoat colour.
- If a clear overcoat is desired, use a product from the Resene Qristal Clear range as a waterborne polyurethane may react with the effect.
- The crackle effect will vary depending on the application method, basecoat and topcoat used. Always try out a sample panel before starting the project.
- Crackle effect finishes are best used on uneven or rough walls, furniture, picture frames, woodwork and small feature areas. Interior use only.
- First aid is generally not required. If in doubt contact the NZ Poisons Centre 0800 POISON (764 766), Australian Poisons Information Centre 131 126 or a doctor.

**Resene**

the paint the professionals use

LLCRACKLE37 9/12

**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924,  
Beenleigh, Qld, 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email [advice@resene.com.au](mailto:advice@resene.com.au)  
or visit [www.resene.com.au](http://www.resene.com.au)

**In New Zealand:** Resene Paints Limited  
Vogel Street, PO Box 38242,  
Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email [advice@resene.co.nz](mailto:advice@resene.co.nz)  
or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using U.V. inks ensuring no emissions.