

net contents 1 litre

Must be mixed with the appropriate base. Makes 2 litres when mixed with 1 litre of Resene Epox-O-Bond Epoxy Filler Base.

LL88101H 2/16

WARNING

Read label before use. Keep out of reach of children. Harmful if swallowed. Harmful in contact with the skin. May cause an allergic skin reaction. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Wear protective gloves and clothing, eye and face protection. Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Remove immediately all contaminated clothing and wash before reuse. Rinse skin with plenty of water. If skin irritation or rash occurs, get medical attention or advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention or advice.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call POISON CENTRE, doctor or physician.

If exposed or concerned: Get medical advice or attention.

If medical attention is required: have product container or label at hand.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Ethylenediamine <10 gms/L, Benzyl Alcohol 10-100 gms/L, Benzene-1,3-Dimethanamine 10-100 gms/L, 3-(Diethylamino)-1,2-Propanediol 10-100 gms/L, N-[3-(Trimethoxysilyl)Propyl]Ethylenediamine 10-100 gms/L, Bisphenol A 10-100 gms/L, Isopentane <10 gms/L, N,N-Bis[3-(Trimethoxysilyl)Propyl]Ethylenediamine <10 gms/L, N,N-Bis[3-(Trimethoxysilyl)Propyl]Ethylenediamine <10 gms/L.

Ethylenediamine <10 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D806.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

FIRE: Blanket flames with dry chemical, carbon dioxide or foam. Closed containers may explode when exposed to extreme heat.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Epox-O-Bond Epoxy Filler HARDENER

Engineered Coating Systems



Resene Epox-O-Bond is a two component filler or surfacing compound with excellent non sag and gap filling qualities. An ideal product for applications requiring gap filling or as a fairing product for rough surfaces. Epox-O-Bond Epoxy Filler adheres to a wide range of materials. It is not designed for flexible materials nor certain plastics.

General

- Safety Data Sheet (SDS) is available and must be consulted before use.
- In every case it is recommended that the current Resene Data Sheet is consulted for product data, application guidelines and surface preparation information.
- The paint must be thoroughly mixed before use. Efficient mixing at all stages requires power mixing with an air or explosion proof mixer until uniformly blended.
- Thinning requirements may vary according to application method, equipment and environmental conditions. Excessive thinning will reduce the dry film build and may result in the appearance of runs or sags in the coating.
- After thinning thoroughly re-mix using the power mixer.
- Ensure correct wet film thickness is applied to achieve desired dry film thickness. Allowance must be made for any thinner added.
- Use of incorrect thinner may have adverse effect on application and performance.
- Drying is affected by low temperatures and high humidity.
- Ensure that the mixed product is used within the stated pot life. The pot life of the mixed product is given for a specific temperature. Higher temperatures will reduce the pot life, conversely lower temperatures will increase it.
- The temperature of the substrate should be 3°C above the "Dew Point".
- The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.
- Following appropriate preparation, all surfaces must be dry and clean prior to painting.
- This product may be used to paint a wide variety of

surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop for your nearest Technical Representative.

Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure for full cleaning instructions or the Resene website.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



COMBUSTIBLE LIQUID

Keep away from heat, sparks, open flames, hot surfaces. No smoking.

UN NO 3066 – PAINT, CORROSIVE



Epox-O-Bond Filler Hardener SDS



Epox-O-Bond Filler TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Name: Resene Epox-O-Bond Epoxy Filler Hardener.

Mixing ratio: 1 part Base, 1 part Hardener (by volume).

Pot life: Workable life of 250gm of mixed product at 25°C is 25-30 minutes. May be extended by spreading mixed product out in a shallow container or mixing smaller quantities. Cooler temperatures will extend pot life.

Clean up: Uncured epoxy may be removed with a strong detergent solution or Resene Thinner No.12. Cured material requires abrasion, chipping, sanding or planing.

Epoxy and polyaminoamides have been known to cause dermatitis and usual precautions to avoid skin contact should be taken.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.