

**WARNING**  
KEEP OUT OF REACH OF CHILDREN

# Resene

## Graffiti Cleaner ready to use

net contents 4 litres

Resene Graffiti Cleaner is formulated for effective and easy removal of graffiti from Resene Engineered Coating Systems anti-graffiti coatings. Very effective against common materials used for graffiti, such as spray paint, permanent markers, inks, crayons and lipsticks. NMP free.

### Directions

Protect skin and eyes at all times with approved safety equipment.

1. Wet graffiti with Resene Graffiti Cleaner. Wait 3-5 minutes ensuring area is kept moist with Resene Graffiti Cleaner. Wipe clean with clean white rags (**Do not re-use rags**).
2. If more than two applications of Resene Graffiti Cleaner are needed to remove stubborn graffiti, rinse the area with clean water and wipe dry before each additional application.
3. Removal of aged graffiti or from absorbent substrates may require scrubbing with a soft natural bristle brush.
4. Rinse all Resene Graffiti Cleaner cleaned surfaces with water. Allow surface to dry.
5. Discard dampened wiping rags in a closed container. Treat as combustible.
  - Resene Graffiti Cleaner should only be used on solvent resistant finishes.
  - Graffiti removal becomes more difficult as it ages.

LL82404 11/11

### WARNING

Read label before use. Causes mild skin irritation. Causes eye irritation. May cause an allergic skin reaction. Harmful if swallowed or in contact with the skin. Suspected of damaging organs through prolonged or repeated exposure. Harmful if inhaled.

### PRECAUTIONS

**AVOID BREATHING FUMES/VAPOURS.** Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke whilst handling this product. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Store locked up. Wear protective gloves, eye/face protection. Use other personal protective equipment as required. Wash thoroughly after handling.

### FIRST AID

**IF SWALLOWED:** Rinse mouth.

**IF ON SKIN (or hair):** Remove/take off all contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/shower. If skin irritation or rash occurs get medical advice/attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

**IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTRE or a doctor/physician if you feel unwell. For advice, contact a Poisons Information Centre: Australia 131 126; New Zealand 0800 764 766, or a doctor. If exposed or concerned:

get medical advice/attention. When seeking medical advice take this container with you.

Further information can be obtained from.  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Benzenemethanol 255-280 gms/L.

For removal of graffiti from selected Resene Engineered Coatings Systems anti-graffiti coatings.

For full technical instructions see Data Sheet RA101.

**SPILLS:** Eliminate all sources of ignition. Ventilate area, avoid breathing vapours. Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove. Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

**IN CASE OF FIRE OR EXPLOSION:** Use foam, CO<sub>2</sub>, dry chemical for extinction

### Recommended safety equipment

Safety glasses with side shields, protective clothing and gloves (neoprene or butyl rubber) should be worn when using this product. Polyethylene or polypropylene trigger pack. Clean rags, soft natural bristle brush.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



### COMBUSTIBLE LIQUID

Keep away from ignition sources such as heat/sparks/open flame/hot surfaces. No smoking.

# Resene

the paint the professionals use

**In Australia:** Resene Paints (Aust) Limited

7 Production Ave, PO Box 785, Ashmore City, Queensland, 4214  
Phone 1800 738 383 Fax 1800 064 960

Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

**In New Zealand:** Resene Paints Limited

Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600

Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

