

WARNING

KEEP OUT OF REACH OF CHILDREN

LL82401 9/19

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Harmful if swallowed. May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life. Toxic to the soil environment. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT BREATHE DUST, FUME, GAS, MIST, VAPOUR OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor IMMEDIATELY.

Call a POISON CENTRE or a doctor/physician if you feel unwell. For advice, contact a Poisons Information Centre: Australia 131 126; New Zealand 0800 764 766, or a doctor. If exposed or concerned get medical advice or attention. When seeking medical advice take this container with you.

Further information can be obtained from:

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: Ethylene Glycol Monobutyl Ether 290-590 gms/L, Benzyl Alcohol 90-300 gms/L.

For removal of graffiti from selected Resene Engineered Coatings Systems anti-graffiti coatings.

For full technical instructions see Data Sheet RA101.

SPILLS: Eliminate all sources of ignition. Ventilate area, avoid breathing vapours. Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove. Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

IN CASE OF FIRE OR EXPLOSION: Use foam, CO₂, dry chemical for extinction.

Recommended safety equipment

Safety glasses with side shields, protective clothing and gloves (neoprene or butyl rubber) should be worn when using this product. Polyethylene or polypropylene trigger pack. Clean rags, soft natural bristle brush.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

Graffiti Cleaner

ready to use

net contents 1 litre

Resene Graffiti Cleaner is formulated for effective and easy removal of graffiti from Resene Engineered Coating Systems anti-graffiti coatings. Very effective against common materials used for graffiti, such as spray paint, permanent markers, inks, crayons and lipsticks. NMP free.

Directions

Protect skin and eyes at all times with approved safety equipment.

1. Wet graffiti with Resene Graffiti Cleaner. Wait 3-5 minutes ensuring area is kept moist with Resene Graffiti Cleaner. Wipe clean with clean white rags (**Do not reuse rags**).
2. If more than two applications of Resene Graffiti Cleaner are needed to remove stubborn graffiti, rinse the area with clean water and wipe dry before each additional application.
3. Removal of aged graffiti or from absorbent substrates may require scrubbing with a soft natural bristle brush.
4. Rinse all Resene Graffiti Cleaner cleaned surfaces with water. Allow surface to dry.
5. Discard dampened wiping rags in a closed container. Treat as combustible.
 - Resene Graffiti Cleaner should only be used on solvent resistant finishes.
 - Graffiti removal becomes more difficult as it ages.



COMBUSTIBLE LIQUID

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz



Graffiti Cleaner
SDS



Graffiti Cleaner
TDS

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

