

WARNING

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell

IF ON SKIN (OR HAIR): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with plenty of soap and water/ shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

For use in cleaning interior painted surfaces.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene

Interior Paintwork Cleaner

concentrate

net contents 250ml

Resene Interior Paintwork Cleaner is a labour saving non-dulling neutral cleaner designed for use on all interior painted surfaces. Quick and easy to use, it dries film-free eliminating the need for rinsing.

This pack is supplied as a concentrate. Dilute before use. For light soiling dilute 1:60 with water; for medium soiling dilute 1:50 with water; for heavy soiling dilute 1:40 with water.

- Dip a soft lint free cloth, such as a Jif Ballerina, into the diluted detergent solution. Do not saturate the cloth as this could lead to runs and streaking. If using a spray pack, apply the Paintwork Cleaner direct to the surface you wish to clean.
- Using light strokes, thoroughly wipe the area to be cleaned turning the cloth frequently to maintain a clean edge. Wipe away any excess solution. Wring the cleaning cloth out into an empty bucket before reapplying further detergent solution. This will minimise the appearance of streaks. In order to achieve an even finish, finally wipe using a soft dry lint-free cloth in the direction of the paint flow.
- If trying to remove a localised mark, start from a radius wide of the mark and work towards it. This will minimise any 'tide mark' that might develop.
- Always test the cleaning method in an inconspicuous area to ensure the cleaning process you plan to use does not damage the finish of the paint. Wait until the test area has dried before using the same technique on more conspicuous areas. Walls may appear discoloured as they absorb the water, but should dry back to their original colour.
- Do not vigorously scrub the surface nor use an abrasive and strong detergent as you will burnish the paint surface and mar the paint finish. Do not wash walls for a month after painting, as acrylic paints require this period of time to fully cure.

In every case it is recommended that the appropriate Safety Data Sheet is consulted prior to application.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using U.V. inks ensuring no emissions.



9 4 1 8 0 2 2 0 2 4 3 0 9