



NET CONTENTS **250ML**

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May be harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONS & FIRST AID

Avoid breathing dust, fumes, gas, mists, vapours or sprays. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

IF SWALLOWED: Rinse mouth immediately. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN OR HAIR: Remove all contaminated clothing immediately. Rinse skin with plenty of water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you. If exposed or concerned get medical advice or attention.

Further information can be obtained from AUS: POISONS INFORMATION CENTRE 131 126 or call Resene on 1800 738 383. NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene on 0800 737 363.

CONTAINS: Naphtha (petroleum), hydrotreated heavy 160-340 gms/L.

For use as a decorative/protective coating.

SPILLS

Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

KAREN WALKER
PAINTS

VINTAGE
WAX

WARNING
KEEP OUT OF REACH OF CHILDREN

Add colour, upcycle or rejuvenate walls, furniture, ceilings and accessories with the Karen Walker Chalk Colour range from Resene. Depending on the look you want to create, apply 1-2 coats of Karen Walker Chalk Colour and finish with Karen Walker Vintage Wax if you wish.

Karen Walker Vintage Wax is easy to apply and can be used on bare timber, many stained timbers and painted finishes. Painted finishes usually already have enough protection provided by the paint so don't have to be waxed, but if you prefer an aged or antiqued waxed look finish, this wax will work well over painted surfaces too. It is also available in a clear Soft Wax finish.

PREPARATION

For most surfaces, as long as the surface is clean, you can start waxing. For surfaces with moss and mould, always treat this before you paint or wax using Resene Moss & Mould Killer. If left untreated mould will grow through the new finish.

QUICK TIPS FOR WAXING

Dip the tip of your brush to avoid applying too much wax. You can also apply it with a lint free cloth. Once you have applied the wax, lightly buff or wipe with a lint free cloth for an even finish. Don't worry if it doesn't look quite right or you apply too much - you can easily wipe it off until you get the right look.

Dry time (minimum): 4-5 minutes. This will be slower in colder temperatures and with higher humidity. Allow two hours before recoating. Clean up with mineral turpentine.

Reapply more wax every 1-2 years or as needed, depending on wear and tear and the look you prefer.

WHICH WAX TO CHOOSE

When waxing most timbers, the Soft Wax is recommended. If you are waxing particularly dark timber you may wish to use the Vintage Wax to add a little more colour. For an antiqued or aged finish, use Karen Walker Vintage Wax.

This is a pretinted wax that is designed to help you easily create an antiqued or vintage look on your projects. The darker wax will enhance any distressed areas of your project. When applying over a stained finish, you can use the Soft Wax so that the stain colour can show through, or the Vintage Wax if you want to give your stained finish an antiqued or aged look.

KEEPING IT CLEAN

You can wipe surfaces finished in Karen Walker Soft Wax once they have been left to fully cure for a month. Clean using Resene Interior Paintwork Cleaner using the instructions on pack or in the Resene Caring for your Paint Finish brochure, available on the Resene website or at your local Resene ColorShop or reseller.

Please ensure that this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



UN NO. 1263 - PAINT RELATED PRODUCT
FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, sparks, open flames and hot surfaces.
No smoking.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207
Ph 1800 738 383 visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.