

net contents 250ml

LL79125 10/14

WARNING
KEEP OUT OF REACH OF CHILDREN

WARNING

Read label before use. Keep out of reach of children. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

AVOID BREATHING DUST/FUMES/GAS/MISTS/VAPOURS/SPRAYS.

Store in original or correctly labeled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves, clothing and eye or face protection. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

SWALLOWED: If ingested give water to dilute. Do not cause vomiting. Get medical attention without delay.

IF SKIN irritation or rash occurs: get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

INHALATION: Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

When seeking medical advice take this container with you. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON
(764 766) or call Resene 0800 737 363.

CONTAINS: 3-iodo-2-propynyl Butyl Carbamate 10-30 gms/L, Carbon Black 0-60 gms/L, Octadecylamine Ether, Ethoxylated 0-60 gms/L, Diuron 0-20 gms/L.

For use in tinting Resene decorative paints.

SPILLS

Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

Resene

Master

Painters

Stainers



Application

- Resene MPS Stainers are multi-purpose colourants that have been tested for use in Resene decorative undercoats and topcoats. They are not recommended for use in purpose built primers. They are not designed for use at greater than 50ml per litre of paint in total. Resene does not recommend and cannot guarantee the compatibility of Resene tinters at higher levels than stated or in non-Resene products.
- The use of Bright Yellow and Bright Red is recommended for interior use only.
- Incorporate with thorough stirring.
- For tinting paint only – do not use alone.
- Tint paint before thinning.
- Do not add water, thinner, oil or any other substances to the colourant.
- Do not allow tint to remain in paint unmixed – incorporate immediately.
- Do not use to tint Engineered Coating Systems products.



Resene
the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, QLD 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.