

**WARNING**

KEEP OUT OF REACH OF CHILDREN

# Resene

## Masonry Flat

### exterior/interior

net  
contents  
4 litres  
tinter included

A-LL7090204 2/13

#### WARNING

Read label before use. Keep out of reach of children. May cause an allergic skin reaction.

#### PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/VAPOURS. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Contaminated clothing should not be allowed out of the workplace. Wear protective clothing and gloves. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

#### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Wash skin with plenty of soap and water/shower. If skin irritation or rash occurs get medical advice/attention. Wash contaminated clothing before re-use.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. If present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: Mixed turpenes <2gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D74.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Masonry Flat is a premium quality, self-priming exterior waterborne coating designed for direct application to porous masonry surfaces. It imparts a unique and even matt side sheen finish with very low light reflectivity, which helps provide a uniform surface appearance on substrates such as cement render, brick and concrete block.

#### Preparation

- Ensure surfaces to be coated are in sound condition, dry, free from dirt, dust, loose material and salt. Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

- Waterblasting is the best surface preparation prior to coating of weathered surfaces.

- Ensure all wax or hydrocarbon resin curing membranes are either weathered off or removed by physical or chemical means. In the case of release agents being present, it is advisable to wash the entire surface with Altex P40 Cleaner, working the material into the substrate with stiff bristle brooms/brushes then rinse off with clean water before being allowed to dry on the substrate. DO NOT ALLOW Altex P40 Cleaner to dry on the substrate.

- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

- Efflorescence on masonry **must be treated** (see Data Sheet D83).

- Wherever oil and grease are present ensure the surface to be coated is thoroughly cleaned using Paint Prep and Housewash. Flush clean with water.

- For heavy contamination scrub down with Resene Emulsifiable Solvent Cleaner (see Data Sheet D804) then rinse clean with water.

- All loose powdery material must be removed. If waterblasting is not possible thoroughly wire brush.

- Old cementitious surfaces - if moss and mould are present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

Waterblasting at 21,000 kps (3000 psi) is the best surface preparation method prior to painting weathered cementitious surfaces. If waterblasting is not possible, remove all loose powdery material by thorough wire brushing. Allow to dry and apply one coat of Resene Sureseal (see Data Sheet D42).

- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- Fill cracks larger than 1mm in cementitious surfaces with a suitable elastomeric paintable sealant after priming with Resene Sureseal.

- Fill cracks and holes in interior walls before sealing.

- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

#### Priming

- The use of Resene Limelock (see Data Sheet D809) is highly recommended over recently applied cement render or freshly poured concrete surfaces.

- All surfaces that are in poor condition or affected by efflorescence or which are friable, powdery or chalky must be primed with Resene Sureseal.

- Sealants - special coating requirements of construction sealants and fillers should be followed.

- Sound cementitious surfaces do not normally require a primer. Resene Concrete Primer (see Data Sheet D405) must be used when coating smooth concrete surfaces.

#### Application

- Not recommended for roof areas or areas subject to ponding water.

- Not recommended for application to timber.

- Prepare and prime surface as per above.

- Brick, concrete block, unsealed fibrous cement sheet: Apply two coats of Resene Masonry Flat allowing two hours between coats. Thinning of the first coat by up to ten percent may be necessary on very porous surfaces.

- Cement render: On fresh cement render, apply one coat of Resene Limelock. Allow to dry for as minimum of two hours, longer in cold and damp environments. Apply two coats of Resene Masonry Flat

allowing two hours between coats.

- Off-form concrete, pre-cast concrete panels: Apply one coat of Resene Concrete Primer. Allow to dry for a minimum period of two hours, longer in cold and damp environments. Apply two coats of Resene Masonry Flat allowing two hours between coats.

- G.R.C panels: Apply Resene Vinyl Etch (see Data Sheet RA31) or Resene ConcreteSeal 3 in 1 (see Data Sheet D409). Apply two coats of Resene Masonry Flat allowing two hours between coats.

#### Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



# Resene

the paint the professionals use



Masonry Flat SDS



Masonry Flat TDS

**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email advice@resene.com.au or visit www.resene.com.au

**In New Zealand:** Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. This product complies with all the requirements of an APAS Paint Specification. Refer to the APAS Specification list on the Resene website for full details. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

### Quick check

**Use on:** Exterior and interior cementitious surfaces such as block and brickwork, concrete, fibre cement, G.R.C panels, monolithic building systems and solid plaster.

**Gloss level:** Flat.

**Coverage:** 12 square metres per litre per coat. Application rates vary depending upon choice of texture and application method.

**Dry time (minimum):** Touch dry 45 minutes. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 2 hours.

**Primer required:** Self priming on porous masonry, see Application.

**Usual number of coats:** Two, some colours may require additional coats.

**Application method:** Spray, synthetic fibre roller.

**Thinning and clean up:** Water.

**Colour range:** Selected Resene Total Colour System including B55252, Multi-finish, Whites & Neutrals and The Range.

**Before use:** Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



9 418022 1057826

WHITE