

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Mica Bond micaceous alkyd

A-LL57204 4/15

WARNING

Read label before use. Keep out of reach of children. May be harmful if swallowed. May be fatal if swallowed and enters airways. May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May be harmful if inhaled. May cause genetic defects. May cause cancer.

PRECAUTIONS

AVOID BREATHING DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Wear protective gloves, clothing, eye and face protection. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE, doctor, physician or first aider. Do NOT induce vomiting.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention or advice.

IF INHALED: Call a POISON CENTRE, doctor, physician or first aider if you feel unwell.

If exposed or concerned: Get medical advice/attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: Naphtha Petroleum heavy Hydrodesulfurised 160-320 gms/L, Solvent Naphtha Petroleum heavy aromatic 80-160 gms/L, Naphtha Petroleum light aromatic solvent 10-80 gms/L, Methyl Ethyl Ketoxime <5 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet RA71.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

In case of fire: Use foam, CO₂, dry chemical for extinction.

Engineered Coating Systems



DARK GREY

Resene Mica Bond is an oleoresinous based micaceous iron oxide pigmented coating modified with aluminium to provide lighter colours. Resene Mica Bond is highly resistant to weathering, and mildly corrosive conditions. Its pigmentation confers a very high degree of moisture vapour resistance due to its laminar type structure.

General

• Safety Data Sheet (SDS) is available and must be consulted before use.

• In every case it is recommended that the current Resene Data Sheet is consulted for product data and surface preparation information.

• This product must be thoroughly mixed before use. Efficient mixing at all stages requires power mixing with an air or explosion proof mixer until uniformly blended.

• Thinning requirements may vary according to application method, equipment and environmental conditions.

• If thinning is required thoroughly re-mix using the power mixer.

• Ensure correct wet film thickness is applied to achieve desired dry film thickness. Allowance must be made for any thinner added.

• Use of incorrect thinner may have an adverse effect on application and performance.

• Drying is affected by low temperatures and high humidity.

• The temperature of the substrate should be 3°C above the "Dew Point".

• The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.

• Following appropriate preparation, all surfaces must be dry and clean prior to painting.

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or Reseller for your nearest Technical Representative.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 - PAINT RELATED MATERIAL

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Link to SDS

Resene

the paint the professionals use



Mica Bond SDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

net contents 4 litres

Quick check

Name: Resene Mica Bond.

Generic type: Micaceous iron oxide pigmented alkyd.

Colours: Silver Grey, Medium Grey, Dark Grey.

Finish: Metallic.

Application method: Brush, roller or spray.

Recommended dry film thickness (D.F.T.): 50 microns per coat. Drying will be impaired if application dry film thickness exceeds 50 microns per coat.

Theoretical coverage: 11 square metres per litre at 50 microns D.F.T.

Dry time (minimum): 4 hours at 18°C. Drying is affected by low temperatures and high humidity.

Recoat time (minimum): 16 hours at 18°C.

Usual number of coats: 2.

Primer required: Yes.

Thinning and clean up: Mineral turps (brush/roller application). Resene Thinner No.9 (spray application).

Resene Data Sheet: RA71.

Limitations: When applied over zinc rich primers, a non-saponifiable barrier coat MUST first be applied. Do not apply directly to zinc rich surfaces i.e. bare galvanised steel, Zinalume or zinc rich primers. Dry time may be extended when applied directly over Resene Vinyl Etch Primer and Resene Armourcote 220/221.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.