

net contents 1 litre
tinter included

LL1870201 4/18

KEEP OUT OF REACH OF CHILDREN

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wash all exposed external body areas thoroughly after handling. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D313.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene

Non-Skid Deck & Path

exterior/interior



WHITE

Resene Non-Skid Deck & Path is a waterborne coating filled with graded silicas that can be tinted to a range of standard colours. Designed for use on both exterior and interior trafficable areas where a durable, tough, non-skid finish is desired.

Surface preparation

• Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

• Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812) or Resene Timber and Deck Wash for timber (see Data Sheet D813). If moss or mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• New concrete must be allowed to cure for a minimum of 28 days before acid etching. Efflorescence on concrete **must be treated** (see Data Sheet D83).

• Any timber that has been left exposed to weather for more than one week requires thorough sanding of the surface to remove damaged fibres and then application of Resene TimberLock (see Data Sheet D48) prior to priming.

• When recoating a surface previously coated with other than Resene Non-Skid Deck & Path, all old coatings must be removed by captive abrasive blasting or grinding. This treatment leaves a clean surface ready to be coated.

• When recoating a surface previously successfully coated with Resene Non-Skid Deck & Path, first acid etch any exposed bare concrete, then prime with Resene Non-Skid Deck & Path before recoating the cleaned surface or spot prime any exposed bitumen with Resene Membrane Roofing Primer (see Data Sheet D49) before recoating.

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Priming

• Dark colours used on exterior surfaces are likely to increase heat and stress on the surface and, depending on the substrate, may reduce its lifespan and increase the level of coating maintenance required to maintain an acceptable visual appearance. Resene CoolColours can be used on appropriate projects to assist with heat reflectance.

• When a CoolColour variant of this product is being used, it must be used with a primer coat of Resene Quick Dry white (see Data Sheet D45) or Resene Galvo-Prime (see Data Sheet D402) immediately below the Resene CoolColour topcoat for optimum performance. Refer to Resene

ColorShop or Reseller staff as to the most appropriate CoolColour system for your project.

• On bitumen apply one full coat of Resene Membrane Roofing Primer.
• Prime new unpainted timber with Resene Quick Dry or Resene Wood Primer (see Data Sheet D40). For hardwoods such as Kwila, Purple Heart or Green Heart, prime with Resene Wood Primer. Refer to Data Sheet D313 for timber priming details.

• For repaints of painted concrete, spot prime any bare concrete areas with Resene Concrete Primer (see Data Sheet D405).

Application

• Apply two full coats, allowing at least three hours between coats.

• Maintain good ventilation throughout the drying and curing period to ensure the coating is properly cured. Poor ventilation may inhibit curing and performance.

Maintenance

(after a minimum of four weeks' drying)

Use Resene Paint Prep and Housewash correctly diluted with water and a soft broom to clean down the surface.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



Non Skid Deck & Path SDS

Resene

the paint the professionals use



Non Skid Deck & Path TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.com.nz or visit www.resene.com.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA1, an accredited certification body. This product complies with all the requirements of an APAS Paint Specification. Refer to the APAS Specification list on the Resene website for full details. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Trafficable area surfaces where a non-skid finish is required.

Gloss level: Rough texture.

Coverage: 1st coat: 2-6 square metres per litre per coat, 2nd coat: 4-6 square metres per litre per coat.

Dry time (minimum): 1 hour at 17°C. Allow at least 24 hours before using area that has been coated. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity.

Recoat time (minimum): 3 hours.

Primer required: Dependent upon surface.

Usual number of coats: Two.

Application method: Generally a high solids roller is the recommended method of application. May also be applied by brush, roller, spray or squeegee.

Thinning and clean up: Water.

Colours: Standard colours from the Resene Decks, paths, driveways and recreational areas colour range, selected other Resene Total Colour System colours available on request.

Also available as Resene Non-Skid Deck & Path CoolColour to help reflect heat from exterior surfaces. Application of a Resene CoolColour will reflect more heat than the same colour made using non-cool pigmentation and reduce heat related stress on the substrate; it will not make the painted surface cool to touch. Check with Resene staff whether a Resene CoolColour is right for your project.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Material Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.