

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May be harmful if swallowed. Harmful if inhaled. Causes mild skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Harmful to aquatic life.

PRECAUTIONS

AVOID BREATHING MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off immediately all contaminated clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

If medical attention is required: have product container or label at hand.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: 1,2,4-Trimethyl Benzene 80-280 gms/L..

For cleaning of brushes/rollers freshly used for Resene Polythane (see Data Sheet D53). Will not remove hardened Resene Polythane.

SPILLS: Wear appropriate protective clothing. Eliminate all sources of ignition. Ventilate area, avoid breathing vapours. Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove. Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

IN CASE OF FIRE: Use foam, CO₂, dry chemical for extinction.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene**Polythane
Brush Cleaner**

net contents 1 litre

Equipment

Safety glasses with side shields, protective clothing and gloves (neoprene or butyl rubber).

Directions

Protect skin and eyes at all times with approved safety equipment.

1. Remove excess Resene Polythane using scraper.

2. Clean brush or roller immediately after painting by working vigorously with Resene Polythane Brush Cleaner.

3. Repeat procedure with fresh Resene Polythane Brush Cleaner until equipment is thoroughly clean.

N.B. Must not be used as a thinner for Resene Polythane.

Will not remove hardened Resene Polythane.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

**FLAMMABLE LIQUID
AND VAPOUR**

Keep away from heat, hot
surfaces, sparks, open flames and
other ignition sources.

For further painting advice and information, call
1800 738 383 (AUST), 0800 737 363 (NZ) or visit the
Resene website.



UN NO. 1263 – PAINT
RELATED MATERIAL.



Polythane Brush
Cleaner SDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.