

Resene ProSelect Clean

professional timber flooring finish
concentrate

makes over 10 litres

KEEP OUT OF REACH OF CHILDREN



9 418022 069904

net
contents
1 litre

LL2759001F 10/17

SAFETY PRECAUTIONS

Read label before use. Keep out reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.
Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

FIRST AID

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.
IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Continue rinsing. If eye irritation persists get medical advice or attention.

If medical advice is required have product container or label at hand.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING APPLICATION EQUIPMENT: Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene ProSelect Clean Concentrate is designed to be diluted with water before use. Diluted product is a low VOC, environmentally friendly and biodegradable cleaner for use on Resene ProSelect coated floors. Safe to use and leaves a streak free finish. Specifically designed to be used with a micro-fibre spray mop.

Important note: When cleaning coated hardwood timber floors, always follow the guidelines in the ATFA Caring for your Timber Floor brochure and the Resene ProSelect - Caring for Your Floor information, available from www.resene.com/proselect.

Mixing: Mix 1 part Resene ProSelect Clean Concentrate to 10 parts water (by volume). For particularly dirty floors mix a stronger solution of 1 part Resene ProSelect Clean Concentrate to 5 parts water (by volume).

Note: Diluted product should not be stored in large quantities for extended periods as it is more prone to bio-contamination once diluted. Mix amount required for job at hand.

Application: Simply vacuum or dry mop the floor to remove excess dirt, grit and dust.

Using a micro-fibre spray mop, spray/mist a small area of the floor and wipe in the direction of the grain. Allow to dry before walking on the clean surface. DO NOT wet mop the floor. For particularly stubborn dirty marks, spray directly onto the affected area and allow the cleaner to work for several minutes before wiping off with a micro-fibre cleaning pad.

Refer to www.resene.com/proselect or the Resene ProSelect Technical Data Booklet for more detailed information.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Resene ProSelect
info centre

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.co.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.