

Resene

ProSelect

Colour Concentrate

professional timber flooring finish

WARNING

KEEP OUT OF REACH OF CHILDREN



9 418022 069843

**DARK
BROWN**

net
contents
1 litre

LL2758101F 10/17

SAFETY PRECAUTIONS

Read label before use. Keep out reach of children. Causes mild skin irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Causes serious eye irritation.

PRECAUTIONS

AVOID BREATHING DUST AND FUMES. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists get medical advice or attention.

If medical advice is required have product container or label at hand.

If exposed or concerned get medical advice or attention.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: 3-Iodo-2-Propynyl Butyl Carbamate 1-10 gms/L, Propionic Acid, Ethoxylated, Alky Ethers 1-10 gms/L

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums.

Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING APPLICATION EQUIPMENT: Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Developed specifically for professional flooring contractors, Resene ProSelect Colour Concentrates use durable coloured pigments and are designed to be added to the Resene ProSelect Stain Base. Combinations of different colour concentrates allow a vast colour range to be achieved.

FOR PROFESSIONAL USE ONLY

Important note: All processes for hardwood timber floor coating from the initial consultation, with the client, through to final application/finishing and maintenance should follow the guidelines set out in the Australasian Timber Flooring Association (ATFA) Information Guide Manual and Web Site, www.atfa.com.au.

Mixing: Shake well before use. Add to Resene ProSelect Stain Base to achieve desired colour and strength. Shake or stir well until colour is even. Best used within 48 hours after adding colour concentrate to the Resene ProSelect Stain Base.

Dose rate: Typically 10% is suitable for most timbers. Up to 20% (by volume) can be added to achieve a stronger colour effect.

Clean up: Water.

Refer to www.resene.com/proselect or the Resene ProSelect Technical Data Booklet for more detailed information.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause standard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Resene ProSelect
info centre



Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207

Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045

Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.