

net contents 500ml

Must be mixed with the appropriate base.
Makes 5.5 litres when mixed with 5 litres
of Resene Qristal ClearFloor Base.

LL2480050H 11/10

WARNING

Read label before use. Keep out of reach of children. Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking. Causes mild skin irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful by inhalation. May be harmful if swallowed.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT BREATHE FUMES/ MISTS/ SPRAYS/ VAPOURS. DO NOT EAT, DRINK OR SMOKE WHILE USING. Avoid contact with eyes. Ensure adequate ventilation when using. Wear a positive-pressure air-supplied full-face respirator whilst spraying and until spray mist has been effectively dispersed. Store locked up in original or correctly labelled container, tightly closed, in a cool well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Ground/ bond container and receiving equipment. Use explosion proof electrical/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/ face protection. Wash thoroughly after handling. In case of inadequate ventilation, wear an air-fed respirator.

FIRST AID

IF MEDICAL ATTENTION IS REQUIRED HAVE CONTAINER OR LABEL AND SDS (Safety Data Sheet) AT HAND.

IF SWALLOWED: DO NOT induce vomiting. Rinse mouth. Seek medical advice.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove / take off contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/ shower. If skin irritation occurs get medical advice/ attention.

IF IN EYES: Hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes. Remove contact lenses, if present and easy to do.

If exposed or concerned: Call a POISON CENTRE.

AUST: NATIONAL POISONS CENTRE 131 126

or from the Resene Help Line 1800 738 383

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or from the Resene Help Line 0800 737 363

CONTAINS: Aliphatic isocyanate 0.15%.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D507.

SPILLS: Eliminate all sources of ignition and use approved protective equipment. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or run off into water ways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Remove paint from roller sleeve using a roller scraper and then brush/roll out as much paint as possible onto newspaper before washing out brushes or rollers with recommended clean up thinner. Do not allow washing residues to enter drains or run off into water ways. Refer to your local Council for disposal of dirty solvent borne thinners.

FIRE: Blanket flames with dry chemical, carbon dioxide or foam. Closed containers can explode when exposed to extreme heat.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Qristal ClearFloor 2K

waterborne flooring urethane

GLOSS HARDENER

interior



Quick check

Name: Resene Qristal ClearFloor 2K Gloss Hardener.

Mixing ratio: 10 parts base: 1 part Gloss Hardener.

Induction time: 10-15 minutes.

Pot life: 4 hours @ 18°C (DO NOT USE mixed product beyond pot life, mixed product will remain in a liquid state well beyond pot life)

Dry time: Tack free 1.5 hours @ 18°C. Drying is affected by low temperatures and high humidity.

Thinning: Do not thin, supplied at application viscosity.

Clean up: Warm water and detergent.

CONTAINS ISOCYANATES. When mixed with the correct base and sprayed, this PRODUCT MAY BE HARMFUL BY INHALATION. Do not breathe vapour or spray. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves, eye and face protection including suitable breathing protection such as an air-supplied respirator or hood.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 RESENE (NZ) or visit the Resene website.

Resene Qristal ClearFloor is a two pack waterborne urethane durable flooring finish designed to protect your wooden flooring and keep it looking its best for longer.

General

- Safety Data Sheet (SDS) is available and must be consulted before use.
- In every case it is recommended that the current Resene Data Sheet is consulted for product data and surface preparation information.
- This product comprises a Base and Hardener, which must be mixed in the required ratio using an air or explosion-proof power mixer before application. Mix each component separately before blending them together. Add the total contents of the Hardener container to the total contents of the Base container. Once uniformly mixed, allow to stand for the recommended induction time prior to re-mixing and use.
- Thinning requirements may vary according to application method, equipment and environmental conditions.
- If thinning is required add recommended thinner after components have been blended and thoroughly re-mix using the power mixer.
- Ensure correct wet film thickness is applied to achieve desired dry film thickness. Allowance must be made for any thinner added.
- Use of incorrect thinner may have an adverse effect on application and performance.
- Drying is affected by low temperatures and high humidity.
- Ensure that the mixed product is used within the stated pot life. The pot life of the mixed product is given for a specific temperature. Higher temperatures will reduce the pot life, conversely lower temperatures will increase it.
- The temperature of the substrate should be 3°C above the "Dew Point".
- The "Dew Point" requirement can be presumed to be satisfied if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.
- Following appropriate preparation, all surfaces must be dry and clean prior to painting.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or Reseller for your nearest Technical Representative.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

CAUTION

Do not tightly reseal quantities of leftover mixed product, as the mixed product generates carbon dioxide gas which can cause the lid of a tightly sealed can to pop with force. Leave the mixed material in a safe place for at least 48 hours for outgassing to be completed before sealing cans for disposal through a Resene PaintWise location or approved hazard waste site.

HIGHLY FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/open flames/hot surfaces.
No smoking.



UN NO. 1263 – PAINT RELATED MATERIAL

Resene

the paint the professionals use

In New Zealand: Resene Paints Limited
Vogel Street, Lower Hutt, PO Box 38-242, Wellington Mail Centre
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 785, Ashmore City, Queensland, 4214
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.