

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Roof and Metal Wash

concentrate

exterior/interior

**net
contents
1 litre**

LL846001F 5/13

WARNING

Read label before use. Keep out of reach of children. This material may be harmful if swallowed, inhaled or absorbed through the skin. Causes mild skin irritation. Causes eye irritation.

PRECAUTIONS

AVOID BREATHING VAPOUR. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.
Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wash thoroughly after use. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release to the environment.

FIRST AID

IF SWALLOWED: If ingested give water to dilute. Do not cause vomiting. Get medical attention without delay.

IF ON SKIN (or hair): If skin contact occurs wash skin thoroughly with soap and water. Do not scrub skin. If skin irritation occurs get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF INHALED: Remove to fresh air. **IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.**

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

For use in cleaning exterior surfaces.

For full technical instructions see Data Sheet D88.

CAUTION

- Do not add Resene Roof and Metal Wash to paint.
- Mild steel and aluminium are attacked by Resene Roof and Metal Wash and are unsuitable materials for either storage or application equipment.
- Do not allow the product to come into contact with plants, stormwater outlets, streams or animals. May kill aquatic life if allowed to enter the stormwater system. Divert all roof run-off to a sewer or alternative catchment system.

In Australia:

Resene Paints (Aust) Limited

7 Production Ave, PO Box 924, Beenleigh, Qld 4207

Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

Resene Roof and Metal Wash is the ideal pre-treatment for painted and unpainted galvanised steel and for general cleaning of any previously painted surface.

Preparation

• Resene Roof and Metal Wash is a specially formulated cleaning and degreasing agent. Recommended for all new and previously painted galvanised iron or Galvalume and as a general cleaner and pre-treatment for all repaints.

• Where moss and mould infestation exists use Resene Moss & Mould Killer (see Data Sheet D80) first. On painted surfaces mould looks like dirt and frequently the two cannot be visually distinguished. The most common species are black but others can be brown or green.

• This product may be used to clean a wide variety of surfaces. If the surface you propose to clean is not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

- Mix with water and apply by brush or spray.
- Wear adequate protection. Use overalls, gloves, eye protection and suitable footwear.
- Scrub vigorously using a nylon bristle broom or short, hard bristle scrubbing brush to remove all dirt, grease, mould and any loose flaking paint. Rinse with clean water.
- Use more concentrated mixes to clean more heavily soiled surfaces.

Resene

the paint the professionals use

In New Zealand:

Resene Paints Ltd

Vogel Street, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045

Phone 04 577 0500 Fax 04 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Quick check

Use on: All galvanised iron or Galvalume (painted or unpainted) and previously painted surfaces.

Appearance: Water thin liquid.

Mixing ratio: One part Resene Roof and Metal Wash to three parts clean water.

Usage (diluted mix): 10 square metres per litre per coat.

No. of applications: one.

Application method: Brush, knapsack, garden or conventional spray.

Thinning and clean up: Water.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Roof and Metal Wash SDS



Roof and Metal Wash TDS

