

# Resene

## SRG Grit

slip-resistant additive 500g

Avoid inhaling powder. Keep closed when not in use.

Resene SRG Grit is a proprietary blend of graded silicas to increase slip resistance of selected Resene floor coatings. May also be used to achieve a textured appearance in Resene Paint Effects limewashing.

**DANGER**

KEEP OUT OF REACH OF CHILDREN



LL84350F 5/14

**Warning:** Read label before use. May cause cancer through inhalation. Causes damage to organs through prolonged or repeated inhalation.

**Precautions:** DO NOT BREATHE DUSTS. Do not eat, drink or smoke while handling this product. Do not handle until all safety precautions have been read and understood. Store locked up. Use personal protective equipment as required. Wash thoroughly after handling.

**General:** Prepare and prime surface to be painted according to individual product recommendations (refer to appropriate Data Sheets for technical data and specifications prior to use of the floor coating chosen).

**Safety in use:** This product contains crystalline silica and may cause cancer by inhalation. Long term exposure to respirable silica dust may cause lung diseases. Irritating to eyes and respiratory systems. Danger of serious damage to health by prolonged exposure. Wear protective clothing including a dust mask. In case of contact with eyes, hold open and flood with water for at least 15 minutes. Get medical attention without delay. If exposed or concerned: call a POISON CENTRE or doctor/physician. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or

call Resene 1800 738 383. NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363. When disposing product, avoid generating airborne dust. Refer to local waste management authority.

**Mixing:** Avoid inhaling powder. Keep closed when not in use. Add 1 pack (500g) of Resene SRG Grit per litre of paint. Addition of higher levels of grit is not recommended due to adverse effects on product characteristics. If in doubt, trial a small patch before painting entire area. Mix thoroughly until perfectly homogeneous. Regular mixing during application is recommended. The addition of Resene SRG Grit will result in an increase in total paint volume of about 20%. As a result a large container for mixing is recommended.

**Application:** Mixed product is best applied by roller. Apply one coat of Resene SRG Grit modified coating followed by a second coat of unmodified product. Recoat times will be extended due to the thicker film.

**Coverage:** Coverage of grit modified coating can be up to 50% less than unmodified product. Due allowance must be made for this when estimating quantities.

**Contains:** Crystalline Silica (Quartz) 100%.

## MAY CAUSE CANCER IF INHALED

In Australia: Resene Paints (Aust) Limited, 7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960 Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited, Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600 Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.