

DANGER
KEEP OUT OF REACH OF CHILDREN

Resene

Silvalusta

bitumen coating

exterior

LL7630004 1/10

WARNING

Read label before use. Keep out of reach of children. This material may be harmful if swallowed, inhaled or absorbed through the skin, causes mild skin irritation, causes eye irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer by inhalation. May damage organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

AVOID BREATHING FUMES/MISTS/VAPOURS/SPRAYS. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Ensure all safety precautions are read and understood before handling. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Do not contaminate any water supply. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Store locked up. Wear protective gloves and eye/face protection. In case of inadequate ventilation, wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wash thoroughly after handling. Dispose of empty container safely. Clean up spillage. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Seek medical advice.
IF ON SKIN (or hair): Wash with plenty of soap and water; If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash before re-use.

IF IN EYE: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, call a POISON CENTRE or doctor/physician.

IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

If medical advice is needed, have product label or container at hand.

If exposed or concerned: Call a POISON CENTRE.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

Contains: Aromatic bitumen ingredients

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D36.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

FIRE: Use foam, carbon dioxide or dry chemical powder.



Resene Silvalusta is a solventborne black bitumen cut to brushing viscosity with the addition of a leafing grade aluminium flake.

Preparation

- Ensure surfaces to be coated are in sound condition, dry, free from dirt, dust, loose material and salt. Remove accumulated windblown salt by washing with clean water.

- Waterblasting is the best surface preparation prior to coating of weathered cementitious surfaces.

- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

- Efflorescence on masonry **must be treated** (see Data Sheet D83).

- Wherever oil and grease are present ensure the surface to be coated is thoroughly cleaned using Resene Roof Wash and Paint Cleaner (see Data Sheet D88). Flush clean with water.

- **All sanding dusts can be harmful and appropriate protection should be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos can be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred try a small area first or contact your local Resene ColorShop or Reseller.

Application

- Apply two coats allowing 24 hours between coats.

- Many coats can be applied for maximum protection with no shrinking or cracking of the film.

- Resene Silvalusta develops maximum brilliance after six weeks weathering.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/open flames/
hot surfaces. No smoking.

UN No. 1263 – Paint related material

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 785, Ashmore City, Queensland, 4214
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Cementitious and bituminous surfaces, galvanised steel, Zinalume and machinery. Not to be used as a lining for potable water tanks.

Gloss level: Matt.

Coverage: 15 square metres per litre per coat.

Dry time (minimum): One hour.

Recoat time (minimum): 24 hours. Drying is slowed by low temperatures and high humidity.

Primer required: No.

Usual number of coats: Two.

Application method: Brush, synthetic fibre roller or spray.

Thinning and clean up: Mineral turps.

Colour: Silver.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 RESENE (NZ) or visit the Resene website.